

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A030594
VIN: 555665

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Revolution Hybrid Drop Deck 48' Wide Spread Air (Model: HARHD12WSA)

Est. Wt.: 9300# +/- 3%

Length / Width: 48 feet x 102 inches
Suspension Type: Wide spread air
Deck Lengths: 10 feet front and 38 feet rear
Frame Rating: 80,000 lbs distributed
Flooring: Knurled extruded 3-1/8 aluminum, multi-hollow friction stir welded floor with 2 wood nailer strips
Side Rails: Revolution Technology – one piece aluminum extrusion
Stationary Chain Cargo Tie Downs: 15 pair - recessed in siderails
Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)
Rubrail: Integrated with side rail
Main Beams: Minimum grade 130 bottom flange ; one-piece web with aluminum top flange adapter
Kingpin: 18 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM standard
Bulkheads: None standard
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks
ABS: 4S/2M - no cable or tool
Axle Spread: 122 inches - set at rear
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 aluminum LVL One buffed wheels
Tires: 255/70R 22.5 16PR OEM standard
Tire Inflation System: None standard
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop
Suspension Detail: AANL23K Intraax air ride
Auto Glad Hand Dump: Installed
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle
Front and Rear Corners: Tapered aluminum
Electrical System: Exclusive Revolution Technology: LED: 5 lights/side, 3 rear recessed light bars, with 10 Year Comprehensive Electrical System Warranty
Paint: Black urethane on steel parts with Revolution decals
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Meets U.S. underride requirements
Mudflaps: 2 sets Revolution
Winch Track: Dual full-length integrated aluminum – double L design
Sliding Winches: 12 standard - without straps
Winch Straps: None standard
Dock Bumpers: 1 pair rubber on rear
Hubodometer: None standard
Registration Holder: None standard
Tool Box: None standard
VIN Plate: Standard US VIN plate

Estimated Weight **Est. Wt.: 9300# +/- 3%**

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.