





Resale Inventory
A030596
VIN: 63882

SALES RENTALS PARTS SERVICE			
Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | [@haletrailer](https://www.instagram.com/haletrailer)






800-232-6535 *FINANCING AVAILABLE

=====

We propose to furnish the following described equipment, material and services at prices, terms and delivery set forth below:

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 12.9 Units

STANDARD SPECIFICATIONS: CTSSF-45 (South Specs) (2022 Model)

p>Type: Peerless dual axle, transport semi-trailer, **45 degree front**

p>Design: Box design, flat floor, end dump, live floor

p>Construction: **Skin stressed .063 natural aluminum with aluminum exterior posts (14.5" centers), skins to extend to bottom of lower rail**

p>Unloading Time: Approximately 8 minutes

p>Capacity: 12.9 units (96 cu yd)

p>Dimensions: **45' long, 8' wide, 12'6" high**, 37" king pin location, 36" rear axle from rear of trailer

p>Tires: Eight (8) **11:00 x 24.5 radial tires**

p>Wheels: Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile **steel, Unimount**

p>Axles: 22,500# cap. , 71 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks

p>Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

p>A.B.S.: 2 sensor - 1 module

p>Suspension: Four spring three leaf tandem (**Hutch H9700T with slider**)

p>Landing Gear: Two speed, crank on driver's side (Holland Atlas 55), channel bracing

p>King Pin: Standard SAE, heat treated, **37" setting, 49" height, 3 I-beams with 5/16" plate**

p>Cross Sills & Decking: **Hallco 7/32"**, 3.0" cylinders, 24" wear strips (one end) **4" Jr I-Beams on 12" centers** with aluminum sub-deck,

p>Top: Flat design, open top, single center tie

p>Top Cover: **Shur-lok roll over tarp, black in color, rear crank, 6" arched tarp bows, Flex-handle and telescoping pole, handles on both sides**

p>Rear Door: Full opening, **side hinged, solid freight door with four (4) latches, low mount**



Dump Stands: Two (2) blades at rear for standard Peerless backstop

Screens: **Safety screens on front and under drive**

Ladders: **One located at front and one located at rear**

Rope Hooks: None

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt, air and light plugs on front center

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights

Reflectors: Legal DOT

Paint: Aluminum natural, **steel components primed and painted BLACK**

Weight: Approximately 13,700#

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.