

Length	30'	1		Body	
Width	96" INBOARD	Tarp	NONE	Accessories	
Side Height	64" SOLID	Bow Holders	NONE		
Top Rail	9" DUMP	Tarp Bows	NONE		
Side Matl-front	4'100 WALL	Tarp Basket	NONE		
-middle	20'140 WALL	Tarp Hooks	NONE		TAILGATE
-rear	6'180 WALL	Bulkhead Mat'l	3/16" (10)	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	D/S-MANDOOR	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Slope	NONE
		Body Fenders	18"	Hinges	OVERSLUNG
Crsmbr Spacing	12"	Ladders (Out)	D/S-REAR	Side Swing	YES -W/ IGC P/S HINGE
haranni di landan anna akan mala Diamenta da Diamenta	ыынананынавачоооргашчаныргомириалданымучсиячогоорг	, portuguis (1900 per	инин-жикиштөн.шөөниктөникалин-энц-ооц-оорганик-соорганикалын-	Gateseal	RUBBER
Floor Options	STUB LONGITUDINALS	Inside	NONE		
Community to the Company of the Community	na-minute terraminus prauminis postanines satori	the ornander (dominore).	оокашины воспояния писькамон компинок ополиться	Safety Latch	ONE EACH SIDE
		Shovel Hgr	D/S-FRAME	пантина полина п	
Tailgate Control	AIR / FRAME + ELEC CC (4)	İ		Coal/Grain Door	NONE
Body Pkg	NONE	Light Panel	FULL - LED; X=LED B/U LIGHTS	Ī	
Options			OOOX ooo XOOO (11)	Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED - 5 PR TOP & BOTTOM	Gate Options	
Mudflaps	STD + ACROSS REAR (1)	MMTS	BELOW RAIL -OVAL LED	**************************************	
	CHASSIS	Apron	NONE		((44.1.1.4.1.4.1.1.4.1.4.1.1.1.1.1.4.1.4
		•	CHASSIS SPECIFICATIONS		
Model	TRIAXLE-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM	1	<b>-</b> 9,	Landing Gear	2 SPEED JOST AX150
Length	31'				D/S CRANK
Width	96"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-250 (2)(10)	I		l lacoio Ligino	NONE
Chassis Neck	STD	i		Elec Coupler	7 WAY+ISO 7 WAY LABELED
King Pin Setting	18"	Distance:		anning and a second	AUXILIARY"
5th Whi Plate	3/8" W/ 3/8"X 3" X 7" MOUNT	From:		Hyd Tank	NONE
5th Whi Ht	49"	1		Hyd Hose Fitting	WINGNUT
Overhang	6"	Controls		Hyd Hose Length	108"
Rear Axle Setting	21.5"	l		Tow Hooks	TWO-ONE EACH SIDE
K/P To Rear Axle	332.5"	<u>.                                    </u>		Paint	BLACK SOFTCOAT
Suspension	AAT30K/E3-2 L LIFT-E1(3)(5)	Location		. 41116 	DE CONTROL TOWN
Susp Control	FRAME + ELEC CC (4)(9)	Axle(s)			NONE
Susp Spacing	52" - 52" (6)	UVIG(2)		.de	
Susp Options	GALVANIZED HANGERS	Accessories		Chassis	CHASSIS REAR CM:TAPERED
	AIR	Accessories			W/ DIAMOND PLATE COVER
Springs	TP - HXL-5	  Prokon		Options:	VVI DIAWIOND PLATE COVER
Axles		Brakes			
Accessories	NONE	Drums			
Brakes	16-1/2" x 7"	Hubs			TIDELANYORDO MELATICA
Drums	CAST	l ban i			TIREMAXX PRO INFLATION
Hubs	10 STUD STEEL	Wheels		***************************************	SYSTEM ALL AXLES
	GREASED	<u> </u>			
Wheels	8.25 x 24.5 12HP	Tires			
Tires	11R 24.5 R268 ECOPIA 16PLY	/ BS			

## REMARKS:

- 1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER. INSTALL 4" FORWARD OF STANDARD POSITION.
- 2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.
- 3. AIR IN THE BOX OIL FILLED GAUGE (KG) (FLUSH) ON FRONT CHASSIS CROSSMEMBER.
- 4. WIRED TO AUXILIARY ISO 7 WAY PLUG SUSPENSION EXHAUST WIRED TO AUX ISO 7 WAY PLUG
- 5. HEIGHT CONTROL VALVE ON AXLE #2.
- 6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC **POWER TO RAISE** (WIRED TO AUX 7 WAY PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
- 7. ALL FRAME SWITCHES TO BE IN **BOX** ON D/S NEAR LANDING GEAR.
- 8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
- 9. NO CROSSOVER KITS WEIGHT: 13,669
- 10. NO OUTSIDE ACCESS OR FLAP ON OUTSIDE OF BULKHEAD FOR HOIST-ONLY ON INSIDE DOGHOUSE.
- 11. LED BACK UP LIGHTS WIRED TO AUXILIARY ISO 7 WAY PLUG