

HALE TRAILER BRAKE & WHEEL



A030975
VIN: 572843

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894
Baltimore, MD: 888-601-7500
Concord, NC: 800-438-2250
Delmar, DE: 866-486-1400
Des Moines, IA: 888-673-5011
Elkton, MD: 800-544-7127
Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944
Portland, ME: 800-325-4253
Raleigh, NC: 833-418-9777
Scranton, PA: 800-569-1400
Springfield, MA: 800-854-5306
Voorhees, NJ: 866-315-0235
Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Magnitude 55MXT - Extendable Deck, Modular Tridem Bogie (Model: MAG55MXT)

Est. Wt.: 27110# +/- 3%

Commercial Terms: Ex Works- Springville, AL, USA

Capacity: 55 tons in 16 ft. 0 in. (closed position) length with fourth axle close coupled or single axle stinger--GAWR and tire ratings determine legal payloads

Load Base: Sixteen foot rigid 2 point load centered in deck when deck is fully closed. Note: Only rigid self supporting loads when deck is open. The load base becomes the open deck minus 2 ft.

Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges

Gooseneck Design: Hydraulic removable non ground bearing design

Loaded Fifth Wheel Height: 50 in. nominal with 5 ride height positions

Swing Radius: 102 in. (11 ft. 11 in. overall gooseneck length)

Alternate Kingpin: Removable kingpin at 102 in. radius

Flip Box: None

Power Source: Set up for wet line operation

Electrical receptacle: J560 seven pin connector

Deck Design: Flat Level Telescopic Deck Design

Deck Length: 29 feet clear deck length (retracted); 50 feet (extended) ** NOTE: Trailer is over 53 feet in length

Loaded deck height: Deck: 20 in. Ground Clearance: 6 in.

Flooring: 2 inch nominal Apitong wood

Front ramps: None, front of deck sloped top down to assist in loading with traction cleats

Front bogie ramp: Included

Extension Brackets: (13) pair removable swing type; (1) pair removable hook on type

Deck to Bogie Connection: Modular

Other Deck Specifications: Telescopic Deck Design Crossmember Spacing outboard mainbeams 11.75 in c/c

Number of Axles: 3

Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.

Axle Spread: 54-1/2 in. (between axles)

Dust Shields: None

Brakes: 16-1/2 in. x 7 in. with 5.5 in. autoslacks; heavy duty brake drums; outboard mount

Suspension: Air ride

First Axle Lift: Chain Lift

Third Axle Lift: Air lift

Compatibility: Designed to accept 55/60 rear axle, spreader and/or 23 inch flip box -

Tires: 275/70R 22.5 OEM Standard

Wheels: 8.25 x 22.5 steel disc; hub-piloted

Bolsters: Recessed load bearing between all axles and rear of last axle

Covered Rear Bogie: None

Rear Bogie Height: 40 7/8 in.

Boom Trough: V style boom trough with bolt-in V pan

Mechanical Ride Height Control: Mechanical ride height control valve (Whittle Style)

Manual Dump Valve: Manual Dump Valve (Push Pull)

Bumper: Heavy duty v-style rear bumper

Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes

Standard Deck

1/6

Hyd / Hook

Spreader Bar: None

Flip Axle: None

Dust Shields on Flip Axle: None

Paint: Fontaine black polyurethane enamel

Lash Rings: 13 pair, 26 total - 29 ft. deck (10 pair, 20 total - 26 ft. deck)

Flag Holders: Flag holders 3 pair total, at front of deck, rear deck, and on rear bumper

Accent Package: None

Liquid Filled Gauge: None

VIN Plate: Bilingual VIN plate

Registration/Document Holder: Install registration/document holder

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.