





A031138
VIN: 180960

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-------------------|--------------|------------------|--------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer






800-232-6535
*FINANCING AVAILABLE

Trailer Model:

Kalyn SlideMAXX TT-2A-35T-51

| | | |
|---|----------------------|---|
| Net Capacity: | 35 Tons | 70,000 lbs. Distributed 50,000 lbs. Concentrated in 10' |
| Nominal: | 51 feet OAL | |
| | 8 feet 6 inches Wide | |
| GOOSENECK: | | |
| 9'-6" Gooseneck Length with cut-outs for flush mount transition lights | | |
| 48" Loaded 5th Wheel Height, 18" Kingpin Setting | | |
| 86" Swing Radius | | |
| 20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable | | |
| LED Work light bar on winch | | |
| Trailer Operation: Wet kit (3/4" Hydraulic Quick Couplings) | | |
| Integrated Top-Mounted Tool Boxes in Neck | | |
| Landing gear: 2- Speed | | |
| DECK: | | |
| Nominal Deck Length: | 40 feet | |
| Nominal Deck Width: | 102 in | |
| Loaded Deck Height: | 38 in | |
| 4 Beam design: 100,000 psi yield flanges & 80,000 psi yield web minimum | | |
| 15" tall main beams and 15" tall side rails | | |
| 3" I-beam cross members on 9" Centers, 1-3/8" Apitong Deck(full width) | | |
| Double Key Hole Chain Slots in Upper Flange on 36" Centers | | |
| Double Key Hole Chain Slots Along Center of Deck on 36" Centers | | |
| Traction Plate Over Wood Rear Approach w/ tiedowns | | |
| 6' Upper Deck Ramp (air operated) | | |
| SUSPENSION: | | |
| 25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles | | |
| 50" axle spacing 71" track | | |
| 12-1/4" x 7-1/2" Brakes ABS Module: 4S2M | | |
| Auto Slack Adjusters and Spring Brakes on all Axles | | |
| 6.75 x 17.5 Hub Piloted Disc Wheels | | |
| 235/75 R 17.5 16PR Tires Manual Dump Valve | | |
| Suspension: Ridewell or Equivalent Air ride Air Ride | | |
| Alignment Bracket for Sliding Suspension | | |
| GENERAL: | | |
| 12 Volt System with 7 way Sealed Harness | | |
| DOT Rubber Mounted Sealed Beam LED Lights | | |
| Epoxy Primer & Black Polyurethane Paint | | |
| 6-Function Wireless Remote for Winch/ travel / lift | | |
| Heavy Duty DOT Approved Bumper | | |
| Red & White Conspicuity tape KS Mud Flaps | | |
| LED marker lights every 3' each side including mid turn | | |
| Strobe light with toggle switch on rear | | |
| High Visibility Light Pkg - 1 pr. Swing out side turn / flashing lights | | |

| | |
|--------------------------------|---|
| Models | Alternating Stake Pockets & Chain Slots |
| 2 Axle, 35 Ton, 51' Model | Aluminum Wheels Outside all Axles |
| Options | <input checked="" type="radio"/> OEM 235/75 R 17.5 16PR Tires price is mounted on selected wheels |
| AirWeigh Load Scales | "GUN METAL GRAY" Paint, Seal Deck for Baltimore Tow |
| Tire Inflation System | |
| Central Lube - 18 Point Manual | |
| Bolt-on Step & Handle | |
| Underglow | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.