

HALE

TRAILER

BRAKE & WHEEL



A031702
VIN: 44906

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: T2-35CC-HRG-T1

Capacity in tons: 35

1. GOOSENECK

Gooseneck design
Loaded 5th wheel height
Swing radius
Support cylinder
Power source
Gooseneck locks
Electrical receptacle
Coverplate
Additional gooseneck specifications

Ratchet
51"
90"
Hydraulically operated with 4" x 3" cylinder mount cross member
Hydraulic couplings: 3/4" fixed at front with piping for wet line
Ratchet
Seven pin connector
Aluminum
1) Full penetration weld on gooseneck gusset
2) Base pivot tube reinforcement
3) Ratchet pivot shaft collar

2. DECK

Deck section design
Deck section length
Deck section width
Loaded road clearance
Loaded deck height
Flooring
Gooseneck/deck connection
Deck/rear bridge connection
Outriggers
Reinforced top flange of sidemember
Slope front of deck top down
Heavy duty front folding ramps
Expanded metal
Additional deck specifications

Four beam
24'-0" (23'-6" clear)
8'-6"
6"
22"
1-1/2" apitong secured with deck screws; no lumber between mainbeams
Horizontal pin and plate with remote lock
Fixed/welded
12" swinging/removable with double hook-on at front of deck
None
With smoothplate & traction bars
32" wood filled
Between mainbeams 1st deck section at front
None

3. REAR BRIDGE

Rear bridge section width
Loaded rear bridge height
Number of axles
Axle spacing
Axle capacity
Brakes
Anti-lock brake system
Wheels

8'-6"
40"
2
54"
25,000# GAWR = 20,280#
16-1/2" x 7" air actuated with spring brakes on one axle
Two (2) sensor, one (1) modulator system
Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished
Eight (8) 255/70R22.5 (H) 16PR radials
Ridewell air
Manual
New style +3", -3" with override chains on all axles
1) Liquid filled air gauge mounted in 2nd axle curb side air bag with decal

Tires
Suspension
Exhaust Valve
Manual raising & lowering (+3"/-3")
Suspension options

Rear Bridge Center Section	Boom well, cross members recessed - recess 1st member additionally
Wide center bolster	With chain slots and flagholder slots
Rear half bolster	Rear of axle 2
Front bridge ramp	Sloped to deck outboard of mainbeams with smoothplate and traction bars
Fenders	1/4" floor plate over tires only
Connections for future removable axle	None
Additional rear bridge specifications	1) Omit 1st cross member in rear bridge section (shock mount cross member) for open boom well
4. GENERAL	
Lights and wiring	12 volt system with the following: All lights to be L.E.D. including mid-turn, excluding license plate light All marker/I.D. lights to be 3/4" bullet style 1 marker each side of gooseneck at front 3 marker lights each side of deck including mid-turn strobe lights and switch at rear Battery back-up system with switch at rear to flash all marker/tail lights and strobe lights, battery mounted in battery box.
Paint	Valspar standard Talbert black, R-Cure 800 series paint with ZINC Rich primer
Lash rings	12 Total 4 each side of deck (bent style), 8 total 1 each bolster and half bolster end (straight style), 4 total
Estimated empty weight	15,550#
Additional general specifications	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.