



A031866 VIN: 5A2591

SALES | RENTALS | PARTS Allentown, PA: 800-383-8894 Jacksonville, FL: Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: Scranton, PA: 866-486-1400 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Voorhees, NJ: 866-315-0235 Elkton, MD: 800-544-7127

HaleTrailer.com | @haletrailer (f) (m (g) (m (g) 200-232-6535) *FINANCING AVAILABLE

	800-232-6535 *FINANCING AVAILABLE
RENEGADE XN20 (Model: RENL	XT40NF*834542)
	General
SKU	RENLXT40NF*834542
Capacity	40 Tons in 16-foot Length - GAWR and GVWR Determine Legal Loads
Length (Trailer Only)	55 feet 1 inches (closed); 89 feet 6 inches
Width	8 feet 6 inches
Compatibility	Designed to Accept Optional Third Flip Axle
Accent Package	Stainless Steel Bumper Insert
Weight	Est. Configured Weight: 24837# +/- 3%
	Gooseneck
Gooseneck Design	Narrow Hydraulic Removable Non-Ground Bearing - Swing Radius of 102 inches (11 feet 11 inches overall Gooseneck Length) Set Up for Wetline Operation
Loaded Fifth Wheel Height	50-inch Nominal Loaded Fifth Wheel Height with 5 Ride Height Positions
Power Source	Set Up for Wet Line Operation
VIN Plate	Bilingual VIN Plate
Registration/Document Holder	Install Registration/Document Holder
	Deck
	All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000#
Framework	Webs
Deck Design	Flat Level Deck Design
Deck Length	34 feet 0 inches Clear Deck Length (closed) - 60 feet 0 inches (open) ** Trailer Overall Length is 55 feet**
Loaded Deck Height	20 inches with 6 inches Ground Clearance
Crossmembers	On 24 inch Centers
Deck Lock	First 5 Spaced Approx. 12 inches; Others Every 50 inches
Flooring	1 3/8 inch Nominal Wood (Full Width)
Recessed Floor Mounted D-Ring	
Package	None
Front Ramps	None - Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats
Extension Brackets	Outriggers - 17 Pair - 34 Total Removable Swing Type, 1 Pair - 2 Total Removable Hook-On Type
	Rear Bridge: General
Front Bogie Ramp	Sloped Steel Bogie Ramp (Full Width)
Mini Boom Trough and Traction Cleats	None
Deck to Bogie Connection	Fixed
Covered Rear Bogie	Rear Bogie Platform with 1 1/8 inch Wood Floor
Rear Bogie Height	41 inches
Connections for Future Axle	
Attachment	Air and Electrical Connections to Go Along with Connecting Ears
	Rear Bridge: Axles
Number of Axles	2
Axle Capacity	25,000 lb. Nominal Capacity Per Axle - NOTE: GAWR Determined By Suspension Type, Brakes, Tires and Other Components
Axle Spread	54.5 inches (Between Axles)
Spring Brakes	Spring Brakes (2 Axles)
Dust Shield	None
Hubodometer	None
	Rear Bridge: Suspension
Suspension	Air Ride with Automatic Controls
ABS	4S/2M System without Diagnostic Tool and Cable
Chain Lift	Chain Lift On First Axle
Ride Height Control	Automatic/Manual Raise/Lower Control
Liquid Filled Gauge	Included
Load Scale	None
	•



Detailed Specifications

Wheels and Tires	
Wheels	8.25 x 22.5 LvL One Buffed Outside/Steel Inside - Hub-Piloted
Tires	255/70R 22.5 H Ply OEM Standard
Inflation	None
	Lighting
Electrical System	DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes
Tail Lights	3 Tail Light Package
Marker Lights	7 Marker Lights Per Side Including Mid-Turn
Special	Not Available on This Model
Electrical Receptacle	J560 7-Pin Connector
	Paint
Paint	Fontaine Black Polyurethane Enamel
	Miscellaneous
Lash Rings	12 Pair - 24 Total
Flag Holders	2 Pair Flag Holders
	Additional Options
Flip Axle	None
Dust Shields on Flip Axle	None
RENEGADE XN20	



RENEGADE XN20 Base Model (Note: Options not shown)



