



A032450 VIN: A6874

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: Raleigh, NC 833-418-9777 800-438-2250 Delmar, DE: 800-569-1400 866-486-1400 Scranton, PA: Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f y 庙 🎯 🛗

800-232-6535 *FINANCING AVAILABLE

Intermediate Axle 60-90 (Model: MAG IA 6090 60)	
AXM609060IS	
AAM00900015	Est. Wt.: 3,780# +/- 3%
TRAILER - GENERAL	ESL. WL.: 3,780# +/- 3%
Compatibility: Magnitude 60HD, 65, 75 and 80 ton Attach to A6871	
Length: 5 feet 1 inches	
Width: 8 feet 6 inches	
Width: 8 feet 6 filcries AXLES	
Number of Axles: 1 axle	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined	
by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields on Flip Axle: None	
SUSPENSION	
Suspension: Air ride	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 Outer LvL One buffed/steel disc inside - hub-piloted	1
Tires: 275/70R 22.5 OEM Standard	1
Hubodometer: None Standard	
Tire Inflation: None Installed	
REAR BRIDGE	
Boom Trough: V-style boom trough with bolt-in V pan	1
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Bumper: Heavy duty V-style rear bumper	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush	
mounted amber strobes	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 1 pair - 2 total	
Flag Holders: Flag holders - 1 pair located on rear bumper	
VIN Plate: Bilingual VIN plate	