

HALE

TRAILER

BRAKE & WHEEL



A032452
VIN: A6876

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

MAGNITUDE 80 MDSR 3+3 Modular (Drop Side Rail Deck) Tridem Bogie (Model: MAGNITUDE 80 MDSR)

MAG80***MD930603/FBM1118***H

Est. Wt.: 40,128# +/- 3%

TRAILER - GENERAL

Capacity: 80 tons in 16ft/ 70 tons in 12 ft as a 3+3
Load Base: 16-foot rigid 2-point load centered in deck
Length (Trailer Only): 58 feet 4 inches (with standard deck length)
Width: 9 feet (DECK ONLY)
Compatibility: 60/90 intermediate axle, 60/90 flip axle, EQ3, and/or 111 inch flip box

GOOSENECK

Gooseneck Design: Hydraulic removable non-ground bearing design with 5 inch hooks; 237 inches total including flip box (23ft 4 in feet overall gooseneck length)
Loaded Fifth Wheel Height: 50 inches nominal with 6 ride height positions (Dual arm pawls)
Kingpin: Removable kingpin at 126/114 inch radius
Power Source: 13 HP (min.) Gasoline powered auxiliary power unit
VIN Plate: Bilingual VIN plate
Registration/Document Holder: Registration/document holder installed
Hydraulic Fittings: OEM Standard 1/2 inch

DECK

Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges
Deck Design: Drop Side Rail (DSR) design - 30 feet clear deck length **Note: OAL with this option is 60 feet 4 inches with standard axle spread
Loaded deck height: 16 inches at side rails, 24 inches at main beams with 6 inches of ground clearance
Flooring: 2 1/4 inch nominal wood - side rails only
Front ramps: None, front of deck sloped top down to assist in loading with traction cleats
Front bogie ramp: Included (bolt-on/removable)
Extension Brackets: 16 pair - 32 total heavy duty removable hook on type
Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers
Hammer Plate: Hammer Plate installed over recessed crossmembers. Preforated plate under hammer plate forming two storage areas. 2 pair lashing ring located in last two deck sections.

REAR BRIDGE

Front Bogie Ramp: Included (bolt-on/removable)
Boom Trough: V-style boom trough with bolt-in V pan
Deck to Bogie Connection: Modular pin & plate design with 6in pins
Bolsters: Load bearing between all axles and rear of last axle
Covered Rear Bogie: None
Rear Bogie Height: 43 inches to top flanges- 39 inches to top of bolsters
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears
Air Operated Pins: None Standard

AXLES

Number of Axles: 6 Total - 3 Trailer, 1 EQ3 Axle, 1 Intermediate Flip, 1 Rear Flip	
Rear Bogie Axle Configuration: 3 axles (Tridem)	
Axle Capacity: 30,000 lb. capacity on each trailer axles 25,000 lb nominal capacity each all other axles NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: None	
SUSPENSION	
Suspension: Air ride	
ABS: None required	
Chain Lift: First Axle (acts as limit chains)	
Override Chains: Override Chains Axle 2 & 3	
Third Axle Lift: Air lift installed on third axle	
Ride Height Control: 7-position mechanical ride height control system	
Dump Valve: Manual Dump Valve (Push Pull)	
Liquid Filled Gauge: None	
First Axle Lift: Chain Lift	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted	
Tires: 275/70R 22.5 OEM Standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Tail Lights: 3 tail light package	
Electrical Receptacle: J560 7-pin connector	
Marker Lights: 3 marker lights per side including mid turn	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 14 pair - 28 total	
Flag Holders: 2 pair flag holders	
AVAILABLE COMPONENTS	
Spreader: None included	
Flipbox: 111 inch hydraulic flipbox Serial Number A6877	
Flip Axle (Intermediate): None included	
Flip Axle (Rear): None included	
Dust Shields: None	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.