

HALE

TRAILER

BRAKE & WHEEL



A032455
VIN: A6880

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Rear Axle 60-90 Only available in 60" spread (Model: MAG FA 6090 60)	
AXM609060RS	Est. Wt.: 3,270# +/- 3%
TRAILER - GENERAL	
Compatibility: Magnitude 60HD, 65, 75 and 80 ton Attach to A6876	
Width: 8 feet 6 inches	
AXLES	
Number of Axles: 1 axle	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields on Flip Axle: None	
SUSPENSION	
Suspension: Air ride	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 Outer LVL One buffed/steel disc inside - hub-piloted	
Tires: 275/70R 22.5 OEM Standard	
Tire Inflation: None Installed	
REAR BRIDGE	
Boom Trough: V-style boom trough with bolt-in V pan	
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Bumper: Heavy duty V-style rear bumper	
Accent Package: None	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted amber strobes	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 1 pair - 2 total	
Flag Holders: Flag holders - 1 pair located on rear bumper	
VIN Plate: Bilingual VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.