



A032620 VIN: 025418

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA: Little Rock, AR: 833-424-8944 800-383-8894 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: Walpole, MA: 800-854-5310 800-828-3055

haletrailer.com | @haletrailer f 🕑 🛅 🎯 🔠

800-232-6535

**535** \*FINANCING AVAILABLE

## XL 180 DOUBLE GOOSENECK EXPANDABLE

**OVERALL LENGTH** 

OVERALL WIDTH 144" TO 240"

CAPACITY 180,000 LB DISTRIBUTED

WEIGHT +/- 3% 44,480 LB

FRONT GOOSENECK

LENGTH 24' 7 3/4" COLLAPSED LENGTH

KINGPIN SETTING 16", 3.5" KING PIN

SWING CLEARANCE 238"

5TH WHEEL HEIGHT 49"

DECKING NONE

CYLINDERS DUAL POSITION FOR CYLINDERS

HYDRAULIC HAT BOX IN GOOSENECK WITH 36" OF LIFT

2 EXPANDABLE CROSS BRACES WITH INDIVIDUAL ADJUSTMENT CYLINDERS- 1 EXPANDABLE GATE

HONDA IGX SCU W/ REMOTE START

1 SET OF GROTE TRILLIANT WORK LIGHT ON TOP OF HEADER BEAM, 1 SET ON POWER TOWER

(7) FUNCTION WIRELESS REMOTE (REMOTE START FOR SCU, CROSS BRACES, HAT BOX ON TRAILER)

MANUAL HYDRAULIC CONTROLS FOR GOOSENECK OPERATION ON DRIVER SIDE

( 3 ) PAIR OF FLAT D-RINGS ON TOP FLANGE OF THE GOOSENECK, ( 1 ) ON REAR OF BASE

(2) ON TOP FOR BALANCE LIFTING

**MAIN DECK** 

**CROSSMEMBER** 

LENGTH 30' HYDRAULIC EXPANDABLE DECK FROM 12' WIDE TO 20' WIDE ( OUTSIDE TO OUTSIDE )

(10'2" TO 18'2" INSIDE TO INSIDE)

LOADED DECK HEIGHT 28" LOADED OUTER BEAMS & 8" LOADED TOP OF CROSSMEMBERS IN LOWEST SETTING

**DECKING** NONE

(6) 4" X 12" FAB EXPANDABLE CROSSMEMBERS - BOLT ON REVERSABLE WITH HOLES 16" O/C

CROSSMEBERS TO HAVE 3" INCREMENT ADJUSTMENT

CROSSMEMBERS RATED FOR 30KLBS EACH WITH LOAD SUPPORTED TO OUTSIDE

**BEAMS** (2) 24" PERIMETER FRAME BEAMS

**D-RINGS** (10) PER SIDE ON THE OUTSIDE, (1) ON EACH CORNER ON THE INSIDE

SHIM STORAGE

REAR GOOSENECK

**LENGTH** 24' 7 3/4" COLLAPSED LENGTH

KINGPIN SETTING ROCKER BOLSTER CONNECTION FOR DOLLY

SWING CLEARANCE 238"

5TH WHEEL HEIGHT 49"

DECKING NONE

**HAT BOX** POWER TOWER HAT BOX WITH 36" OF TRAVEL

CYLINDERS DUAL POSITION FOR CYLINDERS

2 EXPANDABLE CROSS BRACES WITH INDIVIDUAL ADJUSTMENT CYLINDERS- 1 EXPANDABLE GATE

HONDA IGX SCU W/ REMOTE START

(10) FUNCTION WIRELESS REMOTE (REMOTE START FOR SCU, CROSS BRACES, HAT BOX, STEERING ON DOLLY)

MANUAL HYDRAULIC CONTROLS FOR REAR GOOSENECK IN GOOSENECK CONTROL BOX (  $\bf 3$  ) PAIR OF FLAT D-RINGS ON TOP FLANGE OF THE GOOSENECK, (  $\bf 1$  ) ON REAR OF BASE

(2) ON TOP FOR BALANCE LIFTING

**ELECTRICAL** 12V SEALED GROTE SYSTEM

1 SET OF GROTE TRILLIANT WORK LIGHT ON TOP OF HEADER BEAM, 1 SET ON POWER TOWER

PAINT BLACK

**ADDITIONAL** 

(2) PAIR OF FLAG HOLDERS (ONE PAIR EACH END OF DECK)

NECKS ABLE TO HOOK TOGETHER

CLEARANCE LIGHT, MIDTURN, AND STROBE LIGHT ON THE BASE OF THE NECKS 3' FROM BOTTOM

FLIP DOWN LADDER ON ROADSIDE OF EACH GOOSENECK REMOTE GREASE LINES FOR PINS ON GOOSENECKS

GOOSENECK HEIGHT MUST BE UNDER 9' 10" RED/GREEN SCU ON/OFF INDICATOR LIGHT

EXPANDABLES GATES HAVE INDICATORS ON THE OPENINGS

QUOTE 100 JPS, 180 DGE, 6 AXLE DOLLY, (5, 10, 15, 25 DEX)

AMERICAN HEAVY HAULER