

# HALE

## TRAILER

### BRAKE & WHEEL



**A032650**  
**VIN: 025575**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	<b>800-383-8894</b>	<b>Little Rock, AR:</b>	<b>833-424-8944</b>
<b>Baltimore, MD:</b>	<b>888-601-7500</b>	<b>Portland, ME:</b>	<b>800-325-4253</b>
<b>Concord, NC:</b>	<b>800-438-2250</b>	<b>Raleigh, NC:</b>	<b>833-418-9777</b>
<b>Delmar, DE:</b>	<b>866-486-1400</b>	<b>Scranton, PA:</b>	<b>800-569-1400</b>
<b>Des Moines, IA:</b>	<b>888-673-5011</b>	<b>Springfield, MA:</b>	<b>800-854-5306</b>
<b>Elkton, MD:</b>	<b>800-544-7127</b>	<b>Voorhees, NJ:</b>	<b>866-315-0235</b>
<b>Jacksonville, FL:</b>	<b>800-828-3055</b>	<b>Walpole, MA:</b>	<b>800-854-5310</b>

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

#### XL 55 MFG

<b>OVERALL LENGTH</b>	53'
<b>OVERALL WIDTH</b>	102"
<b>CAPACITY</b>	55,000 LB DISTRIBUTED, 55,000 IN 20'
<b>WEIGHT +/- 3%</b>	0,000 LB
<b>GOOSENECK</b>	
<b>LENGTH</b>	9' 6" FULL-WIDTH NECK PERIMETER FRAME STYLE (FULL WIDTH)
<b>KINGPIN SETTING</b>	16"
<b>SWING CLEARANCE</b>	87"
<b>5TH WHEEL HEIGHT</b>	PLUMB CONNECTIONS ON INSIDE OF GOOSENECK 50" - CUSTOMER TO CONFIRM 5TH WHEEL PLATE TO SIT 2" LOWER THAN GOOSENECK BEAM BOTTOM FLANGE SHIMMABLE NECK - SHIMS INCLUDED QUICK COUPLER ON FRONT OF MAIN DECK
<b>DECKING</b>	1 1/8" APITONG DECKING FLUSH
<b>D-RINGS</b>	(2) PAIR OF PAN STYLE D-RINGS - (1) EACH CORNER NO BENT D-RINGS PER SIDE
<b>MAIN DECK</b>	
<b>LENGTH</b>	35'
<b>LOADED DECK HEIGHT</b>	90" INSIDE TO INSIDE DIMENSION NEEDED 16" W 4" GROUND CLEARANCE 1/4" WEAR PLATE FULL LENGTH ON BEAMS WITH KICK UP AT FRONT OF THE DECK 1/4" WEAR PLATES DOWN CENTER OF TRAILER, FULL LENGTH 5" HEIGHT TO TOP OF PLATE AND 7" LOADED HEIGHT TO TOP OF CROSSMEMBERS
<b>DECKING</b>	3/16" PLATE UNDER CROSSMEMBERS
<b>CROSSMEMBER</b>	FABRICATED CROSSMEMBERS ON 24" CENTERS - 2" X 2"
<b>SIDE BEAMS</b>	OUTSIDE WEB STIFFENERS WITH 3" X 1/4" RUBRAIL
<b>D-RINGS</b>	2 PERIMETER FRAME BEAMS - 12" FLAT D-RINGS ON INSIDE OF BEAMS - 24" CENTERS
<b>REAR DECK</b>	
<b>LENGTH</b>	8' 6"
<b>LOADED DECK HEIGHT</b>	38"
<b>AXLES</b>	( 2 ) 25,000 LBS. NOMINAL (5/8" WALL)
<b>SUSPENSION</b>	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
<b>AXLE SPACING</b>	49"
<b>ABS</b>	4S2M WITH SPRING BRAKES ON ( 2 ) AXLES
<b>TIRES</b>	245 / 70R / 17.5 MICHELIN
<b>WHEELS</b>	6.75 X 17.5 8-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, MILLED ALUMINUM INSIDE DISC
<b>BRAKES</b>	12 1/4" X 7 1/2"
<b>DRUMS</b>	OUTBOARD
<b>ELECTRICAL</b>	12V SEALED GROTE SYSTEM WITH ( 3L +5L + 3L ) DUAL INTENSITY TAIL LIGHT ALUMINUM PACKAGE 4" AMBER STROBE IN THE 4TH AND 8TH POSITION. 4" TURN AND MARKER IN 1ST AND 11TH POSITION 4" STOP AND MARKER LIGHTS IN THE 2ND, 3RD, 5TH, 6TH, 7TH, 9TH AND 10TH POSITION 1 1/8" APITONG DECKING FLUSH
<b>DECKING</b>	2 PAIR OF PAN STYLE D-RINGS - ONE ( 1 ) EACH CORNER
<b>D-RINGS</b>	( 2 ) BENT D-RINGS IN TAIL CHANNEL
<b>D-RINGS</b>	
<b>PAINT</b>	
	ZINC RICH PRIMER BLACK
<b>ADDITIONAL</b>	
	RIDE HEIGHT SET AT 10" FOR 4" GROUND CLEARANCE TRIPLE DONUTS MANUAL RIDE HEIGHT CONTROL RAISE AND LOWER VALVE ( 11 ) TOTAL TRUCKLITE PENNY LIGHTS AND CONNECTORS PER SIDE ( 3 ) ON UPPER DECK, ( 6 ) ON MAIN DECK , ( 2 ) ON REAR DECK TRANSITION, AND (1) REAR CLEARANCE LIGHTS TO BE BEEHIVE LOOK) LOOM AROUND TRUCKLITE LIGHTS AND CONNECTORS LIGHTS AND WIRING ABOVE CROSSMEMBERS NYLON LIMIT STRAPS GREASE HUBS IN LIEU OF OIL GLADHAND DUMP VALVE ALUMINUM LAYDOWN CENTER RAMPS

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.