



A032658
VIN: 059693

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

BODY SPECIFICATIONS

Design Type:	Genesis Design - INBOARD
Length:	38'-0"
Width:	96"
Overall Side Height:	66" SOLID
Aluminum Height:	66"
Top Rail Type:	9" DUMP
Top Options:	NONE
Side Material:	.100 Wall: 6' -Front .140 Wall: 24' -Middle .180 Wall: 8' -Rear
Rear Post:	STANDARD - INBOARD
Floor Design:	SHEET AND CROSSMEMBER
Body Package Options:	NONE
Body Vibrator:	NONE
Doghouse Width:	14" WIDE
Floor Thickness:	1/4" FULL LENGTH
Floor Overlay:	NONE
Floor Options:	NONE
Floor Cleanout:	1/4" x 5" STANDARD BOTTOM RAIL
Cleanout Overlay:	NONE
Crossmember Spacing:	12" (15 1/2" CENTER TO CENTER)
Crossmember Type:	STANDARD
Floor Stringers:	NONE
Spray Skirts:	STANDARD TRANSITION SKIRT
Body Fenders at Base of Bulkhead:	SQUARED OFF
Apron:	NONE
Flaps:	10" FLAP FRONT, 16" FLAP AHEAD AXLE #1, 42" FLAP BEHIND REAR AXLE
Chassis Flaps:	ACROSS REAR OF CHASSIS + ACROSS CHASSIS AHEAD AXLE 1
Option	NONE
Bulkhead Design:	STANDARD
Bulkhead Material:	3/16"
Cab Shield:	NONE
Doghouse Width:	14" WIDE
Slope Plates at Inside Bottom Front:	5" PLATES
BH Inside Joint Reinforcement:	NONE
Tarp Hooks:	NONE
Ladders Out - Front:	NONE
Ladders In - Front	NONE
Shovel Hanger:	DOGHOUSE PASSENGER SIDE
Bulkhead Equipment:	OVAL ACCESS DOOR - DRIVER SIDE

SERIAL: 1E1F9T382HR059693



TAILGATE SPECIFICATIONS

Tailgate Height:	FULL
Tailgate Slope:	NONE
Rear Post:	STANDARD - INBOARD
Tailgate Material:	.140 GENESIS PANEL
Top Hinges:	OVERSLUNG
Tailgate Powerlift:	NOT APPLICABLE
Sideswing:	SIDE SWING W/ GROUND CONTROL (HINGED PASSENGER SIDE)
Bottom Latch Trip:	AIR CYLINDER
Mid-Gate Hook Latch:	NONE
Tailgate Seal:	RUBBER
Winder Latches:	ONE EACH SIDE
Coal Door:	NO COAL DOOR
Coal Chute:	NONE
Spreader Chains:	NONE
Gate Latch Bar Grease:	STANDARD BEARING BLOCK GREASE ZERKS
Tarp Hooks:	NONE
Marker Lights:	15 BOTTOM - 15 TOP
Side Lamp Type:	TRUCKLITE LED GROMMET MOUNT
Mid-Turn Signal:	BELOW RAIL - OVAL LED - 2" IN FROM EDGE - CTR OF BODY
Rear Body Light Panel	FULL WIDTH - 000X 000 X000 - 11 LIGHTS - Center ID Size: 2" - TRUCKLITE LED - GROMMET MOUNT
Backup Lights:	1 PAIR OF CLEAR LED BACKUP LIGHTS - WIRE TO AUXILIARY BROWN
Apron:	NONE
Rear Post Lights:	NONE
Tarp Bars:	NONE
Tarp Hooks:	NONE
# of Bow Holders:	NONE
Tarp Bow Design/Location:	NONE
Tarp Bow Qty:	NONE
Tarp Bow Rise:	NONE
Tarp Wiring:	NONE
Splash Shields:	NONE
Ladders Out - Front:	NONE
Ladders Out - Rear	DRIVER SIDE
Ladders In - Front	NONE
Ladders In - Rear:	NONE
Shovel Hanger:	DOGHOUSE PASSENGER SIDE
Registration Holder:	NONE
Body Fenders at Base of Bulkhead:	SQUARED OFF
Body Vibrator:	NONE
Wood Color:	N/A
Tarp Bar Tape:	NONE
Top Rail Tape:	NONE



CHASSIS SPECIFICATIONS

Sub Frame Width:	96"
Sub Frame Length Options:	TRIAXLE
Draft Arms:	ALUMINUM
Sub Frame Cover:	NO
Hoist Pin Lubrication:	REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM DRIVER SIDE FACING FORWARD
5th Wheel Plate:	1/4"
Hoist:	9-5-265 CUSTOM
Bottom Hoist - Draft Arm Pin:	ONE PIECE PIN
5th Wheel Transport Straps:	NONE
Number of Axles:	3
King Pin Setting:	16"
Rear Axle Setting:	21 1/2"
Rear Suspension Ride Height:	17"

AXLE - 1

Axle 1 Suspension:	AAL30K - HENDRICKSON (APPROX. 5" GROUND CLEARANCE)	Brake Lining:	EXTENDED LIFE
Dist. to Prev. Axle:	52 Inches	Axle 1 Brake Drums:	CAST
Axle 1 Spindle type:	TP SPINDLES (UP TO 23,000# GAWR)	Axle 1 Wheel type:	8.25 x 24.5 BUFF IN - DURABRITE OUT
Axle 1 Hubs:	10 STUD - STEEL	Axle 1 Tire Selection:	11R 24.5 -16 PLY BRIDGESTONE R250ED LRH
Axle 1 Brake Type:	DRUM - CAM ACTUATED	Qty of Tires/Wheels:	FOUR TIRES
Brake Shoe Size:	16-1/2" x 7"	Suspension Hangers:	GALVANIZED HANGERS (LIFTABLE SUSPENSION)

AXLE - 2

Axle 2 Suspension:	AAL30K - HENDRICKSON (APPROX. 5" GROUND CLEARANCE)	Brake Lining:	EXTENDED LIFE
Dist. to Prev. Axle:	52 Inches	Axle 2 Brake Drums:	CAST
Axle 2 Spindle type:	TP SPINDLES (UP TO 23,000# GAWR)	Axle 2 Wheel type:	8.25 x 24.5 BUFF IN - DURABRITE OUT
Axle 2 Hubs:	10 STUD - STEEL	Axle 2 Tire Selection:	11R 24.5 -16 PLY BRIDGESTONE R250ED LRH
Axle 2 Brake Type:	DRUM - CAM ACTUATED	Qty of Tires/Wheels:	FOUR TIRES
Brake Shoe Size:	16-1/2" x 7"	Suspension Hangers:	GALVANIZED HANGERS (LIFTABLE SUSPENSION)

REAR AXLE - 3

Suspension:	AAT30K HENDRICKSON	Brake Lining:	EXTENDED LIFE
Rear Axle Ride Height:	17"	Brake Drums:	CAST
Rear Axle Type:	AIR - NON-LIFTABLE	Wheel Selection:	8.25 x 24.5 BUFF IN - DURABRITE OUT
Spindle Type:	TP SPINDLES (UP TO 23,000# GAWR)	Tire Selection:	11R 24.5 -16 PLY BRIDGESTONE R250ED LRH
Hubs:	10 STUD - STEEL	Qty Wheels/Tires:	FOUR TIRES
Brake Type:	DRUM - CAM ACTUATED	Rear Axle Susp. Hanger:	GALVANIZED HANGERS (NON-LIFTABLE SUSPENSION)
Brake Size:	16-1/2" x 7"		

Dust Shields:	OEM
Brake Chambers:	OEM
Cam Covers:	INTRAAX
Slack Adjusters:	OEM
Chain - Strap Stops:	NONE
Suspension Scale:	NONE
Tire Inflation System:	NONE
Hub Lubrication:	SYNTHETIC OIL
Hubometer:	NONE
Tire Carrier:	NONE
Landing Gear:	2-SPEED JOST ALUMILIGHT - DRIVER SIDE CRANK - REAR AND CROSS BRACING
Tow Hook:	NONE



Chassis Flaps:	ACROSS REAR OF CHASSIS + ACROSS CHASSIS AHEAD AXLE 1
Underride Guard:	NONE
ABS and RSS:	2S-1M - WABCO
Auxiliary ABS:	NONE
Back Up Alarm	NONE
Air Tank Quantity	STANDARD (PER ENGINEERING)
Air Tank Material:	ALUMINUM TANKS
Air Dryer:	NONE
CONTROLS	
Gate Open-Close:	FRAME SWITCH DRIVER SIDE SUBFRAME
Gate Cab Control:	ELECTRIC SOLENOID - WIRE TO AUXILIARY (RED PIN)
Suspension - Primary Fill-Exhaust:	FRAME SWITCH - DRIVER SIDE SUBFRAME
Suspension - Cab Control:	ELECTRIC SOLENOID - WIRE TO AUXILIARY (BLUE PIN)
Plumbing Note:	NONE
Liftable Suspension Up-Down:	FRAME SWITCH - DRIVER SIDE (NEAR LANDING GEAR)
Liftable Up-Down Cab Control:	ELECTRIC SOLENOID - WIRE TO AUXILIARY (BLACK PIN)
SPIF:	NONE
Down Bag Pressure:	EQUALIZING WITH PRIMARY SUSPENSION
Brake Release:	YES - BRAKES DO NOT APPLY WHEN AXLE IS RAISED
Control Box:	TWO POLYCARBONATE; ONE FOR SUSP. & GATE SWITCHES; ONE FOR LIFT AXLES/CONTROLS
Electric Coupler:	7-WAY + 6-WAY (MARKED AUXILIARY)
Hydraulic Hose Fitting:	WINGNUT FITTING
Hydraulic Hose:	STANDARD 108" LONG (4,000 LBS. PSI)
Back-Up Alarm:	NONE
Frame Color:	BLACK
Wheel Color:	N/A
Wheel Guard Insulators:	NONE

Estimated Unit Weight: 14,414 lbs.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.