

HALE TRAILER BRAKE & WHEEL



A032859
VIN: A6807

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Magnitude 55H FLD Air Tridem (Flat Level Deck) (Model: MAGNITUDE 55H FLD)	
	Est. Wt.: 22,780# +/- 3%
TRAILER - GENERAL	
Capacity: 55 tons in 12-foot length with 4 axle close coupled or single axle stinger - GAWR and GVWR determine legal payloads	
Length (Trailer Only): 52 feet 0 inches (with standard deck length and axle spread)	
Compatibility: Designed to accept optional 51/60 rear axle, spreader, and/or 35 inch flip box	
Accent Package: Accent Package Installed - ONLY INSTALL ON BACK OF NECK	
GOOSENECK	
Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 11in overall gooseneck length) set up for wetline operation	
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Swing Radius: 102 inches (11 feet 11 inches overall gooseneck length) - NGB	
Alternate Kingpin: Dual kingpin at 81 inch and 102 inch radius	
Power Source: Set up for wet line operation	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder installed	
Hydraulic Fittings: OEM Standard 1/2 inch	
DECK	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Deck Width: 8 feet 6 inches overall (unless optional deck width is selected)	
Deck Length: Flat Level Deck (FLD) design - 25 feet clear deck length **Note: OAL with this option is 51 feet 0 inches with standard axle spread	
Loaded Deck Height: 22 inches with 6 inches ground clearance	
Crossmembers: On 24 inch centers (nominal)	
Chain Slots: Chain Slots located on siderail	
Flooring: 2 inch nominal wood - side rails only	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Extension Brackets: 12 pair - 24 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type (26 swing type, 1 hook-on type on 27 foot deck)	
Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers	
Hammer Plate: Hammer Plate installed over recessed crossmembers. Perforated plate under hammer plate forming two storage areas. 2 pair lashing ring located in last two deck sections.	
REAR BRIDGE	
Front Bogie Ramp: Included	
Boom Trough: Low Boom Well V crossmembers with bolt-in V pan	
Bolsters: Recessed	
Deck to Bogie Connection: Fixed	
Covered Rear Bogie: None	
Rear Bogie Height: 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
AXLES	
Number of Axles: 3 axles	

Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches (between axles)	
Dust Shields: None	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: None	
SUSPENSION	
Suspension: Air ride	
ABS: None required	
Chain Lift: First Axle (acts as limit chains)	
Override Chains: Override Chains Axle 2 & 3	
Third Axle Lift: Air lift	
Mechanical Ride Height Control: 7-position mechanical ride height control system	
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Liquid Filled Gauge: Liquid filled air gauge installed	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted	
Tires: 275/70R 22.5 OEM Standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Tail Lights: 3 tail light package	
Electrical Receptacle: J560 7-pin connector	
Marker Lights: 3 marker lights per side including mid turn	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 14 pair - 28 total	
Flag Holders: Flag holders - 1 pair located at front of deck and on rear bumper	
AVAILABLE COMPONENTS	
Flipbox: None	
Spreader: None	
Flip Axle: None	
Hydraulic Flip Axle Option: None Standard	
Dust Shields on Flip Axle: None	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.