



A033117  
VIN: 44994

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

**Model:**T(4)-55CC-HRG-T1

**Capacity in tons:** 55

### 1. GOOSENECK

Gooseneck design  
Loaded 5th wheel height  
Swing radius  
Alternate kingpin  
Support cylinder  
Power source  
Gooseneck locks  
Electrical receptacle  
Additional gooseneck specifications

RATCHET  
52"  
108"  
Removable kingpin stations for 108" and 90" swing radius  
Hydraulically operated with 4" x 3" cylinder mount cross member  
Hydraulic couplings: 3/4" fixed at front of gooseneck  
RATCHET  
Seven pin connector  
1) Aluminum diamond cover plate  
2) Formed aluminum diamond plate light bar mounted in gooseneck base with 4 LED stop/tail/turn lights and 2 clear work lights wired to marker light circuit with on/off switch  
3) Fully enclosed chain bar with aluminum diamond plate and lockable hinged lid (paddle latches)  
4) Full penetration weld on gooseneck gusset  
5) Base pivot tube reinforcement

### 2. DECK

Deck section design  
Deck section length  
Deck section width  
Loaded road clearance  
Loaded deck height  
Flooring  
Mainbeams  
Gooseneck/deck connection  
Deck/rear bridge connection  
Outriggers  
Additional deck specifications  
Slope front of deck top down  
Heavy duty front folding ramps  
Expanded metal

Four beam  
26'-0" (25'-6" clear)  
8'-6"  
6"  
18"  
2" apitong secured with deck screws; no lumber between main beams  
12" T-1A  
Horizontal pin and plate with remote lock  
Fixed/welded  
12" swinging/removable with double hook-on at front of deck  
Bucket well, recess last 4 deck cross members in deck between main beams and cover with 1/4" plate  
With plate and traction bars  
32" with smooth plate and traction bars  
Between main beams 1st deck section at front and last deck section at rear, in front of bucket well

### 3. REAR BRIDGE

Rear bridge section width  
Loaded rear bridge height  
Number of axles  
Axe capacity  
Axe spacing  
Brakes  
8'-6"  
41" frame; 37" bolsters  
3  
25,000# - GAWR = 24,700#  
54"  
16-1/2" X 7" air actuated with spring brakes on one axle

Anti-lock brake system	None required - GVWR is greater than 120,000#
Wheels	Ten (10) stud; 285.75mm B.C. aluminum disc hub piloted system with oil seals, inner aluminum wheels polished, outer aluminum wheels polished
Tires	Twelve (12) 275/70R22.5 (H) 16PR radials
Suspension	25,000# Capacity Ridewell air
Suspension options	<ol style="list-style-type: none"> <li>1) Over ride chains on all axles</li> <li>2) Talbert manual raising and lowering (+3", -3")</li> <li>3) Air lift on axle 3</li> <li>4) Manual exhaust</li> <li>5) Liquid filled air gauge mounted in 2nd axle curb side air bag with decal</li> </ol>
Rear Bridge Center Section	Boom well, cross members recessed - recess 1st member additionally
Wide center bolster	With chain slots & flag holder slots
Rear half bolster	Rear of axle 3 with flag holder slots
Front bridge ramp	Sloped to deck outside of main beams with plate and traction bars
Rear bridge fenders	None
Additional rear bridge specifications	<ol style="list-style-type: none"> <li>1) Omit 1st cross member in rear bridge section (shock mount cross member) for open boom well</li> <li>2) Connections for future 4th axle</li> </ol>
<b>4. GENERAL</b>	
Lights and wiring	<p>12 volt system with the following:</p> <p>All lights to be LED including mid-turn, excluding license plate light</p> <p>6 Markers (2") each side of gooseneck (SN44189 for layout)</p> <p>7 Markers (2") each side of deck including a mid-turn (SN44189 for layout)</p> <p>Markers (2") in each bolster end</p> <p>3 combination (3 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit</p> <p>Rear bridge work light (ref. LRBUL52CB) mounted on front side of first recessed cross member wired to switch at rear on marker light circuit</p> <p>Strobe lights with switch at rear of axle 3</p> <p>Battery back-up system with switch to flash all marker/tail lights and strobes</p>
Paint	Special color Red Valspar urethane matched to a customer supplied paint chip (NON-METALLIC) with ZINC RICH primer
Lash rings	<p>36 total -</p> <p>6 each side of deck (bent style), 12 total</p> <p>1 each side between deck main beams in the first three deck sections (bent style), 6 total</p> <p>1 each side mounted on side of deck bucket well plate in-line with the last three cross members of deck (bent style), 6 total</p> <p>1 each bolster and half bolster end (straight style), 6 total</p> <p>1 each side between rear bridge main beams mounted on the sides of the recessed cross members (straight style), 6 total</p>
Estimated empty weight	22,360#
Design notes	Not reinforced for spread axle capabilities
Additional general specifications	None

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
 Equipment availability, prices and specifications are subject to change without notice.