

BASE MODEL: CV-CT | Chip Van - Closed Top

BASE MODEL. CV-C1   Chip vall - Closed Top		
components	description	
OVERALL LENGTH	48'	
OVERALL WIDTH	8' 6"	
OVERALL HEIGHT	13' 2" (105" PH)	
UPPER COUPLER HEIGHT	* * * 50" * * *	
UPPER COUPLER PLATE	4 1/4" w/ 1/2" Plate	
KING PIN SETTING	36"	
SWING CLEARENCE	90"	
LANDING GEAR	Two Speed	
SUSPENSIONS	Air Ride - Watson- Tridem - Lift Rear Axle	

- \*\* When Air is Dump off Suspension make sure there is 1" Clearance so body will not set on Tires.\*\*
- \*\* Install Electric and Manual Switch for Lift and Dump in Sealed Box also, able to control from Tractor.\*\*
- \*\*Locate Box on D/S in Front of Suspension (Protected)\*\*
- \* \* \* Air Guage to be installed on Nose (See MAC Trailer Picture)\* \* \*

A)	XLES	(3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride
	** Restrants on all Axles.**	
A)	XLE SPACING	* * * 54.5" * * *

54.5" Axle Spacing, from Axle 1 to 2

54.5" Axle Spacing, from Axle 2 to 3

\*\*Set Rear Axle 5ft from Rear of Bumper.\*\*

WHEELS	Disc - Hub Piloted	
TIRES	11R24.5 - Manufactures Choice Tires	
**Install 10ga Plate Located over the Susp. Area.**		
FRONT TYPE	18" Diagonal	
FRONT MATERIAL	Aluminum	
** Land Frank Alamina to be an all from ACCILLED Alamina for Discussions for Discussions		

\*\* Inside Front Aluminum to be made from .125" H.D. Aluminum for Blow In \*\*

\*\* Install 3/4" Plywood in Nose Section Due to Blow in Chips.\*\*

LADDERS	None
REAR DOOR TYPE	Heavy Duty Top 2 Hinged Chip Gate - Top Half Open for Blow In Chipper Stream
REAR DOOR MATERIAL	Heavy Duty Steel Mesh
SIDE SHEET MATERIAL	Aluminum
SIDE SHEET COLOR	* * * .063" Natural Aluminum * * *
SIDE POST	Extruded Aluminum on 12" Centers
SIDE VENTS	24 Total - 16" in Height and Framed - Expanded Metal Vent Screen
•	

\*\* 10 Vents in a Row between each Post opening, Skip 7 Post and add One more, Skip 7 More Post and Add One More for a total of 24.\*\*

\*\*Use X-Bracing Due To Plywood Flooring.\*\*

SILL SPACING See note

\*\*8" Sill Centers in Upper Coupler Area.\*\*

\*\*12" Sill Centers in Bay Area.\*\*

\*\*8" Sill Centers in Susp. Area.\*\*

PARKING BRAKES	3 Axle
DUST SHIELDS	All Axles
ANTI-SAIL MUD FLAPS	Rear Frame
BUMPER	3" x 4" Pusher
LIGHTS	Sealed Wiring Harness w/ LED Pkg
CUSTOM 1	Smooth Top Roof with Cross Members at 16" Centers

- \*\* Add .050" Aluminum Roof w/ Roof Bows.\*\*
- \*\* Roof to be Completely Flat.\*\*
- \*\* Two Roofs w/ Blow in Strip to 3/4 of Trailer.\*\*

CUSTOM 2	Hinged Vent Door at Front Top Center
**0.75" Plywood With 0.25" Alum Cover.**	
CUSTOM 3	Removble Screw-In Kingpin