



A033334

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

GVWR: 90,000#

Beam Rating in 10': 60,000#

FRAME

Type	Drop Deck															
Model	Titanium															
Neck Type	Fixed Gooseneck - Full Width															
Extendible	None															
Length	<table> <thead> <tr> <th></th> <th>Feet</th> <th>Inches</th> </tr> </thead> <tbody> <tr> <td>Overall length</td> <td>53</td> <td>0</td> </tr> <tr> <td>Top deck length</td> <td>11</td> <td>0</td> </tr> <tr> <td>Bottom deck length</td> <td>42</td> <td>0</td> </tr> <tr> <td>Well length</td> <td></td> <td></td> </tr> </tbody> </table>		Feet	Inches	Overall length	53	0	Top deck length	11	0	Bottom deck length	42	0	Well length		
	Feet	Inches														
Overall length	53	0														
Top deck length	11	0														
Bottom deck length	42	0														
Well length																
Width	102 Inches															
Beams	2 Main Beams (Standard on 43" Beam Centers)															
Inner Beam Flange	Aluminum: 1" x 5" Top Flange & 1 .05" x 6" Bottom Flange (Heavy&Super Duty)															
Web Thickness	Aluminum: 0.380" Thickness (Heavy Duty & Super Duty Beams)															
Inner Beam Depth	25" - Titanium Heavy Duty Beam - Huck Bolted Construction															
Beam Holes	None															
Well Deck Height	No Well with a Flatbed or Dropdeck Trailer or Flip Axle															
Sill Height	Aluminum: 5" Crossmember Height on 12" Centers. 12" Lower deck - 18" Top deck															
Coil Kit	One Coil Kit - 7 Aluminum Stub Sills															
Rear Deck Height	41 Inches - Dropdeck (Plat/Chap/Titanium - Based on 22.5" Tires)															
Fifth Wheel Height	49 Inches															
King Pin	30 Inches															
Side Rail	Aluminum: 7.4" Ext w/ J-Hook Track and Heavy Duty Continuous Contact Rub Rail															
Extra Stake Pockets	None															
Conspicuity Tape	Conspicuity Tape on Side Rail															
Front & Rear Plates	FRONT: Alum Bev Cnr NO-Stake Pkts - REAR: Alum NO-Stake Pkts & Rubrail															
Flag Holders	None															

Pair Qty

Rubber Dock Bumpers	Rubber Dock Bumpers on Rear Sill	
Drop Plate	23" Aluminum Drop Plate (Chap on 22.5")	
Knee Braces	None.	
Paint	Aluminum Trailer: Susp & Axles are Undercoated, LG/FW painted Silver	
Flooring	Aluminum Floor W/ 3 Apitong Nailers	
Load Hook Flooring	No Load Hook Track in Floor	
Landing Gear	Jost AX150 Aluminum (10 Year Warranty, 5 Year No Lube) - Handle: Road	
Rear Enclosure	Open Aluminum Rearend - Lights In Rear Sill	
PERIMETER BEAM OPTIONS	No Options Selected - Perimeter Beam Options May be Grouped	
OILFIELD OPTIONS	No Options Selected - Oilfield Options May be Grouped	
STRUCTURAL OPTIONS	No Options Selected - Structural Options May be Grouped	
SUSPENSIONS & AXLES	GAWR: 20,280 #	2
Suspension Type	Air Ride Suspension - Hendrickson -- AA230 (Intraax)	Axles on this Configuration
Axle Type	Hendrickson 23k Integrated RTR Axle - HXL5	
Number of Axles	2 Axles - Standard	Will have holes in main beams for slider pins so can easily be monitored
Sliding Axles	Dropdeck - Rear Axle Slide - Pins Through Internal Slider Tube	
Axle Spacing	61/122 Inches - For Rear Slider	Inches <input type="text" value="0"/>
Overhang	Determined by California Legal - Min. Overhang Est.: 63 Inche	Inches <input type="text" value="0"/>
Cal & Can Legal	California Legal	
Steerable Axle	None	
Lift Kits	None	
Axle Straps	None	
Axle Spindle Type	N-Type (All Axles)	
Brake Type	Drum Brakes - Spring brakes with auto slack adjusters	
Hub Type	Cast - Hub Piloted	
Drum Type	Cast	
Brake Dust Covers	None	
Bearing Lubricant	Synthetic Semi Fluid Solid Grease	
Hub-O-Meter	None	
Inflation Sys & Crossfires	None	
Mudflaps	One Pair Per Axle	
TIRES & WHEELS		8 Wheels and Tires in this Configuration
Tires	Gladiator (Tier 3) 255/70R22.5 (H) - QR40ST - 120PSI	
Outer Wheels	22.5" Standard Duty Steel - White	

Inner Wheels	22.5" Standard Duty Steel - White			
Spare Tire	None			
Spare Wheel	None			
Tire Carrier	None			
LIGHTS				
Rear Lights	3-3-3 Light Pattern - Center 3 are MicroDot Lights, Outers are 4" LED			
Extra Row of Rear Light	None			
Back-up Lights	None			
Strobe Lights	None			
Over Dimension Lights	None			
Side Marker Lights	MicroDot Lights - Qty between 4 and 9 Pairs			
Side Light Options	None			
AIR & ELECTRICAL OPTIONS				
Anti-lock Braking System	Meritor 4S/2M			
Air & Electrical Connection	Standard Plus Extra 7-way in Front Plate with Harness PLUS 4-way in rear panel			
Air Raise & Lower Valve	Air Raise & Lower Valve In An Aluminum Box (Mounted on Bracket)	ISO Type Aux 7 way on nose - Wired to Electric dump on rear axle		
Dump Valve	Both Auto Dump & Electric Dump	Standard Steel air tank for air system		
Pull Lanyards on Air Tanks	None	Electric dump on rear axle		
Gauges And Scales	None			
LOAD SECUREMENT				
Winch Track	Winch Track (Double L) on Roadside & Curbside (Integrated in Aluminum Side Rail)			
Tie Bar	Aluminum Tie Bar on Roadside & Curbside			
Fixed Winches	None			
Sliding Winches 1	Standard Sliding Winch - BLACK	(Specify Qty)	Qty[0]	
Sliding Winches 2	None	Qty[12]	[1 Ea side top, 5 Ea side lower]	
Recessed Floor D-Rings	None	Pair Qty[0]		
Chain Ties	Recessed Chain Ties - Bolt-on (Specify Qty in Pairs in space to)	Pair Qty[17]		
Rope Hooks	None	Pair Qty[0]		
C & G - Hooks	None	Qty[0]		
J-Hooks	None	Qty[0]		
J-Hook Carriers	None	Qty[0]		
Container Locks	None			
Load Bunks	None	Qty[0]		
Bulkheads	None	No Options Selected - Box Options May be Grouped		
BOXES				
Tool Boxes: Type 1	None	Door: None	Locks: None	Qty[0]
Tool Boxes: Type 2	None	Door: None	Locks: None	Qty[0]
Gooseneck Boxes	None			
Belly Boxes	None			
Racks	None			
DOVETAILS & RAMPS				
MISCELLANEOUS				
Certificate Holder	Certificate Holders			
FHWA Inspection	FHWA Inspection			

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.