

HALE

TRAILER

BRAKE & WHEEL



A033439
VIN: 090150

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ALUMINUM "BST" PLATFORM TRAILER

LENGTH:	53'	SUSPENSION:	AANT 23K E2-1 WITH AUTO REINFLATE RAS (2) GALV HANGERS - SLIDER INSIDE MAIN BEAM
WIDTH:	102"	LOWERING KIT:	AUTOMATIC
NOSE:	SQUARE 7 WAY + 4 WAY	AXLE TO AXLE:	60 - 121"
KING PIN SETTING:	30" 1/4" PLATE	AXLE TO REAR:	CALI LEGAL IN CLOSED POSITION
FLOOR:	KNURLED 3 NAILERS INTGRATED SIDE RAIL	LIFT / AXLE:	
XMEMBER SPACING:	22"	SPACING:	
COIL PACKAGE:	YES	F.W. HEIGHT:	49"
SPOOLS:	DOUBLE	CONTROLS:	
POCKETS:	HD	AXLES:	TP SPINDLE PREP FOR TIRE MAXX PSI
ROPE HOOKS:	NONE	AUTO SLACKS:	STD
TIE DOWNS:	NONE	BRAKES:	16 1/2" X 7"
MARKER LIGHTS:	5 PAIR (1)	ABS SYSTEM:	4S -2M
MID TURN SIGNAL:	COMBO(1)	HUBS:	10-S LWSTL LWBD - HXL5
FLAT <input checked="" type="radio"/> ANGLED <input type="radio"/>		WHEELS:	8.25 X 22.5 (8) ALUM HP
LIGHT PANEL:	000 000 000	TIRES:	11R 22.5 RR 150 DOUBLE COIN
	FULL WIDTH BUMPER	LANDING GEAR:	JUST AX 150 DRIVERS SIDE CRANK
BULKHEAD:	NONE	TIRE CARRIER:	NONE
TYPE:		TOOLBOX: QTY:	NONE
HEIGHT:		SIZE:	
RETURNS:		LOCATION:	
MAT'L:		MAT'L:	
ACCENT TAPE:	CONSPICUITY TAPE ON RUB RAIL	MUDFLAPS:	STD - MOUNT ON SLIDER
PAINT:	BLACK	TYPE:	
WINCH TRACK:	INTEGRATED IN SIDE RAIL	LOCATION:	USE PLASTIC FLAPS
LOCATION:	BOTH SIDES		
WINCHES:	NONE		
WINCH CLIPS:	NONE		
STRAPS:	NONE		

REMARKS:

WEIGHT +/-3%: 9923 **CHANGE 1**

- FRONT FACING LIGHT TO BE A MODEL 33. FRONT LIGHT IN STANDARD POSITION, REAR LIGHT IN REAR POCKET, ABS LIGHT IN GUSSETT BOX IN REMAING 2 MARKERS BELOW RAIL
- AUTO REINFLATE WIRED TO BLUE WIRE ON 4-WAY

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.