

HALE

TRAILER

BRAKE & WHEEL



A033519
VIN: 088528

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

BASE MODEL: CV-CT | Chip Van - Closed Top

components	description	
OVERALL LENGTH	48'	
OVERALL WIDTH	8' 6"	
OVERALL HEIGHT	13' 6"	
106" Post Height.		
UPPER COUPLER HEIGHT	* * * 50" * * *	
UPPER COUPLER PLATE	4 1/4" w/ 1/2" Plate	
KING PIN SETTING	36"	
SWING CLEARANCE	90"	
LANDING GEAR	Two Speed	
Install Dummy Set of Landing Gear Like 45ft Trailer.		
No Dummy Leg, Just Frame Work.		
SUSPENSIONS	Air Ride - Watson- Tridem - Lift Rear Axle	
** When Air is Dump off Suspension make sure there is 1" Clearance so body will not set on Tires.**		
** Install Electric and Manual Switch for Lift and Dump in Sealed Box also, able to control from Tractor.**		
Locate Box on D/S in Front of Suspension (Protected)		
* * * Air Guage to be installed on Nose (See MAC Trailer Picture)* * *		
Add 1" Ride Height Clearance Due To Possible Super Singles.		
AXLES	(3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride	
** Restrants on all Axles.**		
AXLE SPACING	* * * 54.5" * * *	
54.5"" Axle Spacing, from Axle 1 to 2		
54.5" Axle Spacing, from Axle 2 to 3		
Set Rear Axle 5ft from Rear of Bumper.		
WHEELS	Disc - Hub Piloted	
TIRES	11R24.5- General S371	
Install 10ga Plate Located over the Susp. Area.		
General S371 16 Ply Tires.		
FRONT TYPE	18" Diagonal	
FRONT MATERIAL	Aluminum	
** Inside Front Aluminum to be made from .125" H.D. Aluminum for Blow In **		
** Install 3/4" Plywood in Nose Section Due to Blow in Chips.**		
LADDERS	None	
REAR DOOR TYPE	Heavy Duty Aluminum Top 2 Hinged Chip Gate - Top Half Open for Blow In Chipper	
REAR DOOR MATERIAL	Heavy Duty Galvanized Mesh	
SIDE SHEET MATERIAL	Aluminum	
SIDE SHEET COLOR	.050 Natural Alum.	
SIDE POST	Extruded Aluminum on 12" Centers	
SIDE VENTS	40 Total - 22" in Height and Framed - Expanded Metal Vent Screen	
** Install Vents Starting At Front Every Other Post, Stopping 7ft From Rear of Trailer.**		
INSIDE LINING	Gator Plate Lining	
FLOOR	Marine Plywood	
** 3/4"x4'x8' **		
FLOOR SILLS	4" Wax Coated Steel Crossmebers	
Use X-Bracing Due To Plywood Flooring.		
SILL SPACING	See note	
8" Sill Centers in Upper Coupler Area.		
12" Sill Centers in Bay Area.		
8" Sill Centers in Susp. Area.		
PARKING BRAKES	3 Axle	
DUST SHIELDS	All Axles	

ANTI-SAIL MUD FLAPS	Rear Frame	
BUMPER	3" x 4" Pusher	
LIGHTS	Sealed Wiring Harness w/ LED Pkg	
CUSTOM 1	Top Roof with Cross Members at 16" Centers	
Blow in Strip to Full Length of Trailer.		
CUSTOM 2	Hinged Vent Door at Front Top Center	
0.75" Plywood With 0.25" Alum Cover.		
CUSTOM 3	Removble Screw-In Kingpin	
Document Holder.		
New Shorter Header Alum. Rear Gate New Rear Frame Roof Sheets Lapped For Blow In		

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.