


HALE TRAILER BRAKE & WHEEL



A033691
VIN: 78724

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-------------------|--------------|------------------|--------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Impact Flat 48' Wide Spread Air (Model Code: HAMCF12WSA)

Length / Width: 48 feet x 102 inches

Suspension Type: Wide spread air

Frame Rating: 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

Flooring: 1 1/8 inch aluminum with 4 wood nailer strips

Crossmembers: 16 inch centers - 4 inch jr. I-steel; *7 Ga. Steel Rear Skirt Due to 16" C/C Crossmember Spacing

Single Coil Hauling Package: Included

Chain Cargo Tie Downs: None included

Side Rails: Extruded Aluminum

Stake Pockets: Extruded aluminum on approximately 24 inch centers on sides

Pipe Spools: Double aluminum between each stake pocket

Rubrail: 3 1/4" extruded aluminum

Main Beams: 130K load bearing flanges; **Approximately 9 1/2" Deep Beam at Nose**

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard- **Steel Angle Bracing**; **Rear bracing extended to 44" to allow for dunnage**; **Forward bracing incl.**

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkhead Pockets: NONE Installed on Front

Bulkheads: None standard

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: Not installed

ABS: Meritor Wabco iABS 2S/1M - no cable or tool (*Fontaine recommends 4S/2M)

Axle Spread: 122 inches - set ahead approximately 12" from rear (*Approximately 42' CL Kingpin to CL Rear Axle)

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 295/75R 22.5 14PR OEM standard tires - STANDARD

Tire Inflation System: None standard

Suspension Detail: Hendrickson AANT23K Intraax air ride

Auto Glad Hand Dump : Installed

Electric Dump Valve: NONE installed

Air Lift: None standard

Front Corners: Tapered steel

Electrical System: LED: 3 lights/side, **2 lights/side on rear** - STANDARD

Paint: Black urethane on steel parts **with Impact Decals**

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Weld-on type - meets underride requirements - painted steel

Mudflaps: 1 set OEM standard behind rear axle only

Spare Tire Carrier: None standard

Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD

Sliding Winches: 12: 6 each side; **NO sliding Rope Hook/ Winch Strap Hook Retainers**

Winch Strap Hook Securement: 5/16 inch x 2 1/2 inch steel flat bar welded under crossmembers both sides near siderails

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.