

# HALE TRAILER BRAKE & WHEEL



**A033894**  
**VIN: K64237**

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 46' Length, 14.4 Units

STANDARD SPECIFICATIONS: **CTSSF-46**

Type: Peerless dual axle, transport semi-trailer

Design: Box design, flat floor, end dump, live floor

Construction: **.063 prepainted BLACK aluminum skins with aluminum exterior posts (14.5" centers), last two (2) panels each side to be .125 aluminum - FURNISHED BY CUSTOMER**

Bottom Rail: **Bottom rail to be one piece extruded aluminum**

Top Rail: **Enclosed "refuse style" top rail**

Unloading Time: Approximately 8 minutes

Capacity: 14.4 units (106.3 cu yd) (top of box)

Dimensions: **46' long, 8'6" wide, 12' 4" high (12' 10" at top of arch), 37" king pin location, 36" rear axle from rear of from rear of trailer**

Tires: **Eight (8) 11:00 x 24.5 General RA radial tires (16 ply)**

Wheels: **Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, unimount**

Tire Inflation: **None**

Axles: **25,000# cap., 77 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks, HP spindles (same inner & outer bearings)**

Brakes: **16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system**

A.B.S.: **2 sensor - 1 module**

Suspension: **Henderson AAT25K Vantraxx with slider**

Air Scale: **Air gauge recessed in bevelled corner – driver's side**

Landing Gear: **Two speed, crank on driver's side (Binkley)**

King Pin: **Standard SAE, heat treated, 37" setting 49" height, needs to be 18" of radius around king pin**



- Cross Sills  
& Decking: **Hallco 7/32**” two way standard live floor, **4” Jr. I-Beams on 12” centers with aluminum sub-deck, 3.5” drive aluminum crossmembers with 8” spacing over suspension, stainless steel hyd. Lines, KNL to furnish and install floor**
- Top: Flat design, open top, **five center ties (bolted type)**
- Top Cover: **Shur lok roll over tarp, black in color, 6” arched tarp bows and caps, telescoping pole with flex handle cut flush at rear, add “spacer” to handle holder**
- Rear Door: Full opening, side hinged, **“polymer core” freight doors skinned with prepainted black skins on the outside, - mill finish aluminum on inside and stainless steel hardware, 6” arched doors and header**
- Rear Frame: **Header, door frame and bumper to be stainless steel**
- Ladders: **Aluminum front ladder with safety loop none at rear**
- Mud Flaps: Legal, rubber
- Wiring: Unitized wiring system, 12 volt
- Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights, **(2) back up lights, (2) work lights on inside front wired to front in waterproof switch, all lights to be LED**
- Reflectors: Legal DOT
- Paint: Aluminum prepainted, **steel components primed and painted black**
- Weight: Approximately 15,913#

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.