

HALE TRAILER BRAKE & WHEEL



A033914
VIN: D49040

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Model #: DCG53 x 102 - 22.5-BTR 49" Closed Tandem
Serial #: 49040

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53' OAL

TOP DECK-LGTH/HGT 10' Length = 59" Height

LOWER DECK-LGTH/HGT 38' Length = Front 41", Center 42" Rear 40.5" Heights

REAR BEAVERTAIL 60"- 15* DEGREE TRANSITION - STEEL W/ TRACTION BARS

OVERALL WIDTH 8' 6"

KING PIN SETTING 18" - Squared Pickup Plate

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

FRONT SKIRT Aluminum Front and Corners

REAR SKIRT Steel

BULKHEAD None

MAIN FRAME 26" PreCamb Beam-130K Tru-Strength Flanges - Limited Lifetime Warranty

SIDE RAILS 6"-Alum-Extruded W/Double L Track

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

Galvanized Crossmembers.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

Galvanized Crossmembers.

NECK TRANSITION RAMPS * * * NONE * * *

REAR LOADING RAMPS (2)ALUMINUM SELF CLEANING-FULL WIDTH SPR. ASSIST-GOLIATH RAMPS

FLOOR DECKING 1-1/8" HD Aluminum W/ 2 Nailer Boards

COIL HAUL PACKAGE Single Coil Placement - 4 Extra Stud Sils-Ctr On Trailer

WINCHES 12 DOUBLE L

WINCH TRACK Double L Aluminum - Extruded Siderail C/S & R/S - Both Sides

TIE BAR D/S & C/S - Full Length Both Sides - 3/8" x 2"

STRAPS None

LANDING GEAR Two Speed - Jost A500

SUSPENSIONS Air Ride - Hendrickson Intraax 23K - 2 Axles Fixed

SUSPENSION LOCATION 43' from king pin to center of rear axle

AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires

AXLE SPACING 49" Closed Tandem

Closed Tandem.

LIFT AXLE None

DUMP VALVE Manual-Position In Front of 1st Axle D/S No Box-Dump All Axles(+5#)

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1M

DUST SHIELDS None

WHEELS Disc-Hub Pilot-22.5(2-AX)-Polish ALUM 4 Outside Wheels(4-Steel Inside(-308#) TIRES

255/70R 22.5 - Firestone

TIRE INFLATION SYSTEM None

ANTI-SAIL MUD FLAPS Behind Rear Axle
STAKE POCKETS 24" O.C. Sides
SPOOL Triangular Shaped
RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape
DOCK BUMPERS None (-5#)
CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced
CONTAINER TWIST LOCKS None
TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear
DUNNAGE RACK None
TOOLBOX MATERIAL Aluminum- Smooth Box 18Hx18Dx60L- Cam Lock
TOOLBOX LOCATION Driver Side- Behind Landing Gear
LIGHTS Accent Total LED Pkg- 5 Micros Per Side & Mid Turn-4/3/4 Strobe Rear
5 Total Marker Per Side.
Rear Strobes With Toggle Switch.
CUSTOM LIGHTS None
PAINT Black - Sherwin Williams Epoxy Primer and Acrylic Polyurethane - Shot Blasted
DECAL PACKAGE Standard Dorsey Logo Kit
CUSTOM 1. Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle
Rear Axle Dump By Aux. 7-Way and Manual Dump All Axles.
CUSTOM 2. Grote Document Holder Landing Gear R/S

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.