

HALE TRAILER BRAKE & WHEEL



A034268
VIN: 44212

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

PNEU MAC TIC DRY BULK 9300 +/-3%

VESSEL		
GVWR	72 GVWR	
MODEL	1050-S	
COMMODITY	SAND	
VESSEL CONSTRUCTION	SMOOTH EXTERIOR - INTERNAL RINGS	New "MACTrailer Super Lite" frame and dish formed heads
LENGTH	42 FT.	
OPERATING TEMP	185 DEG - (MAX)	
OPERATING PRESSURE	14.7 P.S.I. (HYDRO TESTED TO 22.5 P.S.I.)	
VESSEL THICKNESS	.190 ALUMINUM 5454-H32 (STANDARD)	
VESSEL FINISH	MILL FINISH - VESSEL (STANDARD)	
COMPARTMENTS	SINGLE COMPARTMENT (STANDARD)	
LOWER CONES	WELD ON - 45 DEG (STANDARD)	
# OF MANHOLES	3	
MANHOLE LOCATION	OVER EACH HOPPER	
MANHOLE STYLE	BETTS MODEL 8555 20 IN. MANWAY (STANDARD)	
PIPING / FITTINGS		
UNLOAD TYPE	PRESSURIZED	9
AIR INLET LINE		PTO hose holder, mast, hook and dummy adapter located street side above front fender
AIR INLET SIZE	3 INCH - INLET, MANIFOLD, VALVE	
CHECK VALVES	2-BTI OPTIMA CHECK VALVES (1 @ AIR INLET)-(1UP STREAM OF FRONT HOPPER DISCHARGE)	
AIR INLET LOCATION	STREET SIDE FRONT	
AERATION		
AERATORS	3 PER HOPPER (STANDARD)	
AERATION TYPE	B.T.I. SPIN FLOW AERATION KIT W/ WEAR PLATES AND 2" BTI BLACKMAXX INDIVIDUAL AERATION CONTROLS @ EACH HOPPER	
AERATION LINE LOCATION	STREET SIDE	
AERATION CONTROL	3" BTI BLACKMAXX BUTTERFLY VALVE	
	REGULATES AIR FLOW TO AIR MANIFOLD LINE. 2 INCH - HOSES SUPPLYING AIR TO AERATION SYSTEM.	
SEAT	WHITE MAXXLIFE RUBBER SEAT	
DISK	ALLOMAXX DISC	
HANDLE TYPE	ALUMINUM	
HANDLE POSITION PLATE	MANUAL 10-POSITION	
PROP / PRES CONTROL VALVE		
HOUSING	3" BTI BLACKMAXX BUTTERFLY VALVE	
SEAT	WHITE MAXXLIFE RUBBER SEAT	
DISK	ALLOMAXX DISC	
HANDLE TYPE	ALUMINUM	
HANDLE POSITION PLATE	MANUAL 10-POSITION	
BLOW DOWN LINE		
HOUSING	3" BTI BLACKMAXX BUTTERFLY VALVE	
SEAT	WHITE MAXXLIFE RUBBER SEAT	
DISK	ALLOMAXX DISC	
HANDLE TYPE	ALUMINUM	
HANDLE POSITION PLATE	MANUAL 10-POSITION	
RELIEF PRESSURE	15 P.S.I.	
BLOW DOWN LOCATION	STREET SIDE FRONT	
TOP AIR		
TOP AIR	3" BTI BLACKMAXX BUTTERFLY VALVE	
TOP LINE LOCATION	STREET SIDE FRONT	
PRODUCT VALVE		
PRODUCT VALVE SIZE	5" BTI BLACKMAXX BUTTERFLY VALVES	
HOUSING	COMPOSITE BODY	
SEAT	WHITE MAXXLIFE RUBBER SEAT	
DISK	ALLOMAXX DISC	
HANDLE TYPE	14" EXTENDED ALUMINUM HANDLE	
HANDLE POSITION PLATE	MANUAL 5-POSITION	
PRODUCT TEE		
PRODUCT TEE TYPE	5 X 4 BTI SAND HOG BOTTOM DROP TEE'S	
PRODUCT LINE		
LINE CONNECTIONS	4 INCH SCHD. 40 STEEL GROOVE TO GROOVE CLAMPS @ FRONT AND REAR MAC RUBBER JOINT CONNECTOR WITH WORM GEAR CLAMPS BETWEEN HOPPERS	
REAR DISCHARGE	4 INCH SCHD. 40 STEEL	
DISCHARGE LOCATION	EXTEND THROUGH AXLES TO REAR	
GAUGE ENCLOSURE	1	
GAUGES	1 - LINE P.S.I. / 1 - TANK P.S.I. - (INSIDE ILLUMINATED ENCLOSURE)	
GAUGE LOCATION	STREET SIDE - REAR - FORWARD OF TANDEM (STANDARD)	

ACCESSORIES		
LADDER	LADDER AT REAR - DOUBLE HAND RAIL (STANDARD)	CABINET BETWEEN HOPPERS 1&2 ON DRIVER SIDE
WALKWAY	ADHESIVE BACKED SKID RESISTANT TAPE BETWEEN TOERAILS (STANDARD)	
HAND RAIL	NONE	
TOE RAIL	FULL LENGTH - BOTH SIDES (STANDARD)	4 - 8" ALUMINU HOSE TUBES. 2 - 8" X 21' OUTBOARD
HOSE TUBE	1 - 8 x 21' ALUMINUM HOSE TUBE (STANDARD) - (CURB SIDE)	2 - 8" X 10'6" INBOARD
HOSE TROUGH	NONE	
TIRE CARRIER	NONE	Document holder located street side near landing gear
FENDERS	ALUMINUM ROLLED EDGE - SINGLE CONTOUR AT FRONT, DOUBLE CONTOUR AT REAR (STANDARD)	
MUD FLAPS	ANTI-SAIL FLAPS - REAR OF FRONT FENDERS AND REAR OF BACK FENDERS (STANDARD)	
TOW HOOK	IN FRAME - BETWEEN RAILS	
CHASSIS		
MODEL TYPE	TANDEM	42
5TH WHEEL LOCATION	GALVANIZED, ADJUSTABLE	
5TH WHEEL HEIGHT	48 IN.	
LANDING GEAR	JOST - 5 YEAR NO LUBE - D.S. (STANDARD)	
SUSPENSION	HEND. INTRAAX AAT 230 W/ RAISED AXLE - TP SPINDLE - H.L.S. WHEEL PACKAGE	
AXLES	71.5" AXLES	
WHEEL END PACKAGE	YES	
SUSPENSION CONTROLS	AUTOMATIC DUMP ON EMERGENCY GLADHAND (STANDARD)	
SCALE SYSTEM	LOAD GAUGE - STREET SIDE REAR (STANDARD)	
HUBS & DRUMS	CENT W/ALUM. HUB. HP OB 10 STUD TP, LS, 7 INCH (STANDARD)	
TIRE & RIM SIZE	24.5 WHEELS AND TIRES	
TIRE TYPE	8 - GERERAL 11/R24.5 16 PLY TIRES	
RIM TYPE	ALCOA 8.25 X 24.5 BUFFED WHEELS	
TIRE INFLATION SYSTEM	NONE	
A.B.S.	(1) 4S2M MERITOR / WABCO (STANDARD)	
BRAKE SHOES	7" XL, W/30-30 CHAMBERS (STANDARD)	
SLACKS	STANDARD	
HUBODOMETER	NONE	
SYNTHETIC LUBRICATION	H.L.S. WHEEL END PACKAGE	HXL-5 Chevron-Delo semi-fluid grease with solid hubcaps
LIGHTS		
REAR I.D. LIGHTS	(I.D.) (I.D.) (I.D.)	0
"HIGH MOUNT" BRAKE LIGHT	DUAL FUNCTION REAR I.D. LIGHTS BRIGHTEN WHEN BRAKES ARE APPLIED	
REAR LIGHT PANEL	(TURN) (STOP) (STOP) - (STOP) (STOP) (TURN)	
LIGHT TYPE	TRUCKLITE LED W/GROMMETS (STANDARD)	
MARKER LIGHTS	2 EACH SIDE - FRONT AND REAR (STANDARD)	
MIDTURNS	2-PAIR COMBO MIDTURNS (STANDARD)	
BACK-UP LIGHTS	NONE	
WORK LIGHTS	2 - CUBE LED WORK LIGHTS W/SWITCHES ON GAUGE BOX	1 - MOUNTED DS FRONT FENDER 1 - MOUNTED HIGH AT REAR
AUXILARY CABLE (4 OR 7 WAY)	NONE	
PAINT		
SUSPENSION COATING	GALVANIZED HANGERS WITH HENDRICKSON BLACK SOFT COAT	2
PAINT COLOR	MAC BLACK (STANDARD)	
APPROVAL:		

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.