



A034416
VIN: 990402

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE



Booster with front articulation:

Hydraulic system with accumulator pressurised by:

Truck's wet line Power Pack with Honda motor

Reverse guiding system: Yes No

Control to hydraulically lift booster when reversing:

Yes No

Hydraulic Coupling: 1" wing nut
 3/4" quick coupling 1" quick coupling

Frame: CHT-100 Steel

Fenders: yes no other:

Bumper : Short Long Tow rings
 Tow plate Pusher

Mud flaps : Temisko Extra S.B.C.

Location :

Lights : Truck-lite round type (2/s) 45° flasher
 Truck-lite round type (3/s) Extra marker
 Beacon light Back-up light
 Expandable lights 7 way plug
 Oversize sign interchangeable with low bed
 Other: LED

Title Holder: Non Tite seal #158
Location : Truck-lite

Paint: Colour: Black Tape 55%
Colour code: Tape 100%

Trim : No White Other:

Rim : Natural Paint

Landing Gear motor: JOST

Crank : R/S C/S Jost

SPECIAL

SMALL TUBING FOR FLAGS Reverse guiding cylinders

D RING FOR LIFTING AND STACK

Booster: **30 Tons**

Length: **19' 1"** **Width:** 120

Axes: 2 2+1 3 1+1

Suspension : Intraax AA-300 Turner HT-300
 Other Intraax AA-250 Turner HT-250

Scale-O-Matic Height override valve
 Ball valve
 Chains on axle

Axle location: **60 SPREAD**

Filp axle : Yes No

Hooks for filp axle: Yes No
 with air/elect. connections without air/elect. connections

Axle track: other:

Axes : D22 - 25.000 lbs., 5/8" walls cam enclosure, dust shields

Seals : Stemco Guardian HP Grit G **Bearings :** Stemco

Brake chambers: MGM

Automatic Slack adjuster : Rockwell Haldex

Brake valve: Rockwell Wabco

Brake lining : 16 1/2" x 7" x 3/4" x "Q", non asbestos
 CM20 22.500Lbs. Q+ CM29 25.000Lbs

Hubs : 20" x 6 spokes 22" x 6 spokes

Dura Light 10 studs steel piloted hubs

Other:

Drum : Standard Centrifuse

Rims : Qty : 12 Steel
 Heavy duty Aluminium machine finished

22.5 x 8,25 24.5 x 8,25 Aluminium polished

22.5 x 9 Supplied by customer LVL

Plastic spacer (rim & rim) Plastic spacer (hub & rim)

Tires: Qty : 12 14 Ply 20 Ply S.B.C.

Model : XINCITY Z MICHELIN Size : 275-70/R22,5

Hubodometer: No KM Miles

Location :

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.