

HALE TRAILER BRAKE & WHEEL

A034432
VIN: 007002

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944
 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253
 Concord, NC: 800-438-2250 Raleigh, NC: 833-418-9777
 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400
 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306
 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235
 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE



PQT2855 SLB16E16.XLS

Fifth wheel height : 51"

Gooseneck; 2 cylinders 3 cylinders
 removable with truck's wet line
 removable with 13 HP Honda power pack
 with extension for jeep dolly thaw
 Auto steer front coupler on extension outside thaw

Hydraulic Coupling: 1" wing nut
 3/4" quick coupling 1" quick coupling

Pressure Male Fem. Return Male Fem.

King Pin Location
 15" Other : REMOVABLE____
 Bolt on Weld on Extra block

Coupler : 1/2" HTS 3/8" HTS
Plate Other :

Frame : Camber Other :

Top flange : 1" X 8" Other:

BTM Flange : 1" X 8" Other:

X-Members: none

Side Rails: Fabricated "I" Beams Flat with centre
 None Dropped Extra drop

Front fenders : Yes No Other: half fender

Rear fenders: No flat with 3/8" steel
 "U" shape with 3/8" steel Aluminum

Outriggers : Yes No Other:

D-Rings: 14 per side on lower deck
 3 per side on rear upper deck

Hard wood floor : 2" out 2 1/2" out
 for outriggers Other :

Bumper : Straight "V" shape Tow rings
 tow plate Pusher

Mud flaps : Témisko Extra S.B.C.

Location :

Lights : Truck-lite round type (2/s) 45° flasher
 Strobe Lights Extra marker
 Extendible lights on switch (blue) Back-up light
 Expandable lights 7 way plug
 Oversize sign and D sign
 Other : Strobes on blue wire with switch

SLB16E16 (65T Low Bed)

Length : 59FT **Width :** 120"

Axles : 2 2+1 3 3

Suspension : Intraax AA-300 Turner HT-300
 Other Intraax AA-250 Turner HT-250

Scale-O-Matic Height override valve
 Ball valve Air weight
 Chains on axle Regulator for air ride

Axle location: 60 SPREAD

Flip axle : Yes No

Hooks for flip axle: Yes No
 with air/elect. connections without air/elect. connections

Hooks for Booster: Yes No

Axle track : 77.5" Other : Force steer

Axles : D22 - 25.000 lbs., 3/4" walls cam enclosure, dust shields

Seals : Stemco Guardian HP **Bearings :** Stemco

Brake chambers: 30

Automatic Slack adjuster : Rockwell Haldex

Brake valve : Rockwell Wabco

Brake lining : 16 1/2" X 7" X 3/4" X "Q", non asbestos
 CM20 22.500Lbs. CM29 25.000Lbs Q+

Hubs : 20" x 6 spokes 22" x 6 spokes
 Dura Light 10 studs steel piloted hubs

Drum : Standard Centrifuge

Rims : 13 Standard steel
 Heavy duty steel Aluminium machined finish
 22.5 x 8,25 24.5 x 8.25 Aluminium inside polish
 22.5 x 9 Supplied by customer

Plastic spacer (rim & rim) Plastic spacer (hub & rim)

Tires : Qty : 12 14 Ply 20 Ply S.B.C.
 Model : XINCITY Z MICHELI Size : 275/70R22,5

Hubodometer : No KM Miles
 Location :

Title holder : No Tite seal #158
 Location : Truck-lite

Paint : Color: Black Metalized
 Color code #: Tape 100%

Trim : No White Other :
 Rim : Natural Painted :

Special:

- DETACHABLE DECK
- HYDRAULIC FLIP NECK
- EARS AT FRONT FOR EXTENSION NECK, HYDRAULIC gooseneck level LOCK
- Antenna for steering reciver
- GOOSENECK EXTENSION FOR JEEP 2+1
- DECK SECTIONS - Extendible perimeter frame, 15' extension
- See layout for D ring location
- 72ft of hydraulic line for steering
- Wirless remote control

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.