

# HALE TRAILER BRAKE & WHEEL



A034672  
VIN: S033443

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

## Infinity Flat 45' Air Slider Forklift Trailer (Heavier Lift) (Model Code: HCIFL42SAT)

**Length / Width:** 45 feet x 102 inches

**Suspension Type:** Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

**Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

**Flooring:** 1 1/8 inch aluminum with 4 wood nailer strips

**Crossmembers:** 12 inch centers - 4 inch jr. I-steel

**Single Coil Hauling Package:** Included

**Side Rails:** Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

**Chain Cargo Tie Downs:** None standard

**Stake Pockets:** Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

**Rubrail:** Integrated with siderail

**Main Beams:** 130K load bearing flanges

**Kingpin:** 30 inches

**Loaded Fifth Wheel Height:** 49 inches

**Landing Gear:** OEM Standard with Forward & Rear Bracing

**Knee Braces:** Fabricated on approx. 60 inch C/C

**Bulkhead Pockets:** 4 DOT type bulkhead pockets only - welded to front

**Bulkheads:** Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets **(\*BULKHEAD MUST BE INSTALLED & REMAIN ON TRAILER AT ALL TIMES AS PART OF FRONT COUNTERWEIGHT)**

**Number of Axles:** 2

**Axle Spindle:** Tapered

**Brakes:** Spring brakes, auto slacks

**Air Line Filters:** (2) Meritor In-line type installed

**ABS:** 4S/2M - no cable or tool

**Axle Spread:** 49 inches

**Hub and Drums:** 10-hole hub-piloted with outboard cast drums

**Wheel Ends:** Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\*

**Wheels:** 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

**Tires:** 11R 22.5 14PR OEM standard tires

**Tire Inflation System:** None standard

**Suspension Detail:** Hendrickson AAZNT46K Intraax air ride slider -2 stop adjustable (Approx. 16 in. total slide range)

**Air Assist Slide Box Pins:** Standard mount of controls on slider frame

**Auto Glad Hand Dump :** Installed

**Front Corners:** Tapered steel

**Electrical System:** LED: 3 lights/side, 2 lights/side on rear - STANDARD

**Paint:** Black urethane on steel parts with Infinity decals - STANDARD

**Conspicuity Tape:** Per NHTSA specs - installed in recess on rubrails

**Bumper:** Weld-on hinged type; Uprights notched inside for additional fork clearance

**Mudflaps:** 1 set OEM standard behind rear axle

**Spare Tire Carrier:** None standard

**Winch Track:** Full length integrated double L type aluminum on both sides -- STANDARD

**Sliding Winches:** 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD

**27 foot Winch Straps:** None standard

**30 foot Winch Straps:** Winch Straps - 30 feet x 4 inches installed - EACH - Qty: 12

**Dock Bumpers:** Not available due to design

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box:** None standard

**VIN Plate:** Bilingual US/Canadian VIN plate

**Forklift Kit:** Factory installed Fontaine design with adjustable curved upper wheel stops which accepts many Princeton & Moffett brand lifts

**Forklift Kit Note:** \*Dealer and/or Customer are responsible for final adjustment of stops & kit in order to fit actual lift being transported.  
**\*\*Actual brand, model, & weight should be identified to confirm compatibility**

**Forklift Kit Lower Tire Supports for Moffett:** Removable lower "Moffett" tire supports each side

**Front Counterweights for MAXIMUM 8,400# FORKLIFT :** Steel plates recessed in floor PLUS Additional Weights Added Underneath Floor & Between Crossmembers at Front In Addition To Steel Bulkhead Required & Noted Above

**Counter Balance Note:** FONTAINE WILL ONLY BE RESPONSIBLE FOR ISSUES RELATED TO CARRYING FORKLIFT MODELS WITH MAXIMUM WEIGHTS & CG'S AS SPECIFIED ABOVE

**Unit Numbers & Decals:** Not installed

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.