

HALE

TRAILER

BRAKE & WHEEL



A034702-VIN: 45231

A034703-VIN: 45232

A034704-VIN: 45233

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Model: T3J-275/70R22.5

Capacity in tons: 65

Flip axle: SN45232 & SN45233

Gooseneck design	FG
Loaded kingpin height	52"
Sliding 5th wheel	72"
Sliding 5th wheel height	52"
Swing radius	104" with removable kingpin settings at 104" & 88"
Electrical receptacle	Seven pin connector
Additional gooseneck specifications	Two (2) speed landing gear
Gooseneck/deck connection	Fixed/welded
Rear bridge section width	8'-0"
Number of axles	3 - 25,000# Capacity
	GAWR = 24,700#
Axle spacing	60"
Brakes	16-1/2" x 7" air actuated with spring brakes on one axle
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished
Tires	Twelve (12) 275/70R22.5 (H) 16PR radials
Suspension	Ridewell air ride with removable end axle (SN45232) and intermediate axle (SN45233)
	Chrome tapered connecting pins
Suspension options	1) - Manual exhaust
	2) - Liquid filled air gauge in first axle curb side air bag with conversion decal
	3) - Over ride chains on all axles
Lights and wiring	12 volt LED system with license plate light regular
	Mid-turn each side
	All marker lights to be 3/4" bullet style
Paint	Valspar standard Talbert black, R-Cure 800 series paint with ZINC rich primer
Lash rings	8 Total
	1 each side of the gooseneck (bent style), 2 total
	1 each side in line with axle 1 (bent style), 2 total
	1 each side at balance point of the intermediate axle (bent style), 2 total
	1 each side at balance point of the end axle (bent style), 2 total
Estimated empty weight	11,200#
Compatibility	For use with SN45234
Design notes	5th Wheel set 142" from the 104" radius setting.
	5th Wheel set 125" to center line of tandem.
Additional design specifications	1) - Plate for Hydroneck support cylinder
	2) - Pogo stick to support air/electrical/hydraulic lines

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.