

HALE

TRAILER

BRAKE & WHEEL



A034709
VIN: AN6185

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model:T4-60SA-TELE-HRG-RA-(EC3/1)-T1

Capacity in tons: 60

Gooseneck design	Ratchet
Loaded 5th wheel height	52"
Swing radius	96" With renivable kingoin (89" actual with 12" fixed front deck ramps)
Support cylinder	Hydraulically operated with 4" x 3" cylinder mount cross member
Power source	Hydraulic couplings: 3/4" fixed at front of gooseneck
Gooseneck locks	Ratchet design
Electrical receptacle	Seven pin connector
Gooseneck Extension	24" Flip-up and removable gooseneck extension (AN6174) for 120" (113") radius with lash ring at front
Chain Bar in Gooseneck Base	Fully enclosed with aluminum diamond plate and lockable hinged lid (paddle latches), with plate to protect deck air lock fittings and lines
Coverplate	Aluminum
Additional gooseneck specifications	1) - Formed aluminum diamond plate light bar mounted in gooseneck base with 4 LED stop/tail/turn lights and 2 clear work lights wired to marker light circuit with on/off switch 2) - Full penetration weld on gooseneck gusset 3) - Base pivot tube reinforcement 4) - Ratchet pivot shaft collar
Deck section design	Telescopic
Deck section length	30'-0" (29'-6" clear) closed 51'-0" (50'-6" clear) extended Includes 3'-0" platform at rea Deck to extend in increments of 2'-0"
Deck section width	8'-6"
Loaded road clearance	6"
Loaded deck height	22"
Flooring	1-1/2" apitong, full width, secured with deck screws
Outriggers	12" swinging/removable with double hook-on at front of deck
Gooseneck/deck connection	Horizontal pin and plate with remote lock
Deck/rear bridge connection	Vertical pin and plate (flush connection) (14" & 16" mainbeams)
Slope front of deck top down	With smoothplate & traction bars
Heavy duty front folding ramps	12" fixed with smooth plate and traction bars
Expanded metal	Between main beams in 3'-0" platform
Additional deck specifications	None
Rear bridge section width	8'-6"
Loaded rear bridge height	41"
Number of axles	4
Axle spacing	60"
Axle capacity	25,000# - GAWR 24,700#
Brakes	16-1/2" x 7" air actuated with spring brakes on one axle
Anti-lock brake system	None required - GVWR is greater than 120,000#
Wheels	Ten (10) stud; 285.75mm BC aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels Dura-Bright

Tires	Sixteen (16) 275/70R22.5 (H) 16PR radials
Suspension	30K Ridewell air with 4th axle (AN44991) flip-up and removable, use chrome tapered connecting pins, shims, bolts and nuts
2 Suspension options	<ol style="list-style-type: none"> 1) Over ride chains on all axles 2) Remote Talbert (+3,-3) manual raising and lowering under bolster on driver's side 3) Air lift 3rd axle 4) Manual exhaust 5) Liquid filled air gauge in 2nd axle, curb side air bag with decal 6) Leveling valve on axle 4 with switch for E1 Nitro operation
Rear Bridge Center Section	Boom well, crossmembers recessed - recess 1st member additionally
Wide center bolster	With chain slots & flag holder slots
Rear half bolster	Rear of axle 3 & 4
Front bridge ramp	Sloped to deck outboard of main beams with plate and traction bars
Fenders	1/4" floor plate over tires only - all axles including 4th axle
2 Axle Extension	E1 Nitro axle extension (AN6185). Extension designed for 3 + 1 spread axle capability and to provide 14'-1" spacing between axle 3 & 4. Complete with a Honda gas engine power pack, 2-speed landing gear, shims, and chrome connecting pins.
Connections for future removable axle	Rear of axle 3, includes ears and air/electrical connections
Additional rear bridge specifications	Omit 1st crossmember in rear bridge section (shock mount crossmember) for open boom well
Lights and wiring	<p>12 volt LED system including mid-turn lights, license plate light regular</p> <p>2 marker lights each side of gooseneck upper</p> <p>3 marker lights each side of deck including mid-turn</p> <p>1 marker light each side of deck platform</p> <p>2 strobe lights with switch at rear of axle 3 & 4</p> <p>Battery back-up system with switch to flash all marker/tail lights and strobes</p>
1 Paint	Special yellow Valspar urethane F63YL0264 (NON-METALLIC)
Lash rings	<p>28 total -</p> <p>13 each side of deck (bent style), 26 total</p> <p>1 each side of 3'-0" platform (bent style), 2 total</p>
Additional general specifications	<ol style="list-style-type: none"> 1) Reinforced for East Coast style axle extension for 3 + 1 spread axle capability providing a 14'-7" spread 2) 60 ton capacity in a two point rigid load base 4'-0" shorter than extended deck length when in an extended condition 3) 60 ton capacity in a 16'-0" two point rigid load base with deck fully closed
1 Change order notes	Added paint code

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.