

HALE TRAILER BRAKE & WHEEL



A034719
VIN: 29727

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

VIN #: 1 T K J 0 5 3 3 #### K M 0 2 9 7 2 7

MODEL: TK110HDG+ PAVER CUSTOM OAL: 52 ft 10 in

TK110HDG Advantage Plus Hydraulic Detachable 110,000 Lbs in 12 feet

10003 - STANDARD EQUIPMENT

Frame reinforced for single axle booster or flip axle
16" Kingpin setting / 50" loaded 5th wheel height
Gooseneck arched for increased truck fender clearance
Hydraulic self-lifting detachable gooseneck
(can lift above or below transport positions)
Hydraulic gooseneck support arm
Air-activated, positive self-locking pin
Gooseneck doesn't require ground bearing pads
31" front loading ramps (1 pair)
4-beam main frame construction
I-beam crossmembers on 24" centers
4" stubs in outer bays between crossmembers
Knuckle trough at rear of deck. 72" long, covered with 1/4" steel
3rd axle air lift
Lowered cross members in wheel area
Full depth boom trough in wheel area
Mud flaps
Flag holders, front of deck and rear of trailer
Wide load sign brackets

Triangle cut-outs on deck beams and bolster
Brackets, air and electrical for single axle booster/flip
Rubber mounted sealed lights and harness system
LED Light package (50-state legal)
3 Tail lights per side (amber in center)
Electrical system per DOT regulations
Air, electrical, and hydraulics installed after paint
Brackets, air and electrical for additional axles
7-pole electrical connector
Air ride suspension
Cable style adjustable ride height
Raising/lowering air control panel (includes liquid filled air gauge)
16 1/2" x 7" air brakes
Automatic slack adjusters
One-piece oil seals
Red & white conspicuity markings
Blasted prior to paint
Color: Trail King 2-part polyurethane

10003-110HDG AdvPlus-Base Trailer

1	10003	Open Deck	TK110HDG Advantage Plus Hydraulic Detachable 110,000 Lbs in 12 feet
1	10006	Hydraulic Gooseneck	12' 11" (110" and 86" swing) hydraulic detachable gooseneck

1	10013	Hydraulic Gooseneck	13 HP Honda self-contained hydraulics
1	14222	Hydraulic Gooseneck	5-position gooseneck height adjustment +/- 3"
1	10014	Hydraulic Gooseneck	Dual hydraulics with diverter valve
1	10027	Deck Width	102" deck width
1	10033	Deck Width	Tapered deck with 42" front ramps - Deletes pull-out outriggers at front and adds double-wide outriggers at front. (Non-Flow Line option.)
1	9998	Main Deck	Alternative Option Selected. See Add'l Options Section Below.
1	9998	Main Deck	Alternative Option Selected. See Add'l Options Section Below.
1	14225	Main Deck	25' 9" deck length (single axle booster reinforcement)
1	10017	Main Deck	24" loaded deck height, 8" ground clearance
1	14250	Decking	1 3/4 Apitong decking (raised)
1	14251	Decking	Decking in center ILO outrigger planks
1	14260	Tie Downs	Additional d-rings to fill out deck, 2 D-rings on wheel area
1	14261	Tie Downs	2 pr d-rings in knuckle trough
1	14262	Tie Downs	2 pr d-rings in wheel area transition
1	14252	Ramps	31" front ramps (42" ramps on tapered decks)
1	14256	Ramps	Spring assist option for front ramps
1	14257	Outriggers	Pullout HD outrigger at front, double swingouts at center with planks & 4' storage pan
1	10037	Wheel Area	Fixed wheel area - includes front half bolster
1	14318	Wheel Area	Load-bearing 20 degree slope covered with 1-3/8" apitong (shortens deck 27" for 24" deck height & 42" for 20" deck height)
1	14280	Wheel Area	10ga. Steel boom plates bolted in boom trough
1	11197	Wheel Area	Add upper brackets for hydraulic booster
1	14284	Air Control	Air suspension control panel and adjustable ride height located in end of bolster ahead of rear axle ILO controls at rear

1	10044	Axles	25,000-lb. (5/8" wall) axles
1	14286	Axle Spacing	55" axle spacing (single axle booster reinforcement)
1	10055	Brakes / Air	No ABS
1	08214	Hub / Drum	Steel hub-piloted - cast drum (per complete axle)
6	12851	Wheel Finish (inside)	8.25 x 22.5 10-hole machined (SP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel
6	12857	Wheel Finish (outside)	8.25 x 22.5 10-hole polished (XP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel
1	10058	Spare Wheel	No spare wheel
12	08148	Tire Size	Continental 275/70R22.5 - 18 ply HSR2 (tire only) (per tire) in lieu of STD General 255/70R22.5 - HT
1	10059	Spare Tires	No spare tire
1	14311	Lights	One pair of 4" round amber strobes at rear ILO 3rd tail light w/switch - Multi Diode Super Nova Lights
1	10062	Lights	4-pole socket wired to clearance light
1	10064	Lights	Remote flasher w/ battery back-up
1	11032	Miscellaneous	Air Weigh System (per Advantage Plus! HDG axle group)
1	72485	Custom Options	72485 - TK110HDG - Paver Special - Wood covered slope to be 18 degree ILO 20 degree slope.
1	72484	Custom Options	72484 - TK110HDG - Paver Special - Capacity is 110k lbs distributed or 102k lbs in 16' □
1	73233	Tie Downs - Special	73233 - HDG - D-rings on Bolster ends between axles 1 and 2
1	73331	Tie Downs - Special	73331 - HDG "Paver Special" - (1) pair of Bent style D-rings on outside top corners of rear bolster and wheel cover. Not available with roller stop.

Order Build Sheet

72602 - TKHDG

1	72602	Ramps - Special	+ : No traction aids on 42" front ramps and approach
1	08024	Paint	Black S7203 with white decals
		Custom Options	Deck Length to be maximized to maintain 53' Max OAL

01 Add option - 72485 - TK110HDG - Paver special - Wood covering slope
02 to be 18 degrees. Maintain 53' OAL. (Ride height in WA set at
03 7-1/2", lowers deck height to 22" ILO 9" RH and 24" deck height)

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.