

HALE

TRAILER

BRAKE & WHEEL



A034770
VIN: AN06188

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model:28'-9" Beam Deck Assy.
Capacity in tons: 90

1. GOOSENECK

Electrical receptacle

Seven pin connector

2. DECK

Deck section design

Beam

Deck section length

28'-9" (28'-3" Clear)

Deck section width

50" Out to out mainbeams

Loaded road clearance

6"

Loaded deck height

22"

Flooring

None

Mainbeams

16" T-1A

Gooseneck/deck connection

Horizontal Pin and Teardrop with Remote Lock

Deck/rear bridge connection

Vertical pin and plate

Outriggers

None

Reinforced top flange of sidemember

Reinforce Top Flange of Sidemember (Full Deck Length) with 2" Chain Slots

Additional deck specifications

Recess last 4 cross members at rear of deck 8" below top flange

Slope front of deck top down

Yes

Slope front of deck bottom up

None

Heavy duty front folding ramps

None

Expanded metal

Between mainbeams full deck length

4. GENERAL

Lights and wiring

12 volt system with the following:

All lights to be LED including mid-turn, excluding license plate light

3 markers each side of deck including a mid-turn light

Paint

Special color Yellow Valspar no. KPY0700 urethane matched to a customer supplied paint chip (NON-METALLIC) with zinc rich primer

Lash rings

32 Total

10 each side of deck (bent style), 20 total

1 each side between deck main beams in the first 3 deck sections (bent style), 6 total

Compatibility

Compatible with customers existing SN43115. NOTE: Customer to return all components to TMI for fitting and installation.

Design notes

90 Ton capacity in a 13'-6" two point rigid load base

Additional general specifications

None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.