

# HALE

## TRAILER

### BRAKE & WHEEL

A034801

VIN: S033566



SALES | RENTALS | PARTS | SERVICE

|                                |                               |
|--------------------------------|-------------------------------|
| Allentown, PA: 800-383-8894    | Little Rock, AR: 833-424-8944 |
| Baltimore, MD: 888-601-7500    | Portland, ME: 800-325-4253    |
| Concord, NC: 800-438-2250      | Raleigh, NC: 833-418-9777     |
| Delmar, DE: 866-486-1400       | Scranton, PA: 800-569-1400    |
| Des Moines, IA: 888-673-5011   | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127       | Voorhees, NJ: 866-315-0235    |
| Jacksonville, FL: 800-828-3055 | Walpole, MA: 800-854-5310     |

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

| ITEM                     | DESCRIPTION   |
|--------------------------|---|
| <b>TYPE</b>              | PIN ON AXLE FOR PLATFORM  |
| <b>DIMENSIONS</b>        |   |
| <b>LENGTH</b>            | 61.5".  |
| <b>WIDTH</b>             | 102".   |
| <b>COUPLING</b>          |   |
| <b>COUPLER PLATE</b>     | For anchor joints, 4 x 2" dia. rods and bushings.   |
| <b>STRUCTURE</b>         |   |
| <b>FLANGES</b>           | 1/2" x 6", 100 000 psi steel.   |
| <b>WEB</b>               | 3/16" plate, 80 000 psi steel. 13.5" high.  |
| <b>ENDS</b>              |   |
| <b>BUMPER</b>            | Rectangular steel tubing.<br>Including supports with flag and excessif width sign.  |
| <b>ELECTRICAL</b>        |   |
| <b>FRONT CONNECTOR</b>   | Cord with 7 ways connector.   |
| <b>ELECTRICAL SYSTEM</b> | Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.   |
| <b>MAIN SYSTEM</b>       | Grote Ultra blue LED, sealed beams, in a closed back rubber grommet.<br>(tail lights with male pins #54332, markers #47122 (2 1/2" dia.),<br>licence light #60280-M). |
| <b>STROBE LIGHTS</b>     | Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side.<br>toggle switch installed: AT REAR   |
| <b>BASIC SUSPENSION</b>  |   |
| <b>BOGIE</b>             | Fixed.  |
| <b>SUSPENSION</b>        | Hendrickson HT-250US (6.5), single.<br>located at ***60" semi-trailer rear axles.   |
| <b>U-BOLTS</b>           | With nuts at top.   |
| <b>SPRINGS</b>           | Air.  |
| <b>AXLE(S)</b>           | Hendrickson, HP-S506, 27 000 lbs. capacity.   |
| <b>SPIDERS</b>           | Welded.   |
| <b>CAM SHAFTS</b>        | 28 splines.   |
| <b>TRACK</b>             | 77 1/2".  |
| <b>DUST SHIELDS</b>      | Steel, clamped.   |
| <b>BRAKES</b>            | 16 1/2" standard, long life H26-HXS Hendrickson lining.   |
| <b>BEARINGS</b>          | HM 218248 and HM 212049.  |
| <b>SLACK ADJUSTERS</b>   | TSE S-ASA, automatic, 28 splines.   |
| <b>SEALS</b>             | Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.  |
| <b>BRAKE CHAMBERS</b>    | T.S.E. brake, "Omnibrake" (30-30).<br>(4 years warranty by T.S.E. for parts only).  |
| <b>HUBS AND DRUMS</b>    | WEBB, 10 studs disc hubs, balanced drums 117 lbs,<br>outboard mount, 285.75mm B.C., single flange nuts.<br>(Heavy duty 25000 lbs cap.) ("Drum" heavy duty 25000 lbs)  |
| <b>RIMS</b>              | Alcoa, aluminum, half "ULTRA ONE vHub" and half steel.  |



| ITEM  | DESCRIPTION   |
|---|---|
| <b>TIRES</b>  | 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts.<br>Standard duty with standard steel.<br>Continental, 275/80 R 22.5 HSR-2                      16 ply    (40")   |
| <b>AIR SYSTEM<br/>GLAD HANDS<br/>AIR VALVES</b>   | Fix.<br>Sealco, synflex 3/8" diameter.  |
| <b>ACCESSORIES<br/>REGISTRATION HOLDER<br/>MUD FLAPS</b>  | One plastic, Betts-PS-1 or equivalent.<br>One set, rubber with Manac logo and vertical grooves to reduce spray.   |
| <b>FINISHING<br/>PAINT<br/><br/>AXLE(S) PAINTED<br/>HUBS<br/>WHEELS OR RIMS<br/>RETROREFLECTIVE TAPES<br/><br/>SERIAL PLATE</b> | No paint nor primer applied on. Structure prepared and shipped ready to be galvanized.<br><br>Color: Grey, code: PPG Q37-939514.<br>Color: Grey, code: PPG Q37-939514.<br>White.<br>Conspicuity striping in compliance with CMVSS 108.<br>Gray and red, each side, fully covers rear bumper.<br>V.I.N. plate to be stick on an aluminum plate riveted on the frame.<br>(it doesn't stick on galvanized steel) |
| <b>ADDITIONAL OPTIONS<br/>UNIT COUPLED TO</b>   | Job:Q#255717  |
| <b>CONFORMITY</b>   | This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.                                  |

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.