

HALE

TRAILER






BRAKE & WHEEL



A034842 VIN: Q34060
A034843 VIN: Q34060-1

SALES | RENTALS | PARTS | SERVICE

| | |
|--------------------------------|-------------------------------|
| Allentown, PA: 800-383-8894 | Little Rock, AR: 833-424-8944 |
| Baltimore, MD: 888-601-7500 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Raleigh, NC: 833-418-9777 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |
| Jacksonville, FL: 800-828-3055 | Walpole, MA: 800-854-5310 |

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

| HYDRAULIC DETACHABLE GOOSENECK | Description Model: RTN55TD3-R4A TRAILER |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| TONS CAPACITY | 55 TONS IN ANY 12' |
| CONSTRUCTION | (4) I-BEAM, CAMBERED, T-1 STEEL |
| OVERALL LENGTH | APPROXIMATELY 53'-0" |
| PLATFORM WIDTH | 8'-6" |
| PLATFORM LENGTH | 26' (OVERALL LENGTH MUST BE 53'-0" OR LESS AND MUST HAVE 43'-0" OR LESS FROM THE 90" SWING TO THE CENTER OF MIDDLE AXLE). |
| PLATFORM HEIGHT/ROAD CLEARANCE | 18"/6" LOADED-ADJUSTABLE (12" DEEP MAIN BEAMS) |
| CROSSMEMBER SPACING | ON 20" CENTERS |
| FRONT FOLDING RAMPS | STEEL WITH TRACTION BARS |
| FRAME REINFORCEMENT | FOR A 3+1 (14'-1" SPREAD) |
| TOP FLANGE REINFORCEMENT | OUTSIDE OF OUTER BEAMS ONLY |
| BUCKET TROUGH | LAST 3 CROSSMEMBERS OF DECK WITH 1/4" PLATE |
| HYDRAULIC SYSTEM | REMOVABLE 13HP HONDA POWER PACK WITH DUAL OPERATIONS. MOUNTED ON TOP OF THE GOOSENECK |
| GOOSENECK | NON-GROUND ENGAGING REMOVABLE-HI LIFT |
| GOOSENECK SUPPORT CYLINDER | HYDRAULIC |
| GOOSENECK CONNECTION | PIN & STIRRUP TYPE W/ VERTICAL AIR LOCK PIN |
| SWING CLEARANCE | 108" & 90" |
| FIFTH WHEEL HEIGHT (50" LOADED) | 48"-50"-52"-54"-56" LOADED (ADJUSTABLE) |
| 1/8" ALUMINUM TOP COVER | OVER GOOSENECK AREA |
| ALUMINUM HINGED AND LOCKABLE COVER | AT REAR OF GOOSENECK |
| CHAIN AND BINDER RACK | W/ BASE PLATE AT REAR OF GOOSENECK |
| GOOSENECK LIGHT BAR | (2) CLEAR WORK LIGHTS AND (2) RED TAIL LIGHTS AT REAR OF GOOSENECK |
| AIR BRAKES | 16.5" X 7" W/ AUTO SLACKS & OUTBOARD DRUMS |
| ALUMINUM AIR TANK | |
| ANTI-LOCK BRAKES | NONE (TRAILER GVWR EXCEEDS 120,000#) |
| SPRING BRAKES | ON 2ND AXLE |
| AXLES | (3) 25,000# 3/4" WALL W/ 23,000# BRAKES AND LIMIT CHAINS |
| TIRES | (12) 275/70R22.5 (H) |
| WHEELS | ACCUSHIELD OUTERS, STEEL DISC INNERS |
| SUSPENSION | AIR RIDE W/ 52" AXLE SPACING |
| LIQUID FILLED AIR GAUGE | W/ CHART MOUNTED ON 2ND AXLE CURB SIDE |
| SUSPENSION | AIR LIFT 3RD AXLE ONLY |
| SUSPENSION | +3/-3 HEIGHT CONTROL, AUTO/MANUAL |
| RAISING AND LOWERING VALVE | AT REAR OF TRAILER |
| LIGHTS | L.E.D. RUBBER SEALED SYSTEM |
| ADDITIONAL AMBER CLEARANCE LIGHTS | (1) PER SIDE OF DECK (3 TOTAL INCLUDING THE MID-TURN SIGNAL) |
| ADDITIONAL AMBER CLEARANCE LIGHTS | (1) PER SIDE ON GOOSENECK AT FRONT |



| | |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AMBER L.E.D. STROBES | IN 3RD TAIL LIGHT POSITION W/ SWITCH |
| BATTERY BACK-UP | W/ RECHARGEABLE FEATURE TO FLASH ALL MARKER/TAIL LIGHTS AND STROBES |
| ALL MARKER/I.D. LIGHTS | TO BE 3/4" |
| 4 COMBINATION LIGHTS ON REAR LIGHT PANEL | (2) PER SIDE. STOP/TURN/TAIL AND BACK-UP LIGHTS, BACK-UP LIGHTS WIRED TO SWITCH ON MARKER LIGHT CIRCUIT. |
| REAR WORK LIGHTS | MOUNTED ON FRONT SIDE OF FIRST RECESSED CROSSMEMBER WIRED TO SWITCH AT REAR ON MARKER LIGHT CIRCUIT |
| LASH RINGS | (20) TOTAL, 6-PER SIDE, BENT STYLE, 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1-EACH BOLSTER END AND REAR HALF BOLSTER FLAT STYLE |
| ADDITIONAL BENT STYLE LASH RINGS | (1) EACH SIDE BETWEEN DECK MAIN BEAMS IN SECTIONS 2 AND 3 |
| ADDITIONAL BENT STYLE LASH RINGS | (2) EACH SIDE MOUNTED ON SIDE OF DECK BUCKET WELL PLATE IN-LINE WITH THE LAST TWO CROSSMEMBERS OF DECK |
| EXTENSION BRACKETS (OUTRIGGERS) | 12" SWING/REMOVABLE WITH DOUBLE HOOK-ON FRONT. "FULL LENGTH" OF DECK |
| DECKING | 1-1/2" APITONG (OUTSIDE MAIN BEAMS ONLY) |
| PAINT | PAINT ONLY THE GOOSENECK WEBS, DECK WEBS, EXTENSION BRACKETS, REAR SECTION WEBS, END OF BOLSTERS, REAR LIGHT PANEL WEBS. GLOSS BLACK (2-PART URETHANE) |
| HOT DIP GALVANIZE | ENTIRE TRAILER |
| BOOMWELL | OPEN BOTTOM W/ EXTRA LOW 1ST CROSSMEMBER (BOLT-IN COVER PLATE) |
| TRACTION BARS | ON FRONT & REAR SLOPES |
| CHAIN HOOKS & FLAG HOLDER SLOTS | ON BOLSTERS |
| FLAG HOLDER W/ THUMB SCREWS | 1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL |
| AIR AND ELECTRICAL CONNECTIONS | FOR FLIP/REMOVABLE AXLE |
| WHEEL WELL COVERS | 3/8" FLOORPLATE, ONE PIECE OVER TIRES ONLY, BOLT-ON |
| ALUMINUM STORAGE BASKETS BOLT-IN | (1) FRONT OF DECK, (1) AT REAR OF DECK |
| FLIP/REMOVABLE AXLE | (1) 25,000# 3/4" WALL AXLE, (4) 275/70R22.5 (H) TIRES, WHEELS (ACCUSHIELD OUTERS, STEEL DISC INNERS), RAISING AND LOWERING VALVE, AMBER L.E.D. STROBES IN 3RD TAILLIGHT POSITION, BATTERY BACK-UP W/ RECHARGEABLE FEATURE, FLAG HOLDERS W/ THUMB SCREWS. HOT DIP GALVANIZED |

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.