

HALE

TRAILER

BRAKE & WHEEL



A034929
VIN: 45307

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

Model: T2-35CC-HRG-T1
Capacity in tons: 35

1. GOOSENECK

Gooseneck design
Loaded 5th wheel height
Swing radius
Support cylinder
Power source
Gooseneck locks
Electrical receptacle
Coverplate

Ratchet
51"
90"
Hydraulically operated with 4" x 3" cylinder mount cross member
Hydraulic couplings: 3/4" fixed at front with piping for wet line
Ratchet
Seven pin connector
Aluminum

1 Additional gooseneck specifications

- 1) Formed aluminum diamond plate light bar mounted in gooseneck base with 4 LED stop/tail/turn lights and 2 clear work lights wired to marker light circuit with on/off switch
- 2) Fully enclosed chain bar with aluminum diamond plate and lockable hinged lid (paddle latches)
- 3) Full penetration weld on gooseneck gusset
- 4) Base pivot tube reinforcement
- 5) Ratchet pivot shaft collar

2. DECK

Deck section design
Deck section length
Deck section width
Loaded road clearance
Loaded deck height
Flooring
Gooseneck/deck connection
Deck/rear bridge connection
Outriggers
Reinforced top flange of sidemember
Slope front of deck top down
Heavy duty front folding ramps
Expanded metal
Additional deck specifications

Four beam
24'-0" (23'-6" clear)
8'-6"
6"
22"
1-1/2" apitong secured with deck screws; no lumber between mainbeams
Horizontal pin and plate with remote lock
Fixed/welded
12" swinging/removable with double hook-on at front of deck
None
With smoothplate & traction bars
32" wood filled
Between mainbeams 1st deck section at front
None

3. REAR BRIDGE

Rear bridge section width
Loaded rear bridge height
Number of axles
Axle spacing
Axle capacity
Brakes
Anti-lock brake system
Wheels

8'-6"
40"
2
54"
25,000# GAWR = 20,280#
16-1/2" x 7" air actuated with spring brakes on one axle
Two (2) sensor, one (1) modulator system
Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished
Eight (8) 255/70R22.5 (H) 16PR radials

Tires

Suspension
Exhaust Valve
Manual raising & lowering (+3"/-3")
Suspension options
Rear Bridge Center Section
Wide center bolster
Rear half bolster
Front bridge ramp
Fenders
Connections for future removable axle
Additional rear bridge specifications

Ridewell air
Manual
New style +3",-3" with override chains on all axles
1) Liquid filled air gauge mounted in 2nd axle curb side air bag with decal
Boom well, cross members recessed - recess 1st member additionally
With chain slots and flagholder slots
Rear of axle 2
Sloped to deck outboard of mainbeams with smoothplate and traction bars
1/4" floor plate over tires only
None
1) Omit 1st cross member in rear bridge section (shock mount cross member) for open boom well

4. GENERAL

Lights and wiring

12 volt system with the following:
All lights to be L.E.D. including mid-turn, excluding license plate light
All marker/I.D. lights to be 3/4" bullet style
1 marker each side of gooseneck at front
3 marker lights each side of deck including mid-turn
strobe lights and switch at rear
Battery back-up system with switch at rear to flash all marker/tail lights and strobe lights, battery mounted in battery box.

Paint
Lash rings

Valspar standard Talbert black, R-Cure 800 series paint with ZINC Rich primer
12 Total
4 each side of deck (bent style), 8 total
1 each bolster and half bolster end (straight style), 4 total

1 Estimated empty weight
Additional general specifications

15,650#
None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.