

HALE

TRAILER

BRAKE & WHEEL



A035292
VIN: A7602

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Magnitude 452 Jeep for Magnitude 65, 75 or 80 models (jeep as 2-axle or 2-axle plus 3rd flip axle configuration) (Model: 452JEEP)	
	Est. Wt.: 11,260# +/- 3%
TRAILER - GENERAL	
Capacity: 45 tons GAWR and tire rating determine legal loads	
Length (Jeep Only): 29 feet 5 inches	
Width: 8 feet 6 inches	
Compatibility: Magnitude 65 75 80 ton trailers	
GOOSENECK	
Gooseneck Design: Fixed narrow	
Loaded Fifth Wheel Height: 50 inches	
Swing Radius: 104 and 80 inches (removeable)	
DECK	
Deck Design: Beam design	
Fifth wheel: Sliding fifth wheel with a 52.5 inch loaded fifth wheel height (60 inch slide)	
Deck to Bogie Connection: Fixed	
AXLES	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields: None	
SUSPENSION	
Suspension: Air ride	
Framework: All main longitudinal members fabricated with 100,000 PSI minimum yield steel flanges with 50,000 PSI webs	
ABS: Not required	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 lvL One buffed wheels	
Tires: 275/70R 22.5 Michelin XTY2 Tires	
Hubodometer: None Standard	
Tire Inflation: Tire Inflation System installed	
LIGHTING	
Electrical System: DOT sealed beam and harness	
Electrical Receptacle: J560 7-pin connector	
Additional Marker Lights: Additional Marker Lights	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
AVAILABLE COMPONENTS	
Flip Axle: Flip axle -LvL One buffed wheels - 275/ 70R 22.5 Tires on Separate Order	
MISCELLANEOUS	
Registration/Document Holder: Registration/document holder intalled	

Additional Options:	
Spare Tire Carrier one roadside one curbside	
S Cam Tube Protection	
Poly Fenders	
Zinc Rich Primer	
2 spare tires 275 with lvl one buffed wheels for carrier	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.