

# HALE

## TRAILER

### BRAKE & WHEEL



**A035346**  
**VIN: 000189**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

**Base Weight:** 13,800

#### 42ET3X 42 ft. Tridem Equipment

##### TRAILER

<b>Overall Length</b>	*NPO*: 45 ft.
<b>Overall Width</b>	102 in.
<b>Weight lbs +/- 3%</b>	16196, including options

##### GOOSENECK

<b>Coupler</b>	Weld in King Pin
<b>Coupler Plate</b>	5/16 in. Hi-Tensile, 48 in. Height
<b>Coupler Location</b>	18 in.
<b>Length</b>	10 ft. 6 in.
<b>Cross Members</b>	Hi-Tensile 4 in. Jr. I-beam @ 16 in. O/C
<b>Swing Clearance</b>	83 in.
<b>Floor</b>	*NPO*: 1 3/8 in. Apitong
<b>Web</b>	1/4 in. Hi-Tensile

##### DECK

<b>Deck Length</b>	*NPO*: 28 ft. 7 in.
<b>Loaded Deck Height</b>	35 in.
<b>Main Frame</b>	3/8 in. x 5 in. Top and Bottom Flanges 100 KSI
<b>Cross Members</b>	Hi-Tensile Standard 4 in. I-beam @ 12 in. O/C on Lower Deck w/ Knee Braces
<b>Side Rail</b>	6 in. @ 8.2 Channel
<b>Web</b>	3/16 in. Hi-Tensile
<b>Floor</b>	*NPO*: 1 3/8 in. Apitong
<b>Landing Gear</b>	Dual 2 Speed
<b>Load Securement</b>	14, Pair of Side Mount D-Rings: 9 Pr. on Main Deck; 3 Pr. on GNK; 2 Pr. on B/T; Evenly Spaced as Possible

##### SUSPENSION/AXLES

<b>Axles</b>	25,000 lbs Capacity
<b>Air Lift</b>	Air Lift c/w Control Box: Lead Axle
<b>Spread</b>	49 in.
<b>Suspension</b>	Ridewell RAR 260 U/S 6 1/2 in. Air Ride 25,000 lbs - includes air gauge and dump valve in enclosure
<b>Brakes</b>	Quick Change 12 1/4 in. x 7 in.
<b>Brake Chamber</b>	#3030, All Axles
<b>Air Brake System</b>	2S/1M
<b>Air Tank(s)</b>	Aluminum
<b>Slack Adjusters</b>	Automatic
<b>Camshafts</b>	28 Spline Non Enclosed
<b>Hubs &amp; Drums</b>	8 Stud Unimount C / W Cast Drums
<b>Tires</b>	Tire Upgrade to 245/70R17.5 Continental HTL2 ECO
<b>Wheels</b>	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)
<b>Pressure Equalization</b>	*NPO*: 3, Crossfire Dual Tire Pressure Equalization System

**BEAVERTAIL**

**Length** 5 ft. @ 8 degree slope, Planked

**RAMPS**

**Rear** \* 38 in. x 76 in. Air Operated Planked In

**Front** Two Removable Aluminum Ramps to access GNK, 5ft long, Storage under GNK deck

**GENERAL SPECIFICATIONS**

**Electrical System** Modular, Vapor Proof GROTE Ultra Blue

**Front Connector** SAE J560 7 Pin

**Rear Connector** 4 Pin Plug

**Lights** LED CMVSS 108 / FMVSS 108

**Lights** LED Light Enhancement Package (6 Additional Lights per Side)

**Lights** Amber Flashing Strobe (Mounted in Ramps)

**Color** Galvanized

**Mudflaps** 1 set of BWS at rear

**Fenders** 5/16 in. Heavy Duty Smooth Plate Fenders - NO Traction Bars

**Toolbox** Alum. (45 in. X 18in. X 14in.) + Brackets (Driver's Side)

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.