

HALE TRAILER BRAKE & WHEEL



A035351
VIN: P4063

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Magnitude 402 Jeep (Model: 402JEEP)	
MAGJEP402****602	Est. Wt.: 7,640# +/- 3%
TRAILER - GENERAL	
Capacity: 40 tons GAWR and tire rating determine legal loads	
Length (Jeep Only): 29 feet 2 inches	
Width: 8 feet 6 inches	
Compatibility: Magnitude 60 and 65 ton trailers with optional flipboxes	
GOOSENECK	
Gooseneck Design: Fixed Narrow Width	
Loaded Fifth Wheel Height: 50 in.	
Swing Radius: Two (2) position king pin locations at 84 in. and 108 in. swing radius	
DECK	
Deck Design: Beam design	
Fifth wheel: OEM Standard , 60 in. approximate slide adjustable	
AXLES	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields: None	
SUSPENSION	
Suspension: Air ride	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
DECK	
Supports: Telescopic	
SUSPENSION	
ABS: Not required	
Load Scale: None Standard	
WHEELS AND TIRES	
Tires: 275/70R 22.5 H ply OEM Standard	
Wheels: 8.25 x 22.5 1vL One buffed/steel disc inside - hub-piloted	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: DOT sealed beam and harness	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.