

HALE

TRAILER

BRAKE & WHEEL



A036106
VIN: 45460

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: T4-60SA-HRG-(3+1)-T1

Capacity in tons: 60

Gooseneck design	HRG - Ratchet Design
Loaded 5th wheel height	51"
Swing radius	108"
Alternate kingpin	Removable kingpin stations for 108" and 96" swing radius
Support cylinder	Hydraulically operated
Power source	Hydraulic couplings: 3/4" fixed at front of gooseneck
Gooseneck locks	Ratchet design
Electrical receptacle	Seven pin connector
Additional gooseneck specifications	1) Aluminum cover plate 2) Full penetration weld on gooseneck gusset 3) Base pivot tube reinforcement
Deck section design	Four beam
Deck section length	27'-0" (26'-6" clear)
Deck section width	8'-6"
Loaded road clearance	6"
Loaded deck height	22"
Flooring	2" apitong secured with deck screws; no lumber between main beams
Mainbeams	16" T-1A
Gooseneck/deck connection	Pin and plate with remote lock
Deck/rear bridge connection	Fixed/welded
Outriggers	12" swinging/removable with double hook-on at front of deck
Heavy duty front folding ramps	32" with smooth plate and traction bars
Additional deck specifications	Bucket well, recess last 4 deck cross members in deck between main beams and cover with 1/4" plate
Slope front of deck top down	Yes with plate and traction bars
Slope front of deck bottom up	10 3/4" Finished main beam height

Expanded metal	Between main beams 1st two deck sections at front and 1st two deck sections ahead of deck bucket well
Rear bridge section width	8'-6"
Loaded rear bridge height	41" main beams, 37" bolsters
Number of axles	3
Axle capacity	25,000# - GAWR = 24,700#
Axle spacing	54"
Brakes	16-1/2" X 7" air actuated with spring brakes on one axle
Anti-lock brake system	None required - GVWR is greater than 120,000#
Wheels	Ten (10) stud; 285.75mm B.C. aluminum disc hub piloted system with oil seals, inner aluminum wheels polished with outer aluminum wheels DURA BRITE
Tires	Twelve (12) 275/70R22.5 (H) 16 PR Cooper radials
Suspension	30,000# Capacity Ridewell air
Suspension options	<ol style="list-style-type: none"> 1) Over ride chains on all axles 2) Talbert manual raising and lowering (+3", -3") 3) Air lift on axle 3 4) Manual exhaust 5) Liquid filled air gauge in 2nd axle curb side air bag with decal
Recessed crossmembers	Boom well - 1st member recessed additionally
Wide center bolster	Yes with chain slots and flag holder slots
Rear half bolster	Rear of axle 3 with flag holder slots
Front bridge ramp	Sloped to deck outboard of main beams with plate and traction bars
Rear bridge fenders	None
Additional rear bridge specifications	<ol style="list-style-type: none"> 1) Omit 1st cross member in rear bridge section (shock mount cross member) for open boom well 2) Connections for 4th axle (SN45461) and future spreader bar (3+1)
Axle extension	None
Lights and wiring	<p>12 volt system with the following:</p> <p>All lights to be LED including mid-turn, excluding license plate light</p> <p>3 markers each side of deck including mid-turn</p> <p>Strobe lights with switch at rear of axle 3</p> <p>Battery back-up system with switch to flash all marker/tail lights and strobes</p>
Paint	Valspar standard Talbert black, R Cure 800 series paint with zinc rich primer
Lash rings	<p>30 Total</p> <p>8 each side of deck (bent style), 16 total</p> <p>1 each side between deck mainbeams mounted on web in the first two deck sections (bent style), 4 total</p> <p>1 each side mounted on sides of deck boom well plate in-line with the last two crossmembers (bent style), 4 total</p> <p>1 each bolster and half bolster end (straight style), 6 total</p>
Estimated empty weight	23,410#
Design notes	<p>60 ton capacity in a 13'-6" two point rigid load base with a 108" swing radius and 4 axles close coupled/3+1</p> <p>55 ton capacity in a 12'-0" two point rigid load base with a 108" swing radius and 4 axles close coupled</p> <p>55 ton capacity in a 13'-6" two point rigid load base with a 108" swing radius and 3+1 E1 nitro axles extension</p> <p>Frame is reinforced for a future 4th axle & 3+1 SPREAD</p> <p>Trailer overall length 53'-4"</p>
Additional general specifications	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.