

HALE

TRAILER

BRAKE & WHEEL



A036718
VIN: 4545

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: T(4)-55CC-HRG-T1

Capacity in tons: 55

1. GOOSENECK

- Gooseneck design
- Loaded 5th wheel height
- Swing radius
- Alternate kingpin
- Support cylinder
- Power source
- Gooseneck locks
- Electrical receptacle
- Additional gooseneck specifications

- RATCHET
- 52"
- 108"
- Removable kingpin stations for 108" and 90" swing radius
- Hydraulically operated with 4" x 3" cylinder mount cross member
- Hydraulic couplings: 3/4" fixed at front of gooseneck
- RATCHET
- Seven pin connector
- 1) Aluminum diamond cover plate
- 2) Formed aluminum diamond plate light bar mounted in gooseneck base with 4 LED combination stop/tail/turn/back-up lights (back-up lights wired to switch) and 2 clear LED work lights wired to marker light circuit with on/off switch
- 3) Fully enclosed chain bar with aluminum diamond plate and lockable hinged lid (paddle latches)
- 4) Full penetration weld on gooseneck gusset
- 5) Base pivot tube reinforcement
- 6) Stainless steel gooseneck web inserts

2. DECK

- Deck section design
 - Deck section length
 - Deck section width
 - Loaded road clearance
 - Loaded deck height
 - Flooring
 - Mainbeams
 - Gooseneck/deck connection
 - Deck/rear bridge connection
- Four beam
 - 26'-0" (25'-6" clear)
 - 8'-6"
 - 6"
 - 18"
 - 2" apitong secured with deck screws; no lumber between main beams
 - 12" T-1A
 - Horizontal pin and plate with remote lock
 - Fixed/welded

Outriggers	12" swinging/removable with double hook-on at front of deck
Additional deck specifications	Bucket well, recess last 4 deck cross members in deck between main beams and cover with 1/4" plate
Slope front of deck top down	With plate and traction bars
Heavy duty front folding ramps	32" with smooth plate and traction bars
Expanded metal	Between main beams 1st deck section at front and last deck section at rear, in front of bucket well

3. REAR BRIDGE

Rear bridge section width	8'-6"
Loaded rear bridge height	41" frame; 37" bolsters
Number of axles	3
Axle capacity	25,000# - GAWR = 24,700#
Axle spacing	54"
Brakes	16-1/2" X 7" air actuated with spring brakes on one axle
Anti-lock brake system	None required - GVWR is greater than 120,000#
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel (BLACK), outer aluminum wheels DURA-BLACK WITH DURA-BLACK CENTER CAPS AND VALVE STEMS
Tires	Twelve (12) 275/70R22.5 (H) 16PR radials
Suspension	Ridewell air
Suspension options	<ol style="list-style-type: none"> 1) Over ride chains on all axles 2) Talbert manual raising and lowering (+3", -3") 3) Air lift on axle 3 4) Manual exhaust 5) Liquid filled air gauge mounted in 2nd axle curb side air bag with decal
Rear Bridge Center Section	Boom well, cross members recessed - recess 1st member additionally
Wide center bolster	With chain slots & flag holder slots
Rear half bolster	Rear of axle 3 with flag holder slots
	Stainless steel mudflap brackets with red Talbert logo
	Stainless steel light panel insert each side outboard mainbeams
Front bridge ramp	Sloped to deck outside of main beams with plate and traction bars
Rear bridge fenders	None
Additional rear bridge specifications	<ol style="list-style-type: none"> 1) Omit 1st cross member in rear bridge section (shock mount cross member) for open boom well 2) Connections for future 4th axle

4. GENERAL

Lights and wiring	<p>12 volt system with the following:</p> <p>All lights to be LED including mid-turn, excluding license plate light</p> <p>All marker/I.D. lights to be CLEAR lens, 3/4" bullet style</p> <p>3 marker each side of gooseneck at front</p> <p>7 markers each side of deck including mid-turn (3 markers, mid-turn, 3 markers)</p> <p>1 marker each bolster end</p> <p>4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit</p> <p>Rear bridge work light (ref. UP38552 - SN42977) mounted on front side of first recessed cross member wired to switch at rear on marker light circuit</p> <p>Strobe lights with switch at rear of axle 3</p> <p>Chrome trim rings on all lights except the work light</p> <p>Battery back-up system with switch to flash all marker/tail lights and strobes</p>
Paint	Valspar standard Talbert black, R-Cure 800 series paint with ZINC RICH primer

Lash rings	20 total - 6 each side of deck (bent style), 12 total 2 each side between deck main beams in the first two deck sections (bent style), 4 total 2 each side mounted on side of deck bucket well plate in-line with the last two cross members of deck (bent style), 4 total
Estimated empty weight	22,430#
Design notes	Not reinforced for spread axle capabilities
Additional general specifications	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.