

# HALE

## TRAILER

### BRAKE & WHEEL



**A036928**  
**VIN: 036009**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

#### GVWR

GVWR:	Trailer to meet 68,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
Product Type:	HT Composite
Composite New Design:	Composite New Design

#### GEOMETRY

Length - Exterior:	53'-0"
** Length - Interior:	52'-6" Nominal Lining To Lining
Width - Exterior:	102.36"
** Width - Interior:	101.5" Nominal Lining To Lining
Height - Exterior:	13'-6"
Height - Interior:	110" Nominal
Deck Height:	Standard application
Fifth Wheel Height:	47"
King Pin Location:	36"
Landing Gear Location:	107" from King Pin (+ 1"/-1/4")

#### TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
Tire Size:	295/75R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
* Wheel Finish for Steel:	Hot Dip Galvanized.
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
* Valve Stem & Cap:	TR-572 Valve Stem# 8900HALNC for use w/PSI; w/o Cap

#### UPPER COUPLER

Approach Plate:	1/4" thick 80,000 Lb Yield - 6 Support Channels
King Pin (BTM Main) Plate:	1/4" thick 80,000 Lb Yield
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin
* Front Bottom Rail:	Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle
Upper Coupler Tube Qt'y:	(1) Tubing Application - Joggled

#### BODY/BASE

Forward Crossmember:	Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L
Landing Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)
Bay Area Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L
Running Gear C/M Size:	4" High
Running Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'
Slider Body Rail (VT):	208" Rail Length

#### FLOOR

Upper Coupler Type:	3.40" Joggled with Exposed Coupler Top Plate (New STD)
Floor Specification:	1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood

Floor Ratings - VT: 18,000 lbs Rated Floor per TTMA- Standard HT Dry Van Floor Rating  
Floor- Assembly Method: Wood Floor Assembly  
Floor Screws: (3) 0.31" Dia. screws per Board on I beams  
Threshold-Finish: Hot Dip Galvanized  
Threshold Plate: 0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts  
Threshold-Application: Standard Application

**FRONT**

Front Corner Radius: 4" Extruded Aluminum  
Front Panel & Color - Dry: 0.05" Aluminum Prepainted White w/ natural color rivets  
Front Corner Mat'l - Dry: Extruded Aluminum  
Front Posts: (4) 2.5" Deep (16Ga) Steel Hats - Non AAR  
Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid  
Front Receptacle(7-Way): Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug  
Front Receptacle(7-Way) - Options: Phillips QCS Plug connector  
Gladhand/7-Way Location: Overlaid on Lower Roadside Front  
\* Corner Radius Protector: (2) 0.125" X 12" Alum Diamond Plate Each Side at Top

**SIDE**

Composite Side Material: 6.5 mm thick (0.5 outer/inner skin) Composite Panel, Pre-painted White, Both Sides, with natural color rivets  
Side Posts: 14 Gauge Galv Steel 'A' Slotted Logistic Insets with Composite Panel color matching Outer Closure (For Composite New STD)  
Side Post Centers: 48.5" C/L Stiffener (Side Closure) - For Composite  
Side Top Rail: Side Top Rail for Composite (New STD)  
Side Bottom Rail: Side Bottom Rail for Composite (New STD)  
\* Skylight-General Spec.: Cluster Sky Light Lens on side wall for 24" or bigger post pitch (Single lens on two panels, next to each other, for 16" or less post pitches.)  
\* Skylight-Quantity: Total 5. Both Side Wall Panel. (3) on Roadside and (2) on Curbside  
\* Skylight-Location: Composite Both Side Wall Panel Location from Front, Specifically on panels #5, #9 on C/S & #3, #7, #11 on R/S  
Fasteners to Bottom Rail: Standard Rivets to attach C/Members to the Side Bottom Rail

**REAR**

Rear Frame: Swing Door, 2.5" New Door Header Standard Trailers (with 1 Lock Rod Per LH & RH Door)  
Rear Door Opening Spec.: Standard Application  
Floor Level: Door to be Flush with Floor (STD)  
Door Type for Dry Van - SW: 0.5" Composite Swing Door. Galvanized Prepainted White Interior & Exterior Skin  
Option - Door Install Instruct: Standard Door Installation per Manufacturer's Recommendation  
Option - Door & Hardware: One(1) Rubber Door Bumper Standard (1" Deep) on Hinge of each Swing Door  
Door Holder Type for Swing Door: Standard Door Holdback  
\* Hinges: Four (4) Aluminum Hinges per Door  
\* Additional Hinge Option: Additional One(1) Aluminum Hinge (Total 5 Per Door)  
\* Rear Underride Guard: 4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal. Rear Impact Guard (RIG) 30  
Option - Horiz Member/Other: One piece roll formed w/continuous welding  
Underide Bolt Spec.: Zinc plated bolts & nuts - Standard  
Dock Bumper: Pair 3" X 6" Mold Bolted Bumper  
Rubber Bumper Location: Inboard of Light Protector Bars (Standard)

**LIFT GATE**

Roof Panel: 0.040" Aluminum  
Roof Bow: 16 Gauge Galvanized Steel Anti-Snag  
Roof Bow Centers: 24" Centers Full Length

**LINING/SQUEE**

Front Lining: 0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height

- \* Base Side Scuff: 6.0" High Integral Alum (New Composite STD) with Additional scuff (Plastic, Corrugated or Wood)
- \* Additional Side Scuff: 18Ga x 6.5"H Corrugated Steel Butted to Intergral Aluminum
- \* Front Scuff: 0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)

**LANDING GEAR**

- L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG
- L/Gear Mt'g Method: Inboard Mounting (Standard)
- L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile
- L/Gear Ground Clearance: Nom. 12" Ground Clearance
- L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate
- L/Gear Crank Handle: Roadside
- L/Gear Options: None (HT STD)
- L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

**RUNNING GEAR**

- Bogie Type: Sliding Tandem(2) Axle Bogie
- Axle Spacing: 49" Axle Spacing
- Axle ABS System: Tandem Axle w/2S1M ABS System
- Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
- Option-Related Bogie Stopper Feature: STD plug stopper
- Susp. Manufacturer: Hendrickson
- Suspension Capacity: Standard Duty
- Hendrickson Susp. Specification: Hendrickson Vantraxx HKANT40K Air Ride
- Surelok (Anti-Dock): Surelok (Anti-Dock) Installed
- Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
- Susp. Sub-Frame: Hendrickson K-2 STD Duty
- Type of Susp Spring: Air Bag
- Spring Specification: Air Bag
- \* Axle Diameter: 5.75"
- Axle Supplier: Hendrickson
- Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
- Axle-Track Length: 77-1/2"
- Axle-Spindle Type: Tapered Spindle
- Brake Lining Size: 16.5" X 7"
- Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)
- Brake Control System: 2S/1M Wabco ABS
- Spring Brake Control: Sealco 110500 Springbrake Priority
- Brake Cont-Hose & etc.: Standard Air Line & Hose Application (US&Canada)
- \* Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
- \* Brake Chamber Spec.: Wabco Premium Chamber
- \* Stroke Length: 3" Long Stroke Length
- Hub Specification: HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
- Drum Specification: HT Standard (KIC) Cast Drum
- Hub/Drum-Opt(Nut&Other): Standard
- Bearing Specification: Stemco
- \* Lubrication Spec.: Chev Delo (Syn) Grease
- \* Wheel Seals Spec.: Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
- \* Tire Inflation Spec.: Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
- Tire Inflation Pressure: 100 PSI
- \* Tire Inflation Lamp Location: Indicator PSI Light at Roadside Mounted over corner radius. (STD location)
- \* Tire Inflation Lamp Spec.: 33 Series Lamp

**ELECTRICAL**

- Harness-General Spec.: Molded Color Code Phillips Harness with QCS Plug

Harness-Special Feature:	Manufacturer's Standard Feature
Front Light:	(2) Trucklite 33275Y LED PC Rated Mounted with Grommet
* Rear ID Header Light:	(5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp with Antitheft Bracket
Rear Side Marker Detail Spec:	(2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware
Rear Side Marker MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
S/T/Tail Light-Quantity & Type:	(4) Trucklite 40 or 44 Series (Round Style) or Equivalent
S/T/Tail Light-Detail Spec:	(4) Trucklite 44331R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets
Main Mid-Turn Light:	Install the Mid turn lamp
Mid-Turn Mounting Method:	Mounting Bracket
* Main Mid-Turn Light-Detail Spec:	(2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets & Anti-theft brackets
ABS Light Detail Spec:	(1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
ABS Light MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
License Light:	(1) Trucklite 33210C LED with 33815 Anti-Theft Flange
Option Related Harness/Wiring:	Standard
Electrical Related Regulation:	Standard Application

**MARKING/DECALS**

HT & Product Type Decal Package:	Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)
Decal Package:	Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Decal Opt 2-Decal Location:	Standard Application
Decal Opt 3-Decal Installation:	Standard Application
* Conspicuity Vendor:	Avery
Conspicuity Markings:	Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install:	Standard Install Location - Roadside Below Door Sill
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
* Document Holder/Manifest Loc.:	Overlaid on Lower R/S Front. 18" from the bottom of the front sheet between the front post & corner radius on the roadside

**PAIN/FINISH**

* Upper Coupler Finish:	Galvanized-Whole upper coupler section
* Crossmembers Finish:	HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
* Axle & Components Finish:	Black Undercoating
* Susp. Sub-Frame Finish:	Black Undercoating
L/Gear(K-Bracing) Finish:	Hot Dip Galvanized
* L/Gear(Upper Leg) Finish:	Hot Dip Galvanized
Rear Frame-Finish:	Hot Dip Galvanized
Rear Frame-Paint Color:	None (For Galvanized or Stainless Steel)
Rear Underride-Finish & Spec.:	Hot Dip Galvanized & Welded Horizontal Member
Rear Underride-Paint Color:	None (For Galvanized or Stainless Steel)

**MISCELLANEOUS**

Mudflap Provider:	Factory Furnished Mudflaps
Mudflap Specification:	24"x30" White Plain Plastic with Hyundai Logo
Mudflap Mounting Loc.:	Suspension Frame
Mudflap Mounting:	STD Location w/ H.D Washer Retainer
* Lift Pad Spec.:	Install HT Occasional use lift pads for delivery, with HYUZ decals

**DISCLAIMER**

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.