

# HALE TRAILER BRAKE & WHEEL



**A036981**  
**VIN: 22545**

SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

FRAMELESS TRAILER SS		SERIAL NO. 5MADN4026DC022545
		MODEL NO. TNAR40NF65.750-2013
		WEIGHT 13225 LB. +/- 3PCT, 64 YDS.
<b>FLOOR</b>		
LOAD PROFILE	MATERIAL, 80 GVWR	SAME AS: 21186
LENGTH	40 FT.	
WIDTH	102 WIDE	
FLOOR	PANEL FLOOR (NO CROSSMEMBERS)	
CROSSMEMBER SPACING	10 IN.	
TOW MOTOR PACKAGE	NO	
FLOOR CHAIN TIE DOWNS	NO	
COIL RACK ANGLES	NO	
3-1/2 ANGLES UNDER RAIL	NO	
FLOOR LINER	NONE	
LOAD LEVEL INDICATOR	NO	
VIBRATOR	NONE	
RUBBER SEAL	YES	
TIRE CARRIER	(1) FACING FORWARD	0
SIDES	INSET S.S. VERTICAL PANEL	
WALL HEIGHT	66 IN.	45 HVY
PANEL TYPE	(0) - LT. VERT. (0) - STD. VERT. (45) - HVY. VERT.	USE QTY (45) PANELS, ALL H.D. SIDE PANELS
<b>PANEL SELECTION</b>		DO NOT BOW TOP RAIL, SIDES MUST BE STRAIGHT
TOP RAIL OPTION	TOTAL OF 66	
REAR POCKET SLOPE	2.75	
REAR POCKET HEIGHT	81.625	
TARP BAR	NONE	
WALL LINER	NONE	
INSULATION	NONE	
<b>BULKHEAD</b>		
HOIST	8-5-265 (39-40), CUSTOM	
REMOTE BLEEDER/GREASE	NONE	
BULKHEAD HEIGHT	70.375	
BULKHEAD TAPER	NONE	
BULKHEAD OPTIONS	(STD) 3/16	
BULKHEAD TYPE	RADIUS CORNERS	
BULKHEAD SLOPE PLATES	NO	
DOGHOUSE STYLE	STANDARD	

**FRAMELESS TRAILER SS**

BULKHEAD STEPS	BULKHEAD DOOR	ADD STEPS ON BULKHEAD MAN DOOR
DRIVERS SIDE PANEL STEPS	STD. LAST OUTSIDE ONLY	
CURB SIDE PANEL STEPS	LAST OUTSIDE ONLY	ADD TWO STEPS ON INSIDE OF GATE D/S
TARP HOOKS	BULKHEAD AND TAIL GATE	
TARP BASKET	NO	
CAT WALK	NO	
SHOVEL HANGER	YES	
FENDERS	CORNER WFLAPS	
ALUMINUM ROLL CAP	SEE NOTES	ROLL CAP TO HAVE 12 RISE, SAME CAP AS 17499
LIGHTS	OOO OOO OOO	
LIGHT TYPE	GROTE L.E.D. W/ GROMMET	
LIGHT PANEL	3 LARGE-3 SMALL-3 LARGE (FULL LIGHT PANEL)	
LIGHT SHIELD/APRON	(STANDARD) 1-1/2 FULL LIGHT SHIELD	
MARKER LIGHTS	3 EACH SIDE	
MIDTURNS	1 PAIR L.E.D. (NON-COMBO)	
BACK-UP LIGHTS	NONE	
REAR POCKET LIGHTS	1 PAIR	
AUXILARY CABLE (4 OR 7 WAY)	NONE	
<b>GATE</b>		
GATE HEIGHT	69.25	
GATE WIDTH	96	
GATE PANEL TYPE	HEAVY VERTICAL PANEL	(5) VOID
GATE OPERATION	BALL VALVE (STANDARD)	
HINGE TYPE	O. S. SWING D.S. W/ GROUND CONTROL	GATE TO SWING TO D/S
COAL DOOR	24	SIDE SWING GATE HINGES TO BE STEEL BOLT ON STYLE ILO ALUM.
CHUTE	NONE	WELD ON. REF 17499 SPECIAL GATE
DOUBLE HANDLE DOOR	NO	USE HEAVY DUTY GATE BOTTOM FOR VERTICALS
1/2 ROUND ON GATE	NO	USE HEAVY PANELS FOR GATE
ANGLE ON TOP OF GATE	NO	
SPREADER CHAINS	NO	
WINDERS / SAFETY LATCH	WINDERS (1) EACH SIDE	WINDERS ON BOTTOM OF GATE, APRON WILL NEED NOTCHED
GATE LINER	NO	
<b>CHASSIS</b>		
MODEL	TANDEM	
SUBFRAME TYPE	102IN., WIDE I-BEAM (17IN.)	
SUSPENSION	HEND. INTRAAX AA-250 TP	RIDE HEIGHT: REAR 17, FRONT 18-1/2
PIN TO AXLE SETTING	433, 29 REAR SETTING	
SPRINGS	AIR	
SUSPENSION CONTROL	BALL VALVE (STANDARD)	
AXLE SPACING	122 IN.	
AXLES	(1) AXLE FOR INTRAAX ONLY	
ABS	2S/1M - (MERITOR / WABCO)	
BRAKE SHOES	7 XL, W/30-30 CHAMBERS	
SLACKS	HALDEX	
CAM GUARDS (ALL AXLES)	STANDARD	

**FRAMELESS TRAILER SS**

TIRES	(4) MICHELIN XZE-2 11R 24.5 14 PLY	XT1
CHROME TOP HATS	NONE	
TIRE INFLATION SYSTEM	NONE	
RIM TYPE (PER AXLE)	ALCOA HP 24.5X8.25 10 HOLE MILLED	
HUB AND DRUM	(2) GOLD W/ MW LIGHT HUB HP 10 STUD TP LS 7	
SYNTHETIC LUBRICATION	NO	
HUBODOMETER	NONE	
DUST COVERS	NO	
FLAPS REAR OF TIRES	STD. FLAP	REMOVABLE REAR FLAPS
FLAPS FRONT OF TIRES	STD. FLAP	NEED 6 MIN BETWEEN REAR TIRES AND REAR FLAPS
AIR GAUGE/SYSTEM	NONE	CUSTOMER WANTS RIGHT WEIGHT SCALE SYSTEM
AIR TANKS	12 STEEL AIR TANKS (STANDARD)	
TOW HOOKS	NONE	
ENCLOSURE FOR SWITCHES	NONE	
PIN SETTING	16 IN.	
TRACTOR DRIVE MODEL	TANDEM DRIVE	
REGISTRATION HOLDER	NONE	
DOLLIES	HOLLAND D.S.	
HYD. HOSE FITTING	1 X 108 HOSE W/WING FITTING	19 HYDRAULIC HOSE WITH MALE QUICK CONNECT (PARKER)
DRAFT ARM TYPE	3/8 ALUM. W/STD. SPLIT PIN, WIDE 84 DA	
5TH WHEEL PLATE	BREAK-AWAY PIN @ 49 IN. HIGH	
<b>LIFT AXLE</b>		
TYPE	(1) INTRAAX AA250L TP (4) TIRES	
NO. OF LIFT AXLES	1	
LIFT KIT	(1) HEND. UBL-002 (INTRAXX 96 AND 102)	
AXLE	AXLE FOR INTRAAX ONLY	
TIRES	(4) MICHELIN XZE-2 11R 24.5 14 PLY	XT1
RIM TYPE (PER AXLE)	ALCOA HP 24.5X8.25 10 HOLE MILLED	
HUB AND DRUM	(2) GOLD W/ MW LIGHT HUB HP 10 STUD TP LS 7	
BRAKE SHOES	7, W/30-30 CHAMBERS	
CONTROLS	BALL VALVE - STANDARD (COMMON AIR)	
DISTANCE	122 IN.	
<b>TARP</b>		
TARP MANUFACTURER	NONE	
TARP CONTROL	NONE	
TARP COLOR	NONE	
BOW HOLDERS	STANDARD	
BOWS	HI RISE 12 W/ NO TARP	
<b>PAINT</b>		
CHASSIS COLOR	SILVER	
PIN STRIPING	BLUE	MEDIUM BLUE V2040
BOARD COLOR	NONE	(4) TOTAL PLACKARDS, (1) FRONT, (1) REAR AND (1) EACH SIDE
MAC LOGOS	MAC BLACK	(1) D/S CENTER OF BH, (1) P/S CENTER OF GATE AND (1) EACH SIDE
OPTIONAL SIGNS	(2) DIAMOND BACK PLACKARD	IN CENTER OF TRAILER.

**DISCLAIMER**

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.