





A037247
VIN: Q34100

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer
 f
t
in
@
v

800-232-6535 *FINANCING AVAILABLE

Series: **HYDRAULIC DETACHABLE GOOSENECK** Model: **RTN80TD3-R4/5/6A-RA TRAILER**

Item	Description
CAPACITY	80 TONS IN ANY 16'
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
DETACHABLE REAR SECTION	FOR DECKS AND SHIMMING (HORIZONTAL PIN)
DROPSIDE DECK	16 3/4" SIDE HEIGHT WITH 2" APITONG AND WITH TRANSITION RAMP
PLATFORM WIDTH	9'-0"
PLATFORM LENGTH	30'-0"
PLATFORM HEIGHT/ROAD CLEARANCE	26"/6" LOADED-ADJUSTABLE (20" DEEP MAIN BEAMS)
CROSSMEMBER SPACING	ON 24" CENTERS
AUXILIARY CROSSMEMBERS	OUTSIDE OF MAINBEAMS BETWEEN CROSSMEMBERS
FRONT FIXED RAMPS - MINI	STEEL W/ TRACTION BARS THAT WILL NOT INTERFERE WITH THE FLIP
FRAME REINFORCEMENT	FOR A 3+3 (14'-1" SPREAD)
TOP FLANGE REINFORCEMENT	OUTSIDE OF OUTER BEAMS ONLY
BUCKET TROUGH	LAST 3 CROSSMEMBERS OF DECK
BUCKET TROUGH	NO PLATE
HYDRAULIC SYSTEM	REMOVABLE 13HP HONDA POWER PACK WITH DUAL OPERATIONS AND ALUMINUM HINGED AND LOCKABLE COVER (FULL LENGTH)
BRASS FITTINGS	ON COMPLETE CONFIGURATION
22' GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/ VERTICAL AIR LOCK PIN
SWING CLEARANCE	216", 120", AND 108" WITH 96" HYDRAULIC FLIP-UP GOOSENECK EXTENSION
FIFTH WHEEL HEIGHT (50" LOADED)	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)
1/8" SMOOTH ALUMINUM TOP COVER	OVER GOOSENECK AREA
GOOSENECK LIGHT BAR	(2) CLEAR WORK LIGHTS AND (2) RED TAIL LIGHTS AT REAR OF GOOSENECK
SMOOTH ALUMINUM HINGED AND LOCKABLE COVER	AT REAR OF GOOSENECK
CHAIN AND BINDER RACK	W/ BASE PLATE AT REAR OF GOOSENECK
AIR BRAKES	16.5" X 7" W/ AUTO SLACKS & OUTBOARD DRUMS
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)
SPRING BRAKES	ON 1ST AND 2ND AXLE
AXLES	(3) 30,000# 3/4" WALL W/ 23,000# BRAKES
TIRES	(12) 275/70R22.5 (H)
ACCURIDE ALUMINUM WHEELS	EXTRA POLISHED OUTERS, STANDARD POLISHED INNERS
SUSPENSION	30,000# AIR RIDE W/ 60.5" AXLE SPACING
LIQUID FILLED AIR GAUGE	W/ CHART
SUSPENSION	AIR LIFT 3RD AXLE ONLY
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL
RAISING AND LOWERING VALVE	AT REAR OF TRAILER



LIGHTS	L.E.D. RUBBER SEALED SYSTEM
ADDITIONAL MID TURN SIGNAL	(1) PER SIDE OF DECK
ADDITIONAL AMBER CLEARANCE LIGHTS	(3) PAIRS ON THE SIDE OF THE MAIN GOOSENECK
ADDITIONAL AMBER CLEARANCE LIGHTS	(3) PAIRS ON THE SIDE OF THE GOOSENECK FLIP EXTENSION
ADDITIONAL AMBER CLEARANCE LIGHTS	(4) PAIRS ON EACH SIDE OF DECK
AMBER L.E.D. STROBES	IN 3RD TAIL LIGHT POSITION W/ SWITCH
BATTERY BACK-UP	W/ RECHARGEABLE FEATURE
LASH RINGS	(40) TOTAL, 17-PER SIDE, BENT STYLE, 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1-EACH BOLSTER END FLAT STYLE
ADDITIONAL FLAT STYLE LASH RINGS	(1) ON TOP OF REAR SECTION MAIN FLANGE IN FRONT OF THE TOP LUGS
ADDITIONAL FLAT STYLE LASH RINGS	(1) ON TOP OF REAR SECTION MAIN FLANGE
ADDITIONAL FLAT STYLE LASH RINGS	(1) PER SIDE HALFWAY UP OF THE TRANSITION AREA ON THE MAIN BEAM FLANGES
ADDITIONAL FLAT STYLE LASH RINGS	(1) PER SIDE ON THE INSIDE MAIN BEAM WEBS THE FIRST 10' OF DECK
ADDITIONAL FLAT STYLE LASH RINGS	(1) PER SIDE ON THE INSIDE MAIN BEAM WEBS THE LAST 10' OF DECK
ADDITIONAL FLAT STYLE LASH RINGS	(2) IN RECESSED BUCKET TROUGH AREA AT REAR OF DECK.
ADDITIONAL FLAT STYLE LASH RINGS	(2) ON TOP OF THE 2ND AND 3RD DROPPED CROSSMEMBERS IN REAR BOOMWELL AREA
EXTENSION BRACKETS (OUTRIGGERS)	12" SWING/REMOVABLE WITH DOUBLE HOOK-ON FRONT. "FULL LENGTH" OF DECK
DECKING	2" APITONG (OUTSIDE MAIN BEAMS ONLY)
DECKING SECUREMENT	WITH CARRIAGE BOLTS AND FLOOR CLIPS
PAINT	GLOSS BLACK (2-PART URETHANE) STEEL PARTS TO MATCH PAINT COLOR (PAINT PERIMETER ONLY FRONT & WEBS OF GN & EXT, DECK WEBS, END OF BOLSTERS, AND REAR LIGHT PANEL WEBS). REF Q33200
HOT DIP GALVANIZE	ENTIRE TRAILER (PAINT), GOOSENECK, DECK AND REAR SECTION ONLY
BOOMWELL	OPEN BOTTOM W/EXTRA LOW 1ST CROSSMEMBER (NO COVER PLATE)
TRACTION BARS	ON FRONT & REAR SLOPES
CHAIN HOOKS & FLAG HOLDER SLOTS	ON BOLSTERS
FLAG HOLDER W/ THUMB SCREWS	1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL
AIR AND ELECTRICAL CONNECTIONS	FOR FLIP/REMOVABLE AXLES
OVERSIZE LOAD SIGN	REMOVABLE, (INCLUDES BRACKETS ON FLIP/REMOVABLE AXLE AND/OR BOOSTER IF APPLICABLE)
PLASTIC WHEEL WELL COVERS	INDIVIDUALS OVER TIRES ONLY, BOLT-ON (REF Q33200)
ALUMINUM STORAGE BASKETS BOLT-IN	(2) FRONT OF DECK, (2) AT REAR OF DECK
INTEGRAL SINGLE STEERABLE AXLE HYDRAULIC BOOSTER	9'-0" WIDE, (1) 30,000# 3/4" WALL W/ 23,000# BRAKES, (4) 275/70R22.5 (H) TIRES, ACCURIDE ALUMINUM WHEELS (EXTRA POLISHED OUTERS, STANDARD POLISHED OUTERS), 30,000# AXLE SUSPENSION, RAISING AND LOWERING VALVE, AMBER L.E.D. STROBES IN 3RD TAIL LIGHT POSITION, BATTERY BACK-UP WITH RECHARGEABLE FEATURE, LIQUID FILLED AIR GAUGE, 5HP POWER PACK, PLASTIC WHEEL WELL COVERS (REF Q33200), HOT DIP GALVANIZE, FLAG HOLDERS WITH THUMB HOLDER, EARS AND LUGS FOR ADDITIONAL AXLES, SET-UP FOR 2 ADDITIONAL AXLES



INTERMEDIATE STEERABLE FLIP/REMOVABLE AXLE (5TH AXLE)	9'-0" WIDE, (1) 30,000# 3/4" WALL W/ 23,000# BRAKES, (4) 275/70R22.5 (H) TIRES, ACCURIDE ALUMINUM WHEELS (EXTRA POLISHED OUTERS, STANDARD POLISHED OUTERS), 30,000# AXLE SUSPENSION, RAISING AND LOWERING VALVE, AMBER L.E.D. STROBES IN 3RD TAIL LIGHT POSITION, BATTERY BACK-UP WITH RECHARGEABLE FEATURE, LIQUID FILLED AIR GAUGE, PLASTIC WHEEL WELL COVERS (REF Q33200), HOT DIP GALVANIZE, FLAG HOLDERS WITH THUMB HOLDER, EARS AND LUGS FOR ADDITIONAL AXLES
FLIP/REMOVABLE AXLE (6TH AXLE)	9'-0" WIDE, (1) 30,000# 3/4" WALL W/ 23,000# BRAKES, (4) 275/70R22.5 (H) TIRES, ACCURIDE ALUMINUM WHEELS (EXTRA POLISHED OUTERS, STANDARD POLISHED OUTERS), 30,000# AXLE SUSPENSION, RAISING AND LOWERING VALVE, AMBER L.E.D. STROBES IN 3RD TAIL LIGHT POSITION, BATTERY BACK-UP WITH RECHARGEABLE FEATURE, LIQUID FILLED AIR GAUGE, PLASTIC WHEEL WELL COVERS (REF Q33200), HOT DIP GALVANIZE, FLAG HOLDERS WITH THUMB HOLDER
FLAT FLOOR DECK	PLATFORM WIDTH: 9'-0", PLATFORM LENGTH 30', RIDE HEIGHT: 18"/6", CAPACITY 80 TONS IN ANY 16', LASH RINGS FULL LENGTH OF DECK. HOT DIP GALVANIZED. LIGHTS AND MID-TURN WOULD MATCH THE DROPSIDE DECK.
BEAM DECK	PLATFORM WIDTH: 56", PLATFORM LENGTH 30', RIDE HEIGHT: 26"/6", CAPACITY 80 TONS IN ANY 16', LASH RINGS FULL LENGTH OF DECK. HOT DIP GALVANIZED. LIGHTS AND MID-TURN WOULD MATCH THE DROPSIDE DECK.

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.