



A037407

VIN: S036123



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER HALF ROUND END DUMP THRS (FRAMELESS) *** sloped, non HD tandem air ride ***
DIMENSION	FRAMELESS 40' WITH 76" SIDES (capacity of 66.1 cubic yards)
LENGTH	40' WITH 76" SIDES
WIDTH	102"
HEIGHT	76"
COUPLER HEIGHT	48"
CHASSIS	1/4" AR450 steel bogie pod, with aluminum cover plates
BULKHEAD	CPS, Sloped with inside cylinder assembly. 3/16" AR450 steel. Ref 212561
FIFTH WHEEL	Oscillating coupler plate
KING PIN LOCATION	15" (standard)
GATE STYLE	76" HRS Barn door assembly kit 3/16" AR450 Hardox 3 panel design
SIDE MATERIAL	1/4" AR450 steel
FLOOR MATERIAL	1/4" AR450 steel
TOP RAIL	10" X 4" X 1/4" High strength steel with integral shedder
LONGITUDINAL	1/4" formed steel to middle brace
BODY BRACES	1/4" High strength steel internally stiffened
DRAFT ARM	6" X 4" X 3/16" 70W steel tube
HOIST	8" diameter-5 Stage inverted trunnion mount
LADDERS	1" X 10' hydraulic hose with 1 1/4" female butterfly fitting (1) Front (1) Rear, driver side
MAIN SYSTEM	LED Wiring harness - Custom fit and fully sealed
FRONT CONNECTOR	7 way (SAE J560)
MID-FLASHERS	One lamp including side marker and flasher, each side at middle point, amber.
TAIL LIGHTS	Mounted with stainless steel rivet rings (to secure lights when dumping load)
LANDING GEAR	Jost 2-speed landing gear Mounted with tubular supports
AXLE QTY	Tandem
AXLES	Hub piloted 25K axles : 1ABS 1NON ABS 5" tubular with HN spindle
SUSPENSION	Tandem air ride
TRACK	77.5" (102" width)
BRAKES	16 1/2" X 7" cam brakes
BEARINGS	HM 218248 and HM 212049
SLACK ADJUSTERS	TSE,S-ASA, automatic, 28 splines
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30)
TIRE SIZE	24.5 Hub Piloted (plant choice radials)
EXTERIOR WHEEL	11R24.5 16PLY W/STEEL WHEEL



ITEM	DESCRIPTION
INTERIOR WHEEL	11R24.5 16PLY W/STEEL WHEEL
GATE CONTROL AIR VALVES (ABS)	Manual hand control 2S1M Tandem
FINISHING (PAINT)	Shot blasted, acid based wash with rust inhibitive rinse. One coat of epoxy primer and one coat polyurethane top coat. Color: Black
REFLECTIVE TAPE	Conspicuity striping in compliance with FMVSS/ CMVSS 108. Gray and red each side, fully across rear gate and mudflap brackets.
LOGOS	MANAC insignia ILO of CPS
ADDITIONAL OPTIONS REAR FENDERS MUD FLAPS	estimated weight is 22,460 LBS +/- 3% Steel, Bolt-on, with rubber cushion Mounted to gate for clearance when dumping
CONFIRMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.
DISCLAIMER Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.	