



A037641
VIN: 242370



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER HALF ROUND END DUMP THRS (FRAMELESS) *** sloped, HD, single point ***
DIMENSION	FRAMELESS 40' WITH 100" SIDES (capacity of 87 cubic yards)
LENGTH	40'-0" Half round end dump TSHR (Frameless)
WIDTH	102"
HEIGHT	100"
COUPLER HEIGHT	48"
CHASSIS	1/4" AR450 steel bogie pod, with aluminum cover plates
BULKHEAD	CPS, Sloped with inside cylinder assembly. 3/16" AR450 steel. Ref 242368.
FIFTH WHEEL	Oscillating coupler plate
KING PIN LOCATION	15" (standard)
GATE STYLE	100" Barn door assembly, 3/16" AR450 Hardox 3 panel design -- Side swing with chain locks
SIDE MATERIAL	1/4" AR450 steel
FLOOR MATERIAL	1/4" AR450 steel
TOP RAIL	10" X 4" X 1/4" High strength steel with integral shedder
LONGITUDINAL	1/4" formed steel to middle brace
BODY BRACES	1/4" High strength steel internally stiffened
DRAFT ARM	6" X 4" X 3/16" 70W steel tube
HOIST	8" diameter-5 Stage inverted trunnion mount 1" X 10' hydraulic hose with 1 1/4" female butterfly fitting
LADDERS	(1) Front (1) Rear, driver side
BODY BRACES	CPS, Additional channel ribs ***2 per side between body braces*** connected to top rail
TARPING SYSTEM	
TARP BRAND	CPS, Aero tarp, electric, flip (Aero 595 HD Easy Cover)
TARP STYLE	*** tarp straps to be added *** ref: 212561
MAIN SYSTEM	LED Wiring harness - Custom fit and fully sealed
FRONT CONNECTOR	7 way (SAE J560)
MID-FLASHERS	One lamp including side marker and flasher, each side at middle point, amber.
TAIL LIGHTS	Mounted with stainless steel rivet rings (to secure lights when dumping load)
LANDING GEAR	Jost 2-speed landing gear Mounted with tubular supports
AXLE QTY	Tandem
AXLES	Hub piloted 25K axles : 1ABS 1NON ABS 5" tubular with HN spindle
SUSPENSION	Single point suspension
TRACK	77.5" (102" width)
BRAKES	16 1/2" X 7" cam brakes



ITEM	DESCRIPTION
BEARINGS	HM 218248 and HM 212049
SLACK ADJUSTERS	TSE,S-ASA, automatic, 28 splines
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90
BRAKE CHAMBERS	T.S.E. brake, "Omni brake" (30-30)
TIRE SIZE	24.5 Hub Piloted (plant choice radials)
EXTERIOR WHEEL	11R24.5 16PLY W/STEEL WHEEL
INTERIOR WHEEL	11R24.5 16PLY W/STEEL WHEEL
GATE CONTROL	Manual hand control
AIR VALVES (ABS)	2S1M Tandem
FINISHING (PAINT)	Shot blasted, acid based wash with rust inhibitive rinse. One coat of epoxy primer and one coat polyurethane top coat. Color: Black
REFLECTIVE TAPE	Conspicuity striping in compliance with FMVSS/ CMVSS 108.
LOGOS	Gray and red each side, fully across rear gate and mudflap brackets. MANAC insignia ILO of CPS
ADDITIONAL OPTIONS	estimated weight is 23,689 LBS +/- 3%
REAR FENDERS	Steel, Bolt-on, with rubber cushion
MUD FLAPS	Mounted to gate for clearance when dumping
ANNEX(ES) ATTACHED	
R	ref; 242368.
CONFIRMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.
DISCLAIMER	
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.	
Equipment availability, prices and specifications are subject to change without notice.	