



A038643-A038644
VIN: S037337-S037338



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

SLB85E95

Low Bed Exterior Beams

General:

Length: 53'
Width: 102"
Deck Height: 14" (With 4" ground clearance)
Spread: 60"

Frame:

- Fabricated boxed Beams with T-1 HTS steel
- Hooks for gooseneck hook up
- Horizontal pin joint between tail and deck
- Outside frame gooseneck
- Extendible gooseneck
- Extendible 26' to 44' outside beam deck

Running Gear:

- Hendrickson HT-300 air ride
- Axles rated at 23,000 lbs capacity with D22 spindle ends
- Dust shield and cam enclosure.
- Brake size 12.25 x 8 non-asbestos Q brake
- Stemco Guardian HP oil seal
- Stemco cups and bearings
- Dura light 8 studs steel piloted hubs with cast drum
- Alum. wheels 17.5 x 6.5 machine finish
- Tires 245/70R17.5
- Rockwell Wabco brake system comply with FMVSS 121
- TSE brake chambers 30-30
- Automatic slack adjuster
- Scale-o-matic liquid fill gauge with manual dump valve

Electrical system:

- LED sealed beam installed as per FMVSS 108
- 7 Way receptacle with 7 wire main cable
- Junction box Scepter sealed

- Extendable strobe Lights on gooseneck and tail

Paint:

- All steel components are steel shot blasted for prep
- Epoxy primer
- 2 Coats of urethane paint
- Metalized

Other:

- Chain on axles
- Power Pack on gooseneck (for gooseneck detach)
- Height override valve on tail section

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.