





A039310

VIN: AN06228

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Baltimore, MD: 888-601-7500 Concord, NC: 800-438-2250 Delmar, DE: 866-486-1400 Des Moines, IA: 888-673-5011 Elkton, MD: 800-544-7127 Jacksonville, FL: 800-828-3055	Little Rock, AR: 833-424-8944 Portland, ME: 800-325-4253 Raleigh, NC: 833-418-9777 Scranton, PA: 800-569-1400 Springfield, MA: 800-854-5306 Voorhees, NJ: 866-315-0235 Walpole, MA: 800-854-5310
---	--

haletrailer.com | @haletrailer







800-232-6535 *FINANCING AVAILABLE

Quote number: 55006

Model: Gooseneck assembly

Capacity in tons: 55

1. GOOSENECK

Gooseneck design
 Loaded 5th wheel height
 Swing radius
 Alternate kingpin
 Support cylinder
 Power source
 Gooseneck locks
 Electrical receptacle
 Additional gooseneck specifications

Ratchet
 55" With 3" welded hat box for 52" loaded 5th wheel height.
 108"
 Removable kingpin stations for 108" and 90" swing radius
 Hydraulically operated
 Hydraulic couplings: 3/4" fixed at front of gooseneck
 Ratchet
 Seven pin connector
 1) Formed aluminum diamond plate light bar mounted in gooseneck base with four (4) LED stop/tail/turn lights and two (2) clear work lights wired to marker light circuit with on/off switch
 2) Fully enclosed chain bar in gooseneck base with aluminum diamond plate and hinged lockable lid (paddle latches)
 3) Full penetration weld on gooseneck gusset
 4) Base pivot tube reinforcement
 5) Aluminum cover plate

2. DECK

Gooseneck/deck connection

Pin and plate with remote lock

4. GENERAL

Lights and wiring
 Paint
 Lash rings
 Compatibility
 Additional general specifications

12 volt system
 Standard Talbert red, R-Cure 800 series paint
 1 each side of gooseneck (bent style), 2 total
 Compatible with customers existing SN33676
 None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.