



A039716
VIN: 154241



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, TELESCOPIC STEEL DROP PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	72'-0" open.
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61" high at front and 39" at the bumper.
DROP HEIGHT	20", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	5/16", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, exterior, 3/8" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high and 16 1/2" above suspension.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	12 1/4" high, 48" straight behind king pin.
CROSSMEMBERS	1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel.
FLOOR	16" center to center in gooseneck and the remaining 12" c/c.
FLOOR FASTENING	Aptitong, 1 1/8" thick shiplap finished, no preservative.
SIDE RAILS	Two screws per board at each crossmember.
SIDE BOXES	6" channel @ 8.2 lbs/ft.
RUB RAILS	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high.
CORNERS	(USA Dimensions).
FENDERS	3/8" x 2 1/2" shaped steel.
DIAGONAL BRACES	Bevelled.
LOCKS	Over tires at rear, checker plate 1/8".
ROLLERS	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
SPACERS FOR RUB RAILS	Air operated with a third glad hand at front.
ENDS	4, 2 on female sections of frames and 2 on male sections.
FRONT RAIL	Double between side boxes.
BUMPER	
PULL PLATE	9 gauge formed steel.
REAR RAIL	CMVSS 223-RIG approved (in accordance with Canada & USA regulations).
ELECTRICAL	Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
FRONT CONNECTOR	Pull plates between uprights of bumper.
ELECTRICAL SYSTEM	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.



ITEM	DESCRIPTION
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams Grote, tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400.
TURN SIGNAL	Sealed beams LED, (Grote #54163), one lamp including side marker and flasher, each side at middle point, amber.
REAR ADD. CONNECTOR	4 way.
LANDING GEAR	Holland, Mark V (LGS-4F115).
SAND SHOES	10" x 11 1/2".
CRANK	Road side.
BOGIE	
BASIC SUSPENSION	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-250US (6.5), tridem, 60" spread.
U-BOLTS	With nuts at bottom.
SPRINGS	Air.
AXLE(S)	AXN, TA250T, 22 500 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None (AXN).
BRAKES	16 1/2" standard, AXN R23 extended life lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	Meritor, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omni brake" (30-30).
HUBS AND DRUMS	10 studs disc hubs, outboard mount, 285.75mm B.C., single flange nuts.
	For dual steel wheels or single wheels.
RIMS	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Continental, 255/70 R 22.5 HSR2 SA 16 ply (36.6")
AIR SYSTEM	
GLAD HANDS	Fixed.
AIR VALVES	Meritor Wabco, ABS, 2 sensors 1 modulator.
VALVE(S)	Fast-brake kit.
VALVE	Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table.
DIAGNOSTIC CABLE	not included with ABS valve.
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
SLIDING TRACK	Full length, "LL" extruded aluminum, road side.
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.
EXTRA MUD FLAPS	Qty: 2, rubber.
	Located: 1 at front of landing gear in between main frames, to protect roller and 1 at front of suspension in between main frames, to protect air boosters.



ITEM	DESCRIPTION
FINISHING PAINT	Shot blasted, one coat of epoxy primer and two acrylic urethane top coats, Color: black, code: U-TECH RM 99U.
HUBS	Black.
WHEELS OR RIMS	White.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear sill and horizontal underride protection bar.

ADDITIONAL OPTIONS	SAME AS U#154243
--------------------	------------------

DISCLAIMER
Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.