



A040072
VIN: 33839

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: 3RD Intermediate Axle

Capacity in tons: 55

3. REAR BRIDGE

Width	8'-6"
Loaded rear bridge height	41" Mainbeams; 37" Bolsters
Number of axles	1
Axle spacing	60"
Axle capacity	25,000# GAWR = 24,700#
Brakes	16-1/2" x 7" air actuated with spring brakes on one axle
Anti-lock brake system	None required - GVWR is greater than 120,000#
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel, with outer aluminum wheels DURA BRITE
Tires	Four (4) 275/70R22.5 (H) 16PR radials
Suspension	Ridewell air SN 33839, flip-up and removable
	NOTE: Axle can be used as the 3rd axle in a 3+1 spread
Air Lift	None
Suspension options	Override chains
Rear half bolster	Yes
Connections for future removable axle	Connections at rear of axle for future 4th axle or 3+1 spread

4. GENERAL

Lights and wiring	12 volt LED system including mid-turn lights, license plate light regular 2 strobe lights at rear with switch
Paint	Standard Talbert black
Lash rings	2 Total 2 at rear of axle (bent style), 2 total
Additional general specifications	Reinforced for future East Coast style axle extension for 3 + 1 spread axle capability providing a 14'-1" spread

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.