

HALE

TRAILER

BRAKE & WHEEL



A041087
VIN: 072421

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

Trailer Model: **VersaMAXX** *Extendable 53 Feet to 58 Feet Model*

VersaMAXX	Extendable 53 Feet to 58 Feet Model	Standard Equipment
Net Capacity: 50 tons concentrated in 16 feet Nominal: OAL 53 feet Closed to 58 feet Open 8 feet 6 inches Wide GOOSENECK: Hydraulic Detachable Gooseneck 5 Position Adjustable Neck 50" Loaded 5th Wheel Height, 15" Setting, 2" King pin Narrow neck, Chain storage rack under gooseneck 2" King Pin 84" Swing Radius PTO powered: two main & one lift arm cylinders Hydraulic Controls in a separate covered box Front lugs provisioned for flip neck Hydraulic connection on the side of neck for winching operation DECK: Nominal Deck Length: 22.5 feet Closed to 27.5 feet Open Loaded Deck Height: 22 in 6 in Loaded Ground Clearance 4 Beam design - 100,000 psi yield flanges & 80,000 web minimum All 4 Beams same height & Beams are tapered like Paver Models I-Beam Cross members on (approx.) 24" Centers Junior I-Beam Cross members alternating - Outside bay only 1.5" Nominal Apitong Decking - Full Width, Secured by Floor Screws D Rings: 14 Pairs(6 Deck, 1 Bolster, 1 Rear CM, 3 Porch, 1 Trans.) Tie Downs & Chain Slots : Top Flange Outer beams 24" centers Outriggers: 10 Pair Swing out + 1 Pair Heavy duty hook on at front Front Flip Ramps (removable) for loading Two 6 ft AL. Bus Ramps (Front/Rear Lugs included), Stored on neck	REAR SECTION: Rear Deck 19 ft 7 in, Open Boom trough, brackets for Oversize Load Sign Axles: Three 5" round, 5/8" wall 25000# nominal capacity Suspension: Ridewell or Equivalent air ride with Oil Seals 60" axle spacing, Open wheel wells, axle chains with cut off valves Rear axle equipped with air lift, Auto Slack Adjusters 12-1/4" x 7-1/2" Air, Parking Brakes 1st & 2nd Axles, ABS: 2S1M Hub: 8 Stud, Hub Piloted, Long studs, Cast Drums 235/75R17.5, 16PR (Low Profile) radial tires Aluminum Outer & Steel Inner Wheels Tire inflation system 5 position ride height control with dump valve & Air Gauge Air Ride Suspension With 5 Position Ride Height 10 Apitong riser boards installed on bolsters & porch GENERAL: 12V System with 7 way, Modular Harness, LED Sealed Beam Lights Strobe light package with toggle switch on rear Epoxy Primer & Black Polyurethane Paint Flag and Flag Holders - 2 Pairs - front deck and rear of trailer Mid-Turn Signal/Clearance Light Tool Tray: 4' expanded metal at front of deck (approx.) Red & White Conspicuity tape and KS Mud Flaps Winch: Two 20,000 lb. planetary hydraulic on neck & rear deck 100' of 5/8" wire rope & shackle, fairing rollers & cable tensioner Four function wireless remote (controls both winches) LED-Work lights on both winches with covered toggle switch Battery Back-up w/ charger on rear for disconnected neck operation	

Models **Extendable 53' to 58' Model**

VersaMAXX Optional Equipment

Estimated Weight of the Equipment with the options : **25,100**

± 3% For trailers other than standard specification, weight and dimensional drawing will be provided by plant after order is received and accepted.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.