

HALE

TRAILER

BRAKE & WHEEL

A041088
VIN: PP2323



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

LB35-33CS | Fixed Neck Trailer

Fixed Neck 35 Ton Capacity with 33" Loaded Deck Height, Sloped Ramp

Gooseneck	Fixed Neck To Deck Connection, Full Width Wood Filled Top Deck, Full Width 21 Deg Steel Smooth Plate, Wood Filled Between Main Beams With Loading Slope And Traction Bars 84" Swing Radius, Landing Gear - Two Speed - 50,000 Lbs. Toolbox In Front Of Neck
Gooseneck Transition	Full Width 21 Deg Steel Smooth Plate With Traction Bars, Wood Between The Main Beams
King Pin Height	48"
King Pin Setting	18"
Swing Clearance	84"
King Pin Plate	5/16 Plate
Landing Gear	Two Speed - 50,000 Lbs.
Main Deck	Main Longitudinal Members 16" Fabricated With Positive Camber With 12" Side Rails Level Deck Design 8" I-Beam Crossmembers 1 1/2" Nominal Apitong Decking, Flat Deck Design With Beavertail And Ramp Off The Rear.
Loaded Deck Height	33" (Ground Clearance 17")
Deck Length	26'
Main Deck Flooring	Covered 1 1/2" Nominal Apitong
Deck Width	8'6" Wide
Widening Brackets	None
Dovetail	4' Steel With Traction Bars
Rear Loading Ramps	Hydraulic 96" X 36" Wood Filled (Self-Contained Electric Over Hydraulic Pump. Requires A Dedicated Two Pole 2 Gauge Cable From The Truck)
Axles	(2) Heavy-Duty Axles 22,500 Lbs. Nominal Capacity Per Axle (GAWR Determined By Suspension Type, Brakes, Tires And Other Components), Tapered Spindle Axles, Hub-Piloted 8-Long Stud Mount, Outboard Cast Drums, Auto Slack Adjuster, ABS.
Axle Spacing	49"
Suspension	Heavy Duty Mechanical Steel Leaf Spring
Brakes	12 1/4" X 7 1/2", Heavy-Duty Brake Drums, Outboard Mount, Automatic Slack Adjusters, Type 30/30 Parking Brakes On (2) Axles
Tires	235/75R 17.5 H-Ply Tires
Wheels	(8) Steel Disc Wheels 6.75 X 17.5
Wheel Wells	Covered W/ Steel Plate & Traction Bars
Electrical	Fully Sealed Wiring Harness With LED Lights, Marker Lights And Mid-Turn Signals, (3) Oval Stop, Tail And Turn Lights Per Side On Rear
Strobe	No Amber Strobes

Protective Coating

Metal Prep	White Blasted And Cleaned Prior To Painting
Primer	PPG 2-Part Primer
Paint	2-Part PPG Black Acrylic Urethane

Miscellaneous

Load Securement	16 Bent D' Rings
------------------------	------------------

Weight: 14,475 lbs
| Length: 45' 0"

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.