

HALE

TRAILER

BRAKE & WHEEL



A041095
VIN: 23407

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 800-232-6535
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

FLOOR		
LOAD PROFILE	MATERIAL, 117 GVWR	SET UP FOR NYS 117,000# PERMIT
LENGTH	36 ft .0 in.	
WIDTH		SERIAL NO. 5MADA3643CC023407
FLOOR	STD. 1/4" FULL	MODEL NO. QDAR36AA660-2012
CROSSMEMBER SPACING	12 W/RUBBER CUSHION RIDE	WEIGHT 16718 lb. +/- 3%, 56 yds.
TOW MOTOR PACKAGE		
FLOOR CHAIN TIE DOWNS		
COIL RACK ANGLES		
STUB LONGITUDINALS		
I-BEAM WIDTH	5 in. BEAM 50in. WIDTH	
C.B. FLOOR BRACING		
FLOOR LINER	AMERICAN MADE UHMW 3/8" X 10' "REPRO"	
FLAPS, REAR AXLE	FULL ACROSS	
FLAPS, FRONT AXLE(S)	FLAP FRONT OF FRONT TIRES	
LOAD LEVEL INDICATOR		
BODY HOLD DOWN		
VIBRATOR	NONE	
RUBBER SEAL		
WIDE STANCE 2-3/4" REAR PIN		
SIDES		
WALL HEIGHT		
PANEL TYPE	(10) - LT. VERT. (21) - STD. VERT. (10) - HVY. VERT.	(10) - LT (20) - STD (10) - HVY
PANEL SELECTION		
TOP RAIL OPTION	SOLID, TOTAL OF 66	
REAR POCKET SLOPE	2 3/4	
REAR POCKET HEIGHT	76 1/4 in.	
TARP BAR	NONE	
WALL LINER	NONE	
BULKHEAD		
REMOTE GREASE/BLEEDER	REMOTE HOIST BLEEDER & GREASE	
BULKHEAD HEIGHT	72 7/8 in.	
BULKHEAD TAPER	2 1/2 in.	
BULKHEAD OPTIONS	NONE	
BULKHEAD TYPE	RADIUS CORNERS	
BULKHEAD SLOPE PLATES	NO	
LOWER BULKHEAD WRAP		
DOGHOUSE STYLE	OVERSIZED	
DRIVER'S SIDE PANEL STEPS	BULKHEAD DOOR	ALSO REAR GATE STEPS AND INSIDE 2 STEPS SAME HEIGHT AS TOP OUTSIDE
	NONE	REAR SEE VIN 16811
	NONE	
TARP HOOKS		
TARP BASKET		
SHOVEL HANGER		
FENDERS & DEFLECTORS	NONE	
ALUMINUM ROLL CAP		
LIGHTS		
LIGHT TYPE	GROTE L.E.D. W/ GROMMET	SAME SET UP AS 16811
LIGHT PANEL	5 LARGE-3 LARGE-5 LARGE (FULL LIGHT PANEL)	
LIGHT SHIELD/APRON	(STANDARD) 1-1/2" FULL LIGHT SHIELD	
MARKER LIGHTS	7 EACH SIDE TOP & BOTTOM	
MIDTURNS		
BACK-UP LIGHTS	1 PAIR L.E.D. BACK UP LIGHTS	WIRED TO AUX PLUG
REAR POCKET LIGHTS	3 PAIR OVAL	SAME 16811 EVENLY SPACED
AUXILIARY CABLE (4 OR 7 WAY)	7 WAY (ISO)	
GATE		
GATE HEIGHT	67 3/8 in.	NOTE: ON PREVIOUS UNIT 16811 GATE HEIGHT SHOWED 67- 3/8"
GATE WIDTH	94	
GATE PANEL TYPE	STANDARD (3) VOID	
GATE OPERATION	ELECTRIC ON AUXILIARY / BALL VALVE	
HINGE TYPE	O. S. SWING C.S. (NO GROUND CONTROL)	
COAL DOOR	12"	
CHUTE	NONE	
DOUBLE HANDLE DOOR		
PUSHER BLOCK		
1/2 ROUND (SEAL) ON GATE		
ANGLE ON TOP OF GATE		NOTE: STEPS ON REAR GATE CLOSE TO DRIVERS SIDE SAME AS 16811
SPREADER CHAINS		
WINDERS / SAFETY LATCH	WINDERS (1) EACH SIDE	
GATE LINER		

CHASSIS		
MODEL	QUAD	
FRAME RAILS	17" ALUMINUM BEAMS W/RUBBER CUSHION RIDE	
NECK STYLE	24 in. GOOSENECK, 9.125 I.O. in. HEIGHT	
REAR OVERHANG	6 in.	SET REAR HEND. INTRAAX AA 300T AT A RIDE HEIGHT OF 16-5/8"
FRAME LENGTH	37 ft.-6 in.	THIS WILL ALLOW FOR THE LIFT SUSP. TO RIGHT PROPERLY
FRAME WIDTH	42 in.	
PIN SETTING	0.5 KP, 18 SETTING	
5th WHEEL PLATE	1/2 x 42 x 71 @49 in HIGH	
HOIST & MOUNT STYLE	3 X 6 X 3/8 INCH, 50 in. HOIST PIN SETTING	
PIN TO AXLE SETTING	412, 20 REAR SETTING	
SUSPENSION	HEND. INTRAAX AA-300 TP	25K AXLES
SPRINGS	AIR	
AXLE SPACING	52 in.	
SUSPENSION CONTROL	ELECTRIC ON AUXILIARY / BALL VALVE	
AXLES	(3) AXLE FOR INTRAAX ONLY	25K AXLES
ABS	4S/2M - SINGLE POINTS - (MERITOR / WABCO)	ABS ALL 3 DOWN AXLES
BRAKE SHOES	7" XL, W/30-30 CHAMBERS	
SLACKS	STANDARD (GUNITE)	
CAM GUARDS (ALL AXLES)	STANDARD	
TIRES	(12) CONTINENTAL HSR 11R 24.5 16 PLY	
TIRE INFLATION SYSTEM	NONE	
RIM TYPE (PER AXLE)	ALCOA HP 24.5X8.25 10 HOLE 2 MIL 2 POL DURA-BRITE	
HUB AND DRUM	(6) CENT W/DURA L HUB. HP OB 10 STUD TP, LS, 7"	
SYNTHETIC LUBRICATION	NO	
HUBODOMETER	NONE	
DUST COVERS	YES	
TIRE CARRIER	NONE	
DOLLIES	(STD.) JOST A440 - 5 YEAR NO LUBE - D.S.	
AIR GAUGE/SYSTEM	YES, IN FRONT	
AIR TANKS	12" STEEL AIR TANKS (STANDARD)	
TOW/PINTLE HOOKS	(2) TWO IN POCKET	
HYD. HOSE FITTING	1" X 108" HOSE W/WING FITTING	
ENCLOSURE FOR SWITCHES	STAINLESS STEEL W/F.W.V. & SWITCHES	
HYDRAULIC TANK	NONE	
SQUARED OFF CHASSIS REAR	NO	
BUMPER	NONE	
LIFT AXLE		
TYPE	WATSON STL 2095, STL. HUB, STL. DRUM (NLR)(NAR)(WRLO)	
NO. OF LIFT AXLES	1	
LIFT KIT	(1) SEE NOTES	INCLUDED WITH WATSON
AXLE	SEE NOTES	INCLUDED WITH WATSON
TIRES	(2) MICHELIN XZUS 315/80R 22.5 S.S. (9")	
RIM TYPE (PER AXLE)	ALCOA 22.5X9 SUPER SINGLE POL DURA-BRITE	
HUB AND DRUM	(2) SEE NOTES	INCLUDED WITH WATSON
BRAKE SHOES	7, W/30 CHAMBERS	
CONTROLS	ELEC. UP ON AUX. / BALL VALVE (COMMON AIR)	WATSON INCLUDES REVERSE LOCK OUT
DISTANCE	52 in.	SEPARATE REGULATOR FOR STEERABLE
TARP		
TARP MANUFACTURER	NONE	
TARP CONTROL	NONE	
TARP COLOR	NONE	
BOW HOLDERS	NONE	
BOWS	NONE	
PAINT		
CHASSIS COLOR	BLACK	
PIN STRIPING	BLACK	
BOARD COLOR	NONE	
"MAC" LOGOS	MAC BLACK	
OPTIONAL SIGNS	NONE	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.